



Drive Bay 12 x 3.5-inch SATA 66b/s, 36b/s Drive Compatibility 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives Audio Alert On/Off Switch Yes Form Factor 2U Rackmount Host Interface 1 x USB 3.2 Gen 2 Type-C LED Indicators HDD 1-12, Status, Link, Fan error Buttons Power switch Dimensions (HxWxD) 88.6 × 482 × 562.5 mm Weight (Net) 11.03 kg Weight (Gross) 14.29 kg Max. number of HDDs/SSDs supported Hard Drive Type 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives Operating Temperature 0 - 40 °C (32°F - 104°F) Storage Temperature -20 - 70°C (-4°F - 158°F) Relative Humidity 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) Power Supply Unit 250W(x2) PSU, 100 - 240V Power Consumption: Operating Mode, Typical Fan Mode Switch Yes (Auto, high, medium, low) Fan 2 x 70mm, 12VDC System Warning Buzzer	TL-R1200C-RP	
2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives Audio Alert On/Off Switch Yes Form Factor 2U Rackmount Host Interface 1 x USB 3.2 Gen 2 Type-C LED Indicators HDD 1-12, Status, Link, Fan error Buttons Power switch Dimensions (HxWxD) 88.6 × 482 × 562.5 mm Weight (Net) 11.03 kg Weight (Gross) 14.29 kg Max. number of HDDs/SSDs supported Hard Drive Type 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives Operating Temperature 0 - 40 °C (32°F - 104°F) Storage Temperature -20 - 70°C (-4°F - 158°F) Relative Humidity 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) Power Supply Unit 250W(x2) PSU, 100 - 240V Power Consumption: Operating Mode, Typical Fan Mode Switch Yes (Auto, high, medium, low) Fan 2 x 70mm, 12VDC	Drive Bay	12 x 3.5-inch SATA 6Gb/s, 3Gb/s
Form Factor 2U Rackmount Host Interface 1 x USB 3.2 Gen 2 Type-C LED Indicators HDD 1-12, Status, Link, Fan error Buttons Power switch Dimensions (HxWxD) 88.6 × 482 × 562.5 mm Weight (Net) 11.03 kg Weight (Gross) 14.29 kg Max. number of HDDs/SSDs supported Hard Drive Type 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives Operating Temperature 0 - 40 °C (32°F - 104°F) Storage Temperature -20 - 70°C (-4°F - 158°F) Relative Humidity 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) Power Supply Unit 250W(x2) PSU, 100 - 240V Power Consumption: Operating Mode, Typical Fan Mode Switch Yes (Auto, high, medium, low) Fan 2 x 70mm, 12VDC	Drive Compatibility	2.5-inch SATA hard disk drives
Host Interface 1 x USB 3.2 Gen 2 Type-C LED Indicators HDD 1-12, Status, Link, Fan error Buttons Power switch Dimensions (HxWxD) 88.6 × 482 × 562.5 mm Weight (Net) 11.03 kg Weight (Gross) 14.29 kg Max. number of HDDs/SSDs supported Hard Drive Type 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives Operating Temperature 0 - 40 °C (32°F - 104°F) Storage Temperature -20 - 70°C (-4°F - 158°F) Relative Humidity 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) Power Supply Unit 250W(x2) PSU, 100 - 240V Power Consumption: Operating Mode, Typical Fan Mode Switch Yes (Auto, high, medium, low) Fan 2 x 70mm, 12VDC	Audio Alert On/Off Switch	Yes
Buttons Power switch Dimensions (HxWxD) 88.6 × 482 × 562.5 mm Weight (Net) 11.03 kg Weight (Gross) 14.29 kg Max. number of HDDs/SSDs supported Hard Drive Type 3.5-inch SATA hard disk drives 2.5-inch SATA solid state drives Operating Temperature 0 - 40 °C (32°F - 104°F) Storage Temperature -20 - 70°C (-4°F - 158°F) Relative Humidity 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) Power Supply Unit 250W(x2) PSU, 100 - 240V Power Consumption: Operating Mode, Typical Fan Mode Switch Yes (Auto, high, medium, low) Fan 2 x 70mm, 12VDC	Form Factor	2U Rackmount
Buttons Power switch Dimensions (HxWxD) 88.6 × 482 × 562.5 mm Weight (Net) 11.03 kg Weight (Gross) 14.29 kg Max. number of HDDs/SSDs supported Hard Drive Type 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives Operating Temperature 0 - 40 °C (32°F - 104°F) Storage Temperature -20 - 70°C (-4°F - 158°F) Relative Humidity 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) Power Supply Unit 250W(x2) PSU, 100 - 240V Power Consumption: Operating Mode, Typical Fan Mode Switch Yes (Auto, high, medium, low) Fan 2 x 70mm, 12VDC	Host Interface	1 x USB 3.2 Gen 2 Type-C
Dimensions (HxWxD) 88.6 × 482 × 562.5 mm Weight (Net) 11.03 kg Weight (Gross) 14.29 kg Max. number of HDDs/SSDs supported Hard Drive Type 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives Operating Temperature 0 - 40 °C (32°F - 104°F) Storage Temperature -20 - 70°C (-4°F - 158°F) Relative Humidity 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) Power Supply Unit 250W(x2) PSU, 100 - 240V Power Consumption: Operating Mode, Typical Fan Mode Switch Yes (Auto, high, medium, low) Fan 2 x 70mm, 12VDC	LED Indicators	HDD 1-12, Status, Link, Fan error
Weight (Gross) 14.29 kg Max. number of HDDs/SSDs supported Hard Drive Type 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives Operating Temperature 0 - 40 °C (32°F - 104°F) Storage Temperature -20 - 70°C (-4°F - 158°F) Relative Humidity 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) Power Supply Unit 250W(x2) PSU, 100 - 240V Power Consumption: Operating Mode, Typical Fan Mode Switch Yes (Auto, high, medium, low) Fan 2 x 70mm, 12VDC	Buttons	Power switch
Weight (Gross) 14.29 kg Max. number of HDDs/SSDs supported 12 Hard Drive Type 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives Operating Temperature 0 - 40 °C (32°F - 104°F) Storage Temperature -20 - 70°C (-4°F - 158°F) Relative Humidity 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) Power Supply Unit 250W(x2) PSU, 100 - 240V Power Consumption: Operating Mode, Typical 82.26 W Fan Mode Switch Yes (Auto, high, medium, low) Fan 2 x 70mm, 12VDC	Dimensions (HxWxD)	88.6 × 482 × 562.5 mm
Max. number of HDDs/SSDs supported Hard Drive Type 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives Operating Temperature 0 - 40 °C (32°F - 104°F) Storage Temperature -20 - 70°C (-4°F - 158°F) Relative Humidity 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) Power Supply Unit 250W(x2) PSU, 100 - 240V Power Consumption: Operating Mode, Typical Fan Mode Switch Yes (Auto, high, medium, low) Fan 2 x 70mm, 12VDC	Weight (Net)	11.03 kg
HDDs/SSDs supported Hard Drive Type 3.5-inch SATA hard disk drives 2.5-inch SATA solid state drives Operating Temperature 0 - 40 °C (32°F - 104°F) Storage Temperature -20 - 70°C (-4°F - 158°F) Relative Humidity 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) Power Supply Unit 250W(x2) PSU, 100 - 240V Power Consumption: Operating Mode, Typical Fan Mode Switch Yes (Auto, high, medium, low) Fan 2 x 70mm, 12VDC	Weight (Gross)	14.29 kg
2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives Operating Temperature 0 - 40 °C (32°F - 104°F) Storage Temperature -20 - 70°C (-4°F - 158°F) Relative Humidity 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) Power Supply Unit 250W(x2) PSU, 100 - 240V Power Consumption: Operating Mode, Typical Fan Mode Switch Yes (Auto, high, medium, low) Fan 2 x 70mm, 12VDC	Max. number of	12
Storage Temperature -20 - 70°C (-4°F - 158°F) Relative Humidity 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) Power Supply Unit 250W(x2) PSU, 100 - 240V Power Consumption: 82.26 W Operating Mode, Typical Fan Mode Switch Yes (Auto, high, medium, low) Fan 2 x 70mm, 12VDC		
Relative Humidity 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) Power Supply Unit 250W(x2) PSU, 100 - 240V Power Consumption: 82.26 W Operating Mode, Typical Fan Mode Switch Yes (Auto, high, medium, low) Fan 2 x 70mm, 12VDC	HDDs/SSDs supported	3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives
Power Supply Unit 250W(x2) PSU, 100 - 240V Power Consumption: 82.26 W Operating Mode, Typical Fan Mode Switch Yes (Auto, high, medium, low) Fan 2 x 70mm, 12VDC	HDDs/SSDs supported Hard Drive Type	3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Power Consumption: 82.26 W Operating Mode, Typical Fan Mode Switch Yes (Auto, high, medium, low) Fan 2 x 70mm, 12VDC	HDDs/SSDs supported Hard Drive Type Operating Temperature	3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives 0 - 40 °C (32°F - 104°F)
Operating Mode, Typical Fan Mode Switch Yes (Auto, high, medium, low) Fan 2 x 70mm, 12VDC	HDDs/SSDs supported Hard Drive Type Operating Temperature Storage Temperature	3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives 0 - 40 °C (32°F - 104°F) -20 - 70°C (-4°F - 158°F)
Fan 2 x 70mm, 12VDC	HDDs/SSDs supported Hard Drive Type Operating Temperature Storage Temperature Relative Humidity	3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives 0 - 40 °C (32°F - 104°F) -20 - 70°C (-4°F - 158°F) 5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
	HDDs/SSDs supported Hard Drive Type Operating Temperature Storage Temperature Relative Humidity Power Supply Unit Power Consumption:	3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives 0 - 40 °C (32°F - 104°F) -20 - 70°C (-4°F - 158°F) 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) 250W(x2) PSU, 100 - 240V
System Warning Buzzer	HDDs/SSDs supported Hard Drive Type Operating Temperature Storage Temperature Relative Humidity Power Supply Unit Power Consumption: Operating Mode, Typical	3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives 0 - 40 °C (32°F - 104°F) -20 - 70°C (-4°F - 158°F) 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) 250W(x2) PSU, 100 - 240V 82.26 W
	HDDs/SSDs supported Hard Drive Type Operating Temperature Storage Temperature Relative Humidity Power Supply Unit Power Consumption: Operating Mode, Typical Fan Mode Switch	3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives 0 - 40 °C (32°F - 104°F) -20 - 70°C (-4°F - 158°F) 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) 250W(x2) PSU, 100 - 240V 82.26 W Yes (Auto, high, medium, low)

Note: Her only ONAD moment modules to maintain exctem nerformance and stability. For NAC devices with more than one moment

Note: Use only QINAP memory modules to maintain system performance and stability. For INAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting. Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.