



## TS-673A-8G

CPU	AMD Ryzen™ Embedded V1500B 4-core/8-thread 2.2 GHz processor
CPU Architecture	64-bit x86
Graphic Processors	Optional via a PCIe adapter
Floating Point Unit	Yes
Encryption Engine	Yes (AES-NI)
Hardware-accelerated Transcoding	Optional via a PCIe adapter
System Memory	8 GB SODIMM DDR4 (1 x 8 GB)
Maximum Memory	64 GB (2 x 32 GB)
Memory Slot	2 x SODIMM DDR4 Support ECC memory
	For dual-DIMM configurations, you must use a pair of identical DDR4 modules.
Flash Memory	5GB (Dual boot OS protection)
Drive Bay	6 x 3.5-inch SATA 6Gb/s, 3Gb/s
Drive Compatibility	3.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Hot-swappable	Yes
	The following are not hot-swappable: M.2 SSDs, SSD cache drives, SSDs using PCIe expansion slots.
M.2 Slot	2 x M.2 2280 PCIe Gen3 x1 slots
	Compatible with NVMe SSD PCIe Gen 3 and above. Please refer to https://www.qnap.com/compatibility/ for compatibility. The M.2 SSD is not included as standard. M.2 SSD operations can easily generate excessive heat. It is recommended to install a heatsink (from <u>QNAP</u> or a third-party provider) on the M.2 SSD.
SSD Cache Acceleration Support	Yes
GPU pass-through	Yes

2.5 Gigabit Ethernet Port (2.5G/1G/100M)	2(2.5G/1G/100M)
5 Gigabit Ethernet Port (5G/2.5G/1G/100M)	Optional via a PCIe adapter
10 Gigabit Ethernet Port	Optional via a PCIe adapter
Wake on LAN (WOL)	Yes
Jumbo Frame	Yes
PCIe Slot	2 Slot 1: PCIe Gen 3 x4 Slot 2: PCIe Gen 3 x4
	Card dimensions for PCIe slot 1~Slot 2 : 200 x 111.15 x 18.76 mm / 7.87 x 4.38 x 0.74 inches. Wider cards can be installed if the next PCIe slot will not be used.
USB 3.2 Gen 2 (10Gbps) Port	3 x Type-A USB 3.2 Gen 2 10Gbps 1 x Type-C USB 3.2 Gen 1 5Gbps
HDMI™ Output	Optional via a PCIe adapter
Form Factor	Tower
LED Indicators	Status/Power, USB, LAN, Drive 1-6, M.2 SSD 1-2
Buttons	Power, Reset, USB Auto Copy
Dimensions (HxWxD)	180.2 × 264.3 × 279.6 mm
	100.2 ^ 204.5 ^ 275.0 1111
	Dimensions do not include foot pad (foot pad may be up to 30mm / 1.18 inches high depending on model)
Weight (Net)	Dimensions do not include foot pad (foot pad may be up to 30mm / 1.18 inches
	Dimensions do not include foot pad (foot pad may be up to 30mm / 1.18 inches high depending on model)
Weight (Net)	Dimensions do not include foot pad (foot pad may be up to 30mm / 1.18 inches high depending on model) 6.4 kg
Weight (Net) Weight (Gross)	Dimensions do not include foot pad (foot pad may be up to 30mm / 1.18 inches high depending on model) 6.4 kg 7.3 kg
Weight (Net) Weight (Gross) Operating Temperature	Dimensions do not include foot pad (foot pad may be up to 30mm / 1.18 inches high depending on model) 6.4 kg 7.3 kg 0 - 40 °C (32°F - 104°F)
Weight (Net) Weight (Gross) Operating Temperature Storage Temperature	Dimensions do not include foot pad (foot pad may be up to 30mm / 1.18 inches high depending on model) 6.4 kg 7.3 kg 0 - 40 °C (32°F - 104°F) -20 - 70°C (-4°F - 158°F)
Weight (Net) Weight (Gross) Operating Temperature Storage Temperature Relative Humidity	Dimensions do not include foot pad (foot pad may be up to 30mm / 1.18 inches high depending on model) 6.4 kg 7.3 kg 0 - 40 °C (32°F - 104°F) -20 - 70°C (-4°F - 158°F) 5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Weight (Net) Weight (Gross) Operating Temperature Storage Temperature Relative Humidity Power Supply Unit Power Consumption: HDD	Dimensions do not include foot pad (foot pad may be up to 30mm / 1.18 inches   high depending on model)   6.4 kg   7.3 kg   0 - 40 °C (32°F - 104°F)   -20 - 70°C (-4°F - 158°F)   5-95% RH non-condensing, wet bulb: 27°C (80.6°F)   250W, 100-240V AC, 50-60Hz, 3.5A   21.891 W   45.898 W
Weight (Net)Weight (Gross)Operating TemperatureStorage TemperatureRelative HumidityPower Supply UnitPower Consumption: HDDD Sleep ModePower Consumption: Operating Mode, Typical	Dimensions do not include foot pad (foot pad may be up to 30mm / 1.18 inches high depending on model) 6.4 kg 7.3 kg 0 - 40 °C (32°F - 104°F) -20 - 70°C (-4°F - 158°F) 5.95% RH non-condensing, wet bulb: 27°C (80.6°F) 250W, 100-240V AC, 50-60Hz, 3.5A 21.891 W 45.898 W
Weight (Net) Weight (Gross) Operating Temperature Storage Temperature Relative Humidity Power Supply Unit Power Consumption: HDD Sleep Mode	Dimensions do not include foot pad (foot pad may be up to 30mm / 1.18 inches   high depending on model)   6.4 kg   7.3 kg   0 - 40 °C (32°F - 104°F)   -20 - 70°C (-4°F - 158°F)   5-95% RH non-condensing, wet bulb: 27°C (80.6°F)   250W, 100-240V AC, 50-60Hz, 3.5A   21.891 W   45.898 W
Weight (Net)Weight (Gross)Operating TemperatureStorage TemperatureRelative HumidityPower Supply UnitPower Consumption: HDDD Sleep ModePower Consumption: Operating Mode, Typical	Dimensions do not include foot pad (foot pad may be up to 30mm / 1.18 inches high depending on model) 6.4 kg 7.3 kg 0 - 40 °C (32°F - 104°F) -20 - 70°C (-4°F - 158°F) 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) 250W, 100-240V AC, 50-60Hz, 3.5A 21.891 W 45.898 W 7ested with drives fully populated. 5ystem fan: 2 x 92mm

Standard Warranty	3
Max. Number of Concurrent Connections (CIFS) - with Max. Memory	2000

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting. QNAP reserves the right to replace partial parts or accessories if the original is no longer available from its manufacturer/supplier. Any replacement would be fully tested and verified to meet strict compatibility and stability guidelines and will deliver identical performance to the original.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.