

Key **Features**

- Builtin Full HD webcam and microphone
- Adjustable vertical angles for greater frame control
- Webcam slide cover ensures total security and privacy
- Ergonomic flexibility with quick release stand
- Dual frontfacing speakers



Product **Description**

The ViewSonic VG2440V is a 24" Full HD video conferencing monitor designed to deliver out-of-the-box video conferencing and high-quality live streaming capability. The built-in Full HD webcam allows you to easily adjust the vertical angles to better frame yourself during VC calls and create more engaging content through varied camera angles, while the easy-to-use cover slide ensures total privacy and security when not in use. Providing the full spectrum of ergonomic flexibility, the VG2440V can tilt, swivel, pivot, and height adjust to adapt to any setup or workflow, and the exceptional inbuilt microphones and dual front-facing speakers ensure you can hear and be heard with absolute clarity and professionalism. Combined with the vDisplay Manager productivity software for efficient multi-tasking and streamlined on-screen display control, the VG2440V is the complete solution for anybody looking for a professional live streaming or video communication experience.



Visit Us

www.viewsonic.com

DISPLAY		ADDITIONAL HARDWARE		GENERAL
Display Size (in.):	24	Kensington Lock Slot:	1	
Viewable Area (in.):	23.8	Webcam:	2.0M pixel	Regulations:
Panel Type:	IPS Technology	Cable Organization:	Yes	
Resolution:	1920 x 1080	Microphone:	Yes	
Resolution Type:	FHD (Full HD)	CONTROLS		PACKAGE CONTENTS:
Static Contrast Ratio:	1,000:1 (typ)	Physical Controls:	Key 1 (volume down), Key 2, Key 3,	
Dynamic Contrast Ratio:	80M:1		Key 4, Key 5, Key 6 (power)	Describ /Discressly
Light Source:	LED	On Screen Display:	Input Select, Audio/Mic, ViewMode, Color Adjust, Manual Image Adjust,	Recycle/Disposal:
Brightness:	250 cd/m² (typ)	OPERATING CONDITIONS	Setup Menu	Warranty:
Colors:	16.7M	Temperature:	32°F to 104°F (0°C to 40°C)	Power Management:
Color Space Support:	8 bit (6 bit + Hi-FRC)	Humidity (non-condensing):	20% to 90%	
Aspect Ratio:	16:9	WALL MOUNT	20 % (0 90 %	
Response Time (Typical GTG):	5ms	VESA Compatible:	100 x 100 mm	
Response Time (GTG w/OD):	5ms	INPUT SIGNAL	100 x 100 11111	
Viewing Angles:	178° horizontal, 178° vertical	IN OT SIGNAL	RGB Analog: 16 ~ 83KHz, HDMI	
Backlight Life (Hours):	30000 Hrs (Min)	Frequency Horizontal:	(v1.4): 15 ~ 90KHz, DisplayPort (v1.2): 15 ~ 90KHz	
Curvature:	Flat		• •	
Refresh Rate (Hz):	60	Frequency Vertical:	RGB Analog: 50 ~ 75Hz, HDMI (v1.4): 49 ~ 75Hz, DisplayPort (v1.2): 49 ~ 75Hz	
Blue Light Filter:	Yes	WIDEG INDUS		
Flicker-Free:	Yes	VIDEO INPUT	TMDC_UDML(st_4)_DCLE	
Color Gamut:	NTSC: 72% size (Typ) sRGB: 104% size (Typ)	Digital Sync:	TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.2) Separate/Composite/SOG - RGB	
Pixel Size:	0.275 mm (H) x 0.275 mm (V)	Analog Sync:	Analog	
Surface Treatment:	Anti-Glare, Hard Coating (3H)	ERGONOMICS		
COMPATIBILITY		Height Adjust (mm):	130	
PC Resolution (max):	1920x1080	Swivel:	120°	
Mac® Resolution (max):	1920x1080	Tilt (Forward/Back):	-5° / 40°	
PC Operating System:	Windows 7/8/8.1/10/11 certified; macOS tested	Pivot (Right/Left): WEIGHT (IMPERIAL)	90° / 90°	
Mac® Resolution (min):	1920x1080	Net (lbs):	13.3	
CONNECTOR		Net Without Stand (lbs):	7.9	
VGA:	1	Gross (lbs):	19.2	
USB 3.2 Type A Down Stream:	3	WEIGHT (METRIC)		
USB 3.2 Type B Up Stream:	Ī	Net (kg):	6	
3.5mm Audio In:	1	Net Without Stand (kg):	3.6	
3.5mm Audio Out:	1	Gross (kg):	8.7	
HDMI 1.4:	1	DIMENSIONS (IMPERIAL) (V	VXHXD)	
DisplayPort:	1	Packaging (in.):	24 x 15.9 x 8.3	
Power in:	3-pin Socket (IEC C14 / CEE22)	Physical (in.):	21.6 x 16.02~21.13 x 8.1	
AUDIO		Physical Without Stand (in.):	21.6 x 13.8 x 2	
Internal Speakers:	2Watts x2	DIMENSIONS (METRIC) (WX	HXD)	
POWER		Packaging (mm):	609 x 405 x 210	
Eco Mode (Conserve):	10.3W	Physical (mm):	549 x 406.78~536.78 x 206	
Eco Mode (optimized):	11.71W	Physical Without Stand (mm):	549 x 352 x 50	
Consumption (typical):	13.68W			
Consumption (max):	16.52W			
Voltage:	AC 100-240V			
Stand-by:	0.5W			
Power Supply:	Internal Power Supply			

Copyright © ViewSonic Corporation 2000-2024. All rights reserved.