

Key Features

- USB Type-C
- Full HD 1080p resolution
- Frameless bezel
- SuperClear® IPS technology
- VGA, HDMI and DisplayPort inputs



## Product Description

DescriptionThe ViewSonic VG2755 is a 27" (27" viewable) 1080P IPS monitor designed to fit the modern office space. The monitor comes with a built-in USB Type-C port. Simply charge and display content through a single cable from your device, enabling connection with your laptop by a single USB cable to keep the workstation neat while also use it as a docking monitor. In addition, the monitor is equipped with DisplayPort, HDMI, VGA, and three USB Type-A ports to expand your efficiency. The three-sided frameless bezel design lets you enjoy an uninterrupted view of content across multiple monitors. An advanced ergonomic design offers the widest range of adjustments available for maximum comfort; including pivot, swivel, height adjustment, and an impressive 40° tilt, allowing you to use the monitor while standing or have strategic group discussions around the screen. Packaging is environmentally friendly and offers quick and easy out-of-the-box setup, making VG2755 series monitors perfect for business environments.



1. VESA Compatible (Wall Mount 100 x 100 mm) 2. Menu Control Panel 7. VGA 8. USB Type C 9. USB 3.2 up stream

## ViewSonic VG2755 27" Advanced Ergonomics Business Monitor - ViewSonic Global

3. USB 3.2 down stream x 2 4. AC In 5. DisplayPort 6. HDMI

Visit Us www.viewsonic.com

1/16/24, 5:06 PM

## ViewSonic VG2755 27" Advanced Ergonomics Business Monitor - ViewSonic Global

DISPLAY		CONTROLS	
Display Size (in.):	27	Physical Controls:	Key 1 (eye), Key 2, Key 3, Key 4, K 5, Key 6 (power)
Viewable Area (in.):	27		Input Select, Audio Adjust,
Panel Type:	IPS Technology	On Screen Display:	ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Resolution:	1920 x 1080	OPERATING CONDITIONS	
Resolution Type:	FHD (Full HD)	Temperature:	32°F to 104°F (0°C to 40°C)
Static Contrast Ratio:	1,000:1 (typ)	Humidity (non-condensing):	20% to 90%
Dynamic Contrast Ratio:	50M:1	WALL MOUNT	
Light Source:	LED	VESA Compatible:	100 x 100 mm
Brightness:	250 cd/m² (typ)	INPUT SIGNAL	
Colors:	16.7M	Frequency Horizontal:	RGB Analog: 24 ~ 82KHz, HDMI
Color Space Support:	8 bit (6 bit + FRC)		(v1.4): 15 ~ 82KHz, DisplayPort (v1.2): 15 ~ 82KHz, Type C: 15 ~
Aspect Ratio:	16:9		82KHz
Response Time (Typical GTG):	5ms	Frequency Vertical:	RGB Analog: 50 ~ 75Hz, HDMI (v1. 24 ~ 75Hz, DisplayPort (v1.2): 24 ~ 75Hz, Type C: 24 ~ 75Hz
Response Time (GTG w/OD):	5ms		
Response Time (Typical Tr+Tf):	15ms	VIDEO INPUT	
Viewing Angles:	178° horizontal, 178° vertical	Digital Sync:	TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.2), Micro-Packet - Type C
Backlight Life (Hours):	30000 Hrs (Min)		
Curvature:	Flat	Analas Cursu	Separate/Composite/SOG - RGB
Refresh Rate (Hz):	60	Analog Sync:	Analog
		ERGONOMICS	
Blue Light Filter:	Yes	Height Adjust (mm):	130
Flicker-Free:	Yes	Swivel:	120°
Color Gamut:	NTSC: 72% size (Typ) sRGB: 102% size / 94% coverage (Typ)	Tilt (Forward/Back):	-5° / 40°
		Pivot (Right/Left):	90° / 90°
Pixel Size:	0.311 mm (H) x 0.311 mm (V)	WEIGHT (IMPERIAL)	
Surface Treatment:	Anti-Glare, Hard Coating (3H)	Net (lbs):	16.5
COMPATIBILITY		Net Without Stand (lbs):	11.2
PC Resolution (max):	1920x1080	Gross (lbs):	23.6
Mac® Resolution (max):	1920x1080	WEIGHT (METRIC)	
PC Operating System:	Windows 7/8/8.1/10 certified; macOS	Net (kg):	7.5
	tested	Net Without Stand (kg):	5.1
Mac® Resolution (min):	1920x1080	Gross (kg):	10.7
		DIMENSIONS (IMPERIAL) (W	XHXD)
VGA:	1	Packaging (in.):	27.2 x 16.9 x 8.6
USB 3.2 Type A Down Stream:	3	Physical (in.):	24.1 x 15.99~20.99 x 8
USB 3.2 Type B Up Stream:	1	Physical Without Stand (in.):	24.1 x 14.2 x 2
USB 3.2 Type C Up Stream; DisplayPort Alt mode :	1 (60W power charger)	DIMENSIONS (METRIC) (WX	
HDMI 1.4:	1	Packaging (mm):	692 x 430 x 218
DisplayPort:	1	Physical (mm):	612 x 406.19~533.24 x 202
Power in:			612 x 362 x 52
	3-pin Socket (IEC C14 / CEE22)	Physical Without Stand (mm):	012 X 302 X 32
	2Watto x2	GENERAL	
Internal Speakers: POWER	2Watts x2	Regulations:	cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, MX-CoC, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC,
	13W		
Eco Mode (Conserve):			UkrSEPRO, RCM, GEMS, BIS
Eco Mode (optimized):	15.6W	PACKAGE CONTENTS:	VG2755 x1, 3-pin Plug (IEC C13 / CEE22) x1, DisplayPort Cable (v1.2 Male-Male) x1, USB A/B Cable (v3. Male-Male) x1, Quick Start Guide x
Consumption (typical):	19.1W		
Consumption (max):	22.54W		Please dispose of in accordance wi
Voltage:	AC 100-240V	Recycle/Disposal:	local, state or federal laws.
Stand-by:	0.3W	Warranty:	*Warranty offered may differ from
Power Supply:	Internal Power Supply		market to market
DDITIONAL HARDWARE		Power Management:	Energy Star standards, EPEAT

Copyright © ViewSonic Corporation 2000-2024. All rights reserved.