



TIMBERWOLF®
LEAD THE PACK

With the largest infeed of its class, and our WolfTrack Fixed Track Dual Speed tracking system, means that operator comfort and safety is engineered in harmony with power and efficiency.

A low-speed gear to negotiate difficult terrain and a higher-speed to cover distance efficiently.



TW 280FTR

THE HUNGRY WOLF

With amazing off-road capability, the TW 280FTR is our 'hungry wolf' tracked wood chipper kitted with a powerful Kubota WG1605 57 hp petrol engine.



www.timberwolf-uk.com



TIMBERWOLF®

LEAD THE PACK

FEATURES AND BENEFITS:

- Processing throughput of up to 7 tonnes/hr
- 57 hp Kubota petrol engine
- Class-leading 280 mm x 210 mm infeed opening (8 ¼" cutting performance)
- Quad force rollers for ultimate grip, crushing & infeed power
- 245 mm ground clearance
- Anti-vibration folding operator control platform
- WolfTrack Dual Speed Tracking System (Low speed: 2.5 kph High speed: 5 kph)
- Optional Bushy Hall Delta S3300 electric winch
- Integrated track recovery system
- Dual, ergonomic heavy duty infeed controls
- 280° adjustable discharge chute
- Patented exhaust cooler reduces exhaust temperatures up to 300°C
- WolfPort blade access and removeable side panels for easy maintenance and servicing accessibility
- Double-sided reversible blades
- Timberwolf reliability and simplicity built-in
- 3-year warranty as standard with optional 5-year extended warranty

TW 280FTR SPECIFICATIONS	
PETROL ENGINE	
57 hp Kubota (E10 compliant)	
Fuel tank capacity	36 litres
DIMENSIONS	
Weight	1637 kg
Height	2320 mm
Height with discharge tube removed	1460 mm
Length (tray down)	3300 mm
Length (tray up)	2740 mm
Width	1410 mm
CHIPPING FEATURES	
Feed method	Twin hydraulic rollers c/w Auto Feed Control
Maximum diameter infeed	210 mm (8 ¼")
Discharge tube	280° adjustable discharge
Blades	2 x 158 mm double sided, fully hardened