



TIMBERWOLF®
LEAD THE PACK

Featuring our innovative WolfTrack variable gradient tracking system, the TW 280VGTR uses heavy-duty twin arms to support each of the wide, smooth-running tracks.

This means that the operator has dynamic control over track width, ground clearance and machine tilt angle providing greater control and comfort, particularly whilst navigating uneven and sloping ground up to 30 degrees.



TW 280VGTR

THE GO-ANYWHERE WOLF

The TW 280VGTR is a powerhouse 8" wood chipper with the strength to complete the toughest of jobs in the most remote locations.



www.timberwolf-uk.com



TIMBERWOLF®

LEAD THE PACK

FEATURES AND BENEFITS:

- Processing throughput of up to 7 tonnes/hr
- 57 hp Kubota petrol engine
- Class-leading 280 mm x 210 mm infeed opening (8 ¼" cutting performance)
- Quad force rollers for ultimate grip, crushing & infeed power
- WolfTrack Variable Gradient Tracking System with 210 mm ground clearance and up to 30-degree slope capability
- Anti-vibration folding operator control platform
- Optional WARN ZEON8 3500 kg electric winch
- Integrated track recovery system
- Dual, ergonomic heavy duty infeed controls
- 280° adjustable discharge chute
- Patented exhaust cooler reduces exhaust temperatures up to 300°C
- WolfPort blade access and removeable side panels for easy maintenance and servicing accessibility
- Double-sided reversible blades
- Timberwolf reliability and simplicity built-in
- 3-year warranty as standard with optional 5-year extended warranty

TW 280VGTR SPECIFICATIONS	
PETROL ENGINE	
57 hp Kubota (E10 compliant)	
Fuel tank capacity	36 litres
DIMENSIONS	
Weight	2129 kg
Height	2455 mm - 2850 mm
Height with discharge tube removed	1765 mm - 2160 mm
Length (tray down)	3665 mm
Length (tray up)	2880 mm
Width	1480 mm - 2010 mm
CHIPPING FEATURES	
Feed method	Twin hydraulic rollers c/w Auto Feed Control
Maximum diameter infeed	210 mm (8 ¼")
Discharge tube	280° adjustable discharge
Blades	2 x 158 mm double sided, fully hardened