User Nanual Arcadia 8-in Pendant





Thank you for shopping with Ozarké, we really appreciate your business. Our goal is to provide an excellent customer service before, during and after delivery. We've included a guide on how to install this light, should you require additional assistance please feel free to email us and one of our customer service reps will reach out to assist you.

You can reach us via email at info@ozarke.com or via phone at +1-(800) 604-7271

BEFORE YOU GET STARTED

When working with electrical wiring, follow these safety instructions to prevent injury or damage:

- 1. Turn off the power: Before starting any work, turn off the power to the area you will be working in.
- 2. Use appropriate tools: Only use tools designed for electrical work and in good condition.
- 3. Wear protective gear: Wear safety glasses, gloves, and other protective gear as necessary.
- 4. Test for power: Use a non-contact voltage tester to check for electrical current before touching any wires.
- 5. Avoid wet conditions: Do not work with electrical wiring in wet or damp conditions.
- 6. Keep a safe distance: Stay away from exposed wires or electrical components.
- 7. Seek professional help: Consult a qualified electrician if you are unsure about any aspect of electrical wiring or encounter any problems.

▲ WARNING!

- 1. Do not use the power supply beyond the specified range (110V, 60Hz).
- 2. Avoid scratching the surface and wires of the light during installation.
- 3. Do not install the light outdoors.
- 4. The light should not be close to corrosive chemical objects or gases.
- 5. It should not be washed with water. It can only be wiped with a clean soft cloth.



START FROM HERE

Make sure POWER is COMPLETELY OFF at the fuse box

- Have your fixture installed by a qualified licensed electrician
- Prepare everything in a clear area
- Wear gloves at all times during this installation
- Read instructions carefully before you start assembly
- Keep this installation sheet for future reference
- **1.** Remove fixture from its original package
- 2. Separate mounting plate (1c) from canopy (2a) by removing decorative nuts (2c)
- **3.** Align mounting plate screws (1d) to desired orientation, and then attach mounting plate (1c) to electrical junction box (1a) using junction box screws provided (1e) in hardware package
- Determine hanging height of fixture by securing rods (2d) to canopy (2a) and fixture body (3a) after feeding fixture wires through rods
- Make proper electrical connections (black to hot "L", white to neutral "N", ground to "GND") with wire nuts (1b) provided in hardware package
- **6.** Secure shade (3b) to fixture body (3a) with shade connector (3c)
- **7.** Align and insert mounting plate screws (1d) through holes on canopy (2a), secure with decorative nuts (2c)
- 8. Insert bulb (4a) into fixture socket

Please Note:

- This LED fixture comes with pre-wired LED module(s)
- Unless instructed, Do Not touch any part of the LED module(s) as any unnecessary contact with the module could cause permanent damage
- For dimming, an ELV (Electronic Low Voltage) or TRIAC type of dimmer is required
 120V input



