

SPECIFICATIONS		VL100 Touch	
Processor		32-bit Secure Microprocessor running powerful Linux based OS	
Memory	Flash/DDR4	128 MB/64MB (Up to 256MB/128MB)	
	Micro-SD Socket	Yes	
Display		3.5" Color TFT LCD 320 x 480 Pixels	
Touch Screen		Yes	
Card Reader	Magnetic Stripe	ISO 7810, 7811, 7813 Triple Track, Bi-Directional	
Card Reader	Contact Card	User Card	ISO 7816 ID-1 1.8V/3V/5V T=0, T=1
		SAM Card	2 (Up to 4)
	Contactless (Optional)	ISO 14443 Type A, B ISO 18092 NFC Mifare & Sony FeliCa Working Frequency 13.56 MHz	
Dual SIM		Yes	
Communications Interface Options	Wire	Ethernet RS232 * 2 USB * 2	
Indicators	LED - Contactless	No	
	Audio Buzzer	Yes	
Keypad	Standard Keys	15	
	Function Keys	No	
Printer		57 mm x 50 mm, 100mm/sec	
Software		SDK KMS TMS GDB CTOS library ISO 8583 library Crypto library	
Crypto		TRNG DES T'DES AES RSA MK/SK DUKPT T'DES DUKPT	
Power Supply	Power Adapter	DC 9V/4A	
	Battery	Li-Polymer 7.4~8.2V 1150mAh 5000mA (Max discharge current)	
Dimensions (mm)		190(L) x 78(W) x 78(H)	
Weight		350 g	
Environment	Operating Temperature	0°C to 50°C	
	Storage Temperature	-20°C to 70°C	
	Operating Humidity	5% to 90% non-condensing	
	Storage Humidity	5% to 90% non-condensing	
Certification		PCI PTS 4.x EMV L1/L2 payWave PayPass ExperssPay D-PAS Interac Flash J-Speedy FeliCa UnionPay UICS TQM PBOC L1/L2	
Optional Additional Feature		Speaker Detachable Battery	