



DURA®
Ultra Premium Paint
Interior Satin
DAIP35-L-1



≤ 50 g/L VOC**

Dunn-Edwards DURA Interior Satin Paint is designed for use on properly prepared and primed interior surfaces. It is truly washable while being stain, scuff, burnish and color rub-off resistant due to its 100% acrylic formulation. This ultra-premium satin paint is easy to apply and is ideal for use on projects where ultra-low VOC products are preferred. This multi-use semi-gloss interior paint can also be applied on properly prepared and primed wood cabinets, doors, trim, and furniture.

PRODUCT INFORMATION

SOLVENT TYPE: Waterborne		RESIN TYPE: 100% Acrylic	
FINISH (ASTM D523): Satin: 10–15% on a 60° and 85° meter;			
COLORS: Colors can be special ordered.			
TINT BASES: L Tintable White, M Medium, U Ultra Deep			
VISCOSITY@77°F/25°C (ASTM D 562): 100–110 KU			
MAXIMUM VOC CONTENT 50 g/L (by ASTM Test Method D 6886)		MAXIMUM RAVOC (Reactivity-Adjusted VOC) 15 g/L	
SOLIDS BY VOLUME (ASTM D 2697) 39.0% ± 2%		SOLIDS BY WEIGHT 52.9 ± 2%	
WEIGHT PER GALLON (ASTM D 1475): 10.81 lbs.			
COMPOSITION BY WEIGHT			
Pigment—42.2%		Vehicle—57.8%	
*Prime pigments	22.5%	Resin solids	15.9%
Reinforcing pigments	19.6%	Water & additives	42.0%
*Prime pigments include all pigments directly adding to the hiding power of this paint.			
RECOMMENDED FILM THICKNESS PER COAT			
Wet: 3.8 mils		Dry: 1.5 mils	
PRACTICAL COVERAGE PER COAT AT RECOMMENDED DRY FILM THICKNESS Approximately 350–400 sq. ft. per gallon, depending on surface conditions and application techniques.			
THINNING RECOMMENDATION: This coating is intended to be applied without thinning or diluting under normal environmental and application conditions. If necessary to maintain good workability, add up to 1/4 pint (4 fl. oz.) of clean water per gallon of coating.			
AVERAGE DRY TIME@77°F/25°C (ASTM D 1640)			
Dry to touch: 30–60 minutes		Recoat: 2–4 hours	
Dry times and recoat times are temperature, humidity and film thickness dependent.			
APPLICATION EQUIPMENT: Brush, roller, airless spray			
PACKAGING: Quart, one-gallon containers			
STORAGE: Store in a dry area. Protect from freezing. Protect from temperatures above 110°F for extended periods of time. Extreme temperatures may cause paint to become unusable. See Paint Storage Best Practices Technical Bulletin at dunnedwards.com for more information.			
CLEANUP: Warm, soapy water			
DISPOSAL: For information on local options to dispose of unwanted leftover paint, call Dunn-Edwards Customer Service at 1-888-DEPAINT or visit www.dunnedwardsdura.com. Do not mix with other products.			
CONFORMS TO: CARB 2020 SCM & CALGreen 2022; CA Section 01350; LEED v4/4.1 EQ Credit; MPI Approved Product, #53, #138; CRGI Green Wise Certified; FDA Guidelines for Resinous & Polymeric Coatings.			
SAFETY DATA SHEET: Available at www.dunnedwardsdura.com			

SURFACE PREPARATION: DURA Ultra Premium Paint Satin is self priming on most surfaces. For previously painted surfaces that are properly repaired as needed, one (1) coat may be sufficient. For properly prepared new surfaces, two (2) coats are typically required. All surfaces must be cured, clean, dry, and free from dirt, dust, rust, stains, grease, oil, mildew, wax, efflorescence, bond-breakers, and other contaminants. Remove all loose, peeling, or chalky paint by sanding, scraping, or other appropriate methods. Repair all cracks, holes, and other surface imperfections with a suitable patching material. Repaired surfaces should then be sanded smooth and dusted clean. Glossy surfaces should be dulled to provide a roughened surface for good adhesion.

SPECIAL INSTRUCTIONS

- **CAUTION!** Scraping or sanding surfaces of older buildings (especially pre-1978) may release dust containing lead or asbestos. EXPOSURE TO LEAD OR ASBESTOS CAN BE VERY HAZARDOUS TO YOUR HEALTH. Wear a NIOSH-approved N100 particulate filter mask to avoid breathing dust. Use a HEPA vacuum for cleanup, and finish by water-washing all surfaces. For more information, see Dunn-Edwards brochure on “Surface Preparation Safety” or call U.S. EPA’s lead hotline at 1-800-424-LEAD, or visit www.epa.gov/lead or / asbestos, or contact your state or local Health Agency.
- This product can neither cause nor prevent or cure the growth of mold, mildew, or other forms of fungus. Excessive moisture and inadequate ventilation are the main conditions that promote their growth. Correct any such conditions before painting.
- This paint contains a preservative that inhibits the growth of mildew on the surface of the dry paint film.
- 10% of clean water (3/4 pints per gallon or 1/2 gallon per 5-gallons) for best penetration.
- Do not apply when the air or surface temperature is below 50°F.

HEALTH & SAFETY CAUTIONS: INHALATION OF SPRAY MIST OR SANDING DUST MAY BE HARMFUL. Use only with adequate ventilation. Avoid breathing vapors, spray mist and sanding dust. Wear NIOSH-approved N100 particulate filter mask when spraying or sanding. Avoid contact with skin and eyes. Do not ingest. Close container after each use. **FIRST AID:** If swallowed, immediately give 1 or 2 glasses of water to drink – for emergency information, call 1-800-222-1222. If having difficulty breathing, move to fresh air. For eye contact, immediately flush with water for 15 minutes. For skin contact, wash thoroughly with soap and water.

• KEEP OUT OF REACH OF CHILDREN •

Ingredient (CAS #): Water (7732-18-5); Titanium Dioxide (13463-67-7); Copolymer Resin (Proprietary); Silica Gel (112926-00-8); Ceramic Microspheres (66402-68-4).

WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov