RIKON

14" STANDARD

13" Cutting Capacity

Quickly adjust your cutting height up to 13" Comes with Quick Reference Scale on Guard





115 Volt Power Outlet

Great for adding accessories or worklight. Outlet is located on the rear of the saw column



Quick adjusting fence and re-saw bar



13"



Heavy Duty Steel Stand

Stand can be cut to lower the table height to 28" for wheelchair users.

FEATURES:

Motor

Height

Horsepower.....1-1/2 HP TEFC
Amps.....14/7
Volts.....15/230V, 60Hz

Cutting Capacity

neight		
Width		13-5/8"
• Blade	(Includes 111" x 5/	8" , 4 TPI, Reg.)
Width		3/16" - 3/4"
Length		111"
Blade Sp	eed1,445/	/2,950 FT/MIN
• Table		

 Size
 21-1/2" x 15-3/4"

 Left Tilt
 -5°

 Right Tilt
 45°

 Miter Gauge "T" Slot
 (2) 3/4" x 3/8"

 Height to Floor
 39-1/2"

 Height to Base
 20"

Fence Size......18-3/4" x 1-3/4" x 6"



DIMENSIONS:

Overall

Height	75"
Width	30"
Depth	25"
Base Size	21-5/8" x 14-3/4"
Dust Port	1@4"
Net Weight	212 lbs.
Shipping Weight	223 lbs.
Shipping Carton54"	' x 17-1/2" x 23-5/8"
. Warranty	5 YFΔRS

RIKON



12-201

LED Gooseneck Worklight with Magnetic Base and Magnetic Clip



10-900

Spring Loaded Tool-Less Blade Guide Retrofit Kit System



13-912

Replacement Miter Gauge



C10-109

Replacement Guide Bearings Pack of 6



Table Inserts

Table Insert - *C10-391* Zero Clearance Insert - *C10-392* Aluminum Insert - *C10-395*



C10-995

Replacement Drive Belt

AVAILABLE ACCESSORIES



10-324 Bandsaw Blades

Length	Width	Gauge	TPI	Style	Item No.
111"	3/16"	.025"	10	Reg. Tooth	19-1101
111"	1/4"	.025"	6	Hook Tooth	19-1100
111"	3/8"	.025"	4	Hook Tooth	19-1102
111"	1/2"	.025"	3	Hook Tooth	19-1103
111"	5/8"	.025"	3	Hook Tooth	19-1104
111"	5/8"	.025"	4	Reg. Tooth	19-1105
Bi-Metal					
111"	1/2"	.025"	14	Reg. Tooth	19-1511
111"	1/2"	.025"	18	Reg. Tooth	19-1512
111"	3/4"	.035"	8/12	Var. Tooth	19-1513
111"	3/4"	.035"	10/14	Var. Tooth	19-1514