



14" PROFESSIONAL

10-353

*Featuring NEW Patent Pending Technology




***NEW**
Spring Loaded Tool-Less Guide System

No tools needed to quickly adjust your guide bearings



14" Cutting Capacity

Quickly adjust your cutting height up to 14"
Includes Quick Reference Scale




***NEW**
Quick Adjust 6" Tall Rip Fence System

Easily adjust your fence to either side of the blade



***NEW**
Quick Lock Cast Iron Trunnion System

Equipped with a large handle and locking arm for rapid adjustment



FEATURES:

- **Motor**
 - Horsepower.....3 HP TEFC
 - Amps.....13
 - Volts.....220V, 60Hz, 1Ph
- **Cutting Capacity**
 - Height.....14"
 - Width.....13-5/8"
- **Blade** (Includes 142" x 5/8" , 4 TPI, Reg.)
 - Width.....3/16" - 1"
 - Length.....142"
 - Blade Speed.....4,300 FT/MIN
- **Table**
 - Size.....21-1/2" x 15-3/4"
 - Left Tilt.....-10°
 - Right Tilt.....45°
 - Miter Gauge "T" Slot.....(2) 3/4" x 3/8"
 - Height to Floor.....34-5/8"
 - Fence Size.....19-11/16" x 1-3/4 x 6"

DIMENSIONS:

- **Overall**
 - Height.....74-1/2"
 - Width.....33-1/2"
 - Depth.....28-1/2"
 - Base Size.....25-1/4" x 18-1/8"
 - Dust Port.....2@4"
 - Net Weight.....315 lbs.
 - Shipping Weight.....414 lbs.
 - Shipping Carton.....30" x 21-1/4" x 75-5/8"
- **Warranty.....5 Years**



For more information or to find a distributor near you, please visit:

www.rikontools.com

RIKON


AVAILABLE ACCESSORIES

10-353



12-201

LED Gooseneck Worklight
with Magnetic Base and
Magnetic Clip




13-912

Replacement Miter Gauge



13-345

Optional Mobility Kit



C10-326

Replacement Guide Bearings



Table Inserts

Table Insert - C10-391
Zero Clearance Insert - C10-392
Aluminum Insert - C10-395



C10-993

Replacement Drive Belts



Shown with Optional Mobility Kit

13-345

10-353 Bandsaw Blades

Length	Width	Gauge	TPI	Style	Item No.
142"	3/8"	.025	4	Hook Tooth	19-1410
142"	1/2"	.025	3	Hook Tooth	19-1411
142"	5/8"	.025	3	Hook Tooth	19-1412
142"	3/4"	.032	3	Hook Tooth	19-1413
142"	1/2"	.025	14	Bi-Metal Reg.	19-1520
142"	1/2"	.025	18	Bi-Metal Reg.	19-1521
142"	3/4"	.035	8/12	Var. Bi-Metal	19-1522
142"	3/4"	.035	10/14	Var. Bi-Metal	19-1523

For more information or to find a distributor near you, please visit:

www.rikontools.com