CALIBRATION

Date Of Issue 23rd August 2013

Certificate Number 230813/N21



Certificate Issued By:



Electronic Temperature Instruments Ltd
Easting Close, Worthing
West Sussex BN14 8HQ England
Telephone +44 01903 202151
Facsimile +44 01903 202445
email: sales@etiltd.co.uk
Website: www.etiltd.co.uk

Page 1 of 2 pages	V 91 - ГГ
Approved Signatory	Signature
J. Carswell	folismell.
G. Hills	
J. Hutchins	

Customer Name: SIGNATROL LIMITED

Address: 1st & 2nd FLOOR OFFICES

105 CHURCH STREET

TEWKESBURY

GLOUCESTERSHIRE

GL20 5AB

Order Number: 44378

Ref Number: 370/36833

Date Received: 21st August 2013

Date Calibrated: 22nd August 2013

Ambient Temperature: 22 °C ± 2 °C

Ambient Humidity: <60 % rh

Temperature Scale: International Temperature Scale of 1990

Instrument Type: EUROTRON MICROCAL 1 SIMULATOR

Instrument Serial Number: 0049272

Procedure: The instrument was stabilised at ambient temperature, then calibrated by measuring its

output on traceable reference equipment.

The reported expanded uncertainty is based on a standard uncertainty multiplied by a coverage factor k=2, providing a level of confidence of approximately 95%. The uncertainty evaluation has been carried out in accordance with UKAS requirements.

Results indicate performance of instrument at time of measurement, with no warranty as to specification, repeatability or long term stability

This certificate is issued in accordance with the laboratory accreditation requirements of the United Kingdom Accreditation Service. It provides traceability of measurements to recognised national standards, and to units of measurement realised at the National Physical Laboratory or other recognised national standards laboratories. This certificate may not be reproduced other than in full, except with the prior written approval of the issuing laboratory.

CALIBRATION

UKAS Accredited Calibration Laboratory No 0601

Certificate Number 230813/N21

Page 2 of 2 pages

Instrument Serial No 0049272

Results

Type "J"Output			Equivalent	Uncertainty
Temperature °C	Nominal mV	Measured mV	Temperature °C	of Measurement
-100.0	-4.633	-4.635 8	-100.1	± 0.25 °C
700.0	39.132	39.131 2	700.0	± 0.15 °C
Type "K"Output			Equivalent	
Temperature °C	Nominal mV	Measured mV	Temperature °C	
-100.0	-3.554	-3.556 1	-100.0	± 0.25 °C
900.0	37.326	37.325 3	900.0	± 0.15 °C
Type "T"Output			Equivalent	
Temperature °C	Nominal mV	Measured mV	Temperature °C	
-100.0	-3.379	-3.374 1	-99.9	± 0.25 °C
300.0	14.862	14.865 2	300.1	± 0.15 °C
Type "S"Output			Equivalent	
Temperature °C	Nominal mV	Measured mV	Temperature °C	
800.0	7.345	7.341 1	799.8	±1°C
1400.0	14.373	14.371 3	1399.9	±1°C
Type "R"Output			Equivalent	
Temperature °C	Nominal mV	Measured mV	Temperature °C	
800.0	7.950	7.947 4	799.8	±1°C
1400.0	16.040	16.034 7	1399.6	±1°C
Type "E"Output			Equivalent	
Temperature °C	Nominal mV	Measured mV	Temperature °C	
-100.0	-5.237	-5.237 9	-100.0	± 0.25 °C
650.0	49.116	49.108 1	649.8	± 0.15 °C
PT100 Output			Equivalent	
Temperature °C	Nominal Ohms	Measured Ohms	Temperature °C	
0.0	0.00	100.041 4	0.10	± 0.025 °C
600.0	313.71	313.647 7	599.81	± 0.18 °C