

NRL663



200W



250W




50W




100W



150W



NRL663 200W



Watts	A	B	C	D
50W	495	146	95	ø60
100W	599	190	108	
150W	645	238	130	
200W	776	285	132	
250W	890	319	142	

FEATURES

- Die-cast aluminum housing and Polycarbonate lens with glass
- Streamlined and unique appearance design
- Smooth housing design to avoid dust
- 6KV SPD

PRODUCT BENEFITS

- High-power LED
- Long lifetime of up to 50,000hrs
- Excellent heat dissipation performance
- Support horizontal and vertical installation, the installation angle can be adjusted by 15 degree

TECHNICAL DETAILS

- 3030 LEDs
- CCT available: 4000K/5000K
- Driver PF $\geq$ 0.9
- Operation Temperature: -20°C~+45°C
- IP65 rating
- IK07 rating
- 1-10V dimming optional

APPLICATIONS

- Urban expressway
- Trunk road
- Branch road
- Residential district
- Courtyard

Model	Part Number	Voltage	Wattage	CCT	Lumen	LM/W	CRI	Beam Angle	PF	Lifetime
NRL663	87003240	220-240V	50W	4000K	6500lm	130	70	150*70°	0.9	50000hrs
	87003241			5000K						
	87003242		100W	4000K	13000lm					
	87003243			5000K						
	87003244		150W	4000K	19500lm					
	87003245			5000K						
	87003246		200W	4000K	26000lm					
	87003247			5000K						
	87003248		250W	4000K	32500lm					
87003249	5000K									