

HLP New Product Information Sheet.

Portable Co2 Gas detector

Model: GT220-Co2

This unit is a small, Co2 gas detector. The unit has a loud alarm that sounds when the detected gas level is above the alarm level set by the user. The alarm level can be between 350 PPM and 8000 PPM . The alarm level is easily changed or can be ordered already set at a particular level. The unit has a built in rechargeable battery. The battery lasts approx 14 hours between charges. A battery charger is included.

This unit is around the same size as a mobile phone and an optional belt pouch is available. This is ideal for service people who need to visit hotels, clubs, etc where Co2 gas is used for the transport of beverages.

Time and date data logging is included and the unit stores the last 25 events . The solid electrolyte sensor is very stable and has a long life. Re calibration is easily accomplished with the inbuilt menu.



- ✍ Gas levels from 350 to 8000 PPM can be detected
- ✍ Displays alarms by LCD and a loud buzzer.
- ✍ Small size of 131 x 46 x 25.5 mm
- ✍ LCD display shows all functions, Warm up, time, date, and Current Co2 levels.
- ✍ Resolution of 0.1 PPM
- ✍ Accuracy of +/- 5%
- ✍ Inbuilt Li-ion battery
- ✍ Includes charger
- ✍ Display is backlit for dark areas
- ✍ 12 Months warranty
- ✍ Other models available include Carbon Monoxide, Combustible gasses , and mains powered fixed units for cellars etc.
- ✍ Low cost of purchase and operation.
- ✍ Please read the full technical specifications before operating
- ✍

Suitable for bar staff, cellar managers, beverage service and refrigeration installers.

Ideal to meet the OH&S requirements.

HLP Controls

Phone: 1800 500 160

Fax: 1800 827 160

Email: sales@hlpcontrols.com.au

Web: www.hlpcontrols.com.au

January 2007 - No.: 29