

# TWL-C-B



## DEVICE

## C-Band Tunable Wavelength Laser

## OVERVIEW

The Optilab TWL-C-B is a high spectral purity and stable tunable wavelength laser source. The TWL-C-B features wide wavelength tuning range, narrow laser linewidth, high Side Mode Suppression Ratio (SMSR), excellent wavelength stability and optical output level exceeding 20 mW. With the standard Polarization Maintaining (PM) fiber output, the TWL-C-B offers a linearly polarized output. These features make the cost-effective TWL-C-B well-suited for many different applications, including DWDM device testing, optical sensing, and laboratory measurement applications. TWL-C-B includes an easy-to-use LabVIEW control software and RS232 Interface for remote operation in laboratory environments. Contact Optilab for more information.


## FEATURES


- Narrow laser linewidth of 100 kHz (Optional HP ver.)
- Excellent Side Mode Suppression Ratio of 55 dB
- Output power of 20 mW (Optional 40 mW avail.)
- Wavelength range from 1530 to 1565 nm
- Polarization Maintaining (PM) Output
- Intuitive and easy to use USB interface

## USE IN

- DWDM Networks
- Seed Lasers for modulators
- Fiber Sensors
- Laboratory testing and measurement
- Fiber Optics Components

## FUNCTIONAL DIAGRAM





# TWL-C-B

## SPECIFICATIONS

Laser Wavelength Range	1530 nm to 1565 nm
Wavelength Accuracy	± 1.5 GHz
Wavelength Stability	± 1 pm over 24 hours
Output Power Level	20 mW typ. (40 mW ver Avail).
Output Stability	0.02 dB over 8 hours

## GENERAL

Laser Linewidth	N/A, (<100 KHz option available)
Relative Intensity Noise	-150 dB/Hz typ.
Side Mode Suppression Ratio	55 dB typ.
Polarization Extinction Ratio	20 dB typ.
Optical Isolation	30 dB min.
Fiber Type	Panda 1550 PM Fiber
Optical Connectors	PM Narrow Key, FC/APC or Customer Specified

## CONTROL FUNCTIONS

Base Frequency Range	196.1 THz to 191.5 THz
Channel Setting Time	10 sec. typ.
Output Power Adjustment	6 dBm to max.

## MECHANICAL

Operating Temperature Range	0°C to +40 °C
Storage Temperature Range	-40°C to +70°C
Power Supply	80-240 V, 43-63 Hz AC, 1.5 A max.
Power Consumption	80 W max.
Display	Output Power Level, Wavelength
Controls	Output Power Level, Laser Wavelength, Dithering Freq.
Communication Interface	RS 232, Labview software via laser linewidth
Alarm	Over Temperature, Over Current
Dimensions	250mm (W) x 300mm (L) x 100mm (H)

