



INSTALLATION INSTRUCTIONS

PART No.

FB21031

**Jeep® TJ Wrangler 1997-2006
Windshield Light Brackets**



REQUIRED TOOLS

T-40 Wrench
3/16 Allen Wrench

KIT CONTAINS

Left and Right Gasket
Left and Right Bracket
2" All-Thread
Countersunk bolt

QTY

1 ea
1 ea
1
6

2103100

Jeep® TJ Wrangler 1997-2006 Windshield Light Brackets

1) REMOVE OEM WINDSHIELD HINGE BOLTS

Begin by removing the upper bolt from the windshield hinge using the T-40 torx. **Insert the piece of all-thread into this hole to keep the nut plate from falling down inside your Jeep's window frame.**



Remove the remaining three (3) bolts necessary for installation.

2) INSTALL LIGHT BRACKET

Remove the paper backing from the foam gasket to reveal the adhesive backing. Carefully align the gasket to the bracket and apply it using firm, even pressure to ensure good adhesion.

Secure the new bracket to your Jeep using the included hardware and your OEM button head torx bolt.



Remove the all-thread from the upper bolt location only after installing the other three (3) bolts. Install the last countersunk bolt in its place. Use the all-thread to repeat steps 1 and 2 for the opposite side.

3) LIGHTING

Install your lights following the manufacturer's instructions.