

INSTALLATION INSTRUCTIONS

PART No.

FB21057

**Jeep® TJ Wrangler
Light Bar Bracket**



* LIGHT BAR AND CUBE LIGHTS NOT INCLUDED



REQUIRED TOOLS

T-40 Torx
3/16 Allen Wrench

KIT CONTAINS

Light bar brackets (left and right)
5/16" Flat head socket cap screw

QTY

1 ea
8

Ensure light bar is roughly 52" mount to mount

Fishbone Offroad's light bar bracket is designed to fit light bars that are 52" in overall length. Be sure to check the manufacturer's spec on overall length. Smaller light bars may require spacers (not included).

1) REMOVE TOP FOUR (4) BOLTS

Remove the upper four (4) bolts from the windshield hinges. OEM hardware requires a T-40 torx.



2) INSTALL LIGHT BAR BRACKETS

Place the corresponding light bar bracket on the Jeep and loosely install with the supplied hardware.

NOTE: Keeping everything loose at this time will help when installing the light bar.



2105700

3) **INSTALL LIGHT BAR**

Following your light bar manufacturer's instructions, install the light bar.



4) **TIGHTEN ALL BOLTS**

Securely fasten all hardware after the light bar has been installed and secured.



5) **OPTIONAL – INSTALL CUBE LIGHTS**

If desired, install cube or other small lights on the tabs provided on the brackets.



6) **WIRING**

Wire your lights following your light manufacturer's installation instructions.

7) **YOU'RE READY TO LIGHT UP THE TRAILS!**