

INSTALLATION INSTRUCTIONS

PART No. FB23454F & FB33455F

Jeep® JL Wrangler & JT Gladiator JL & JT Front Elite Fenders



REQUIRED TOOLS

5mm Allen 3mm Allen 8mm Wrench

Note: These instructions will NOT cover how to remove factory fenders or inner fenders, and will NOT cover how to install inner fenders. Instructions on how to do so are available on www.FishboneOffroad.com, or www.FishboneOffroad.ty.

KIT CONTAINS

Front Fender (Left & Right)	2
Rubber Seal	2
M8 25mm Button Head Bolt	24
M8 Flat Washer	24
M8 Serrated Nu	24
Part# FB31456 -	
FB61452 LED Turn Signal	2
LED Retaining Bracket	2
M5 30mm Button Head Bolt	8
M5 Flat Washer	8
M5 Nut Plate	8

23454F & FB33455F00

QTY



INSTALLATION INSTRUCTIONS

PART No. FB23454F & FB33455F

Jeep® JL Wrangler & JT Gladiator JL & JT Front Elite Fenders

1) REMOVE

Begin by removing any inner and outer fenders your vehicle currently has installed.



INSTALL TURN SIGNALS

Please refer to the included installation instructions for the LEDs, Part# FB31456

2) PREPARE

The included rubber seals are driver and passenger side specific. Identify which side which is which by the bolt hole indents in the rubber. Peel off the backing and carefully apply the seal to the vehicle side wall of each fender.



3) INSTALL FRONT FENDERS

Hold the corresponding fender up to the vehicle and begin loosely securing it with 12 of the included M8 bolts, washers, and serrated nuts.