

SYSTEMTHREE

Safety Data Sheets (SDS)

Updated: January 1, 2023

This file contains Safety Data Sheets for the SilverTip Laminating Epoxy (fast and slow) family of products. This is a two-component system. It is imperative that you know whether you need information on the Resin or the Hardener.

Resin: Pages 2-10

Fast Hardener: Pages 11-19

Slow Hardener: Pages 21-29

If this is a medical emergency, call 911 or your local poison control center. Seek medical attention.


For technical assistance, call System Three Technical Support at 253-333-8118 option 2.

These SDS are provided pursuant to 29 CFR 1910.1200(g).

1. Product Identification

Product name	SilverTip [®] Coating and Laminating Resin
SDS Number	0900A
Product type	Epoxy polymer mixture.
Recommended use of the chemical and restrictions on use	Directed at, but not limited to, the laminating and coating of fiber composite and wood.
Restrictions	None known.
Manufacturer/Supplier information	
Company name	SYSTEM THREE RESINS, INC.
Address	8517 Commerce Place Dr NE Lacey, WA 98516 United States
Telephone	1-253-333-8118
Website	www.systemthree.com
Email	support@systemthree.com
Emergency Contact	CHEMTEL (U.S. and CANADA) 1-800-704-9215 CHEMTEL (Outside the U.S.) – Call Collect accepted +1-360-256-7365

2. Hazard(s) Identification

Classification of substance or mixture/Signal Word	WARNING Skin Corrosion/Irritation - Category 2 Serious Eye Damage/Eye Irritation - Category 2 Skin Sensitization - Category 1 Specific Target Organ Toxicity (Single Exposure) [Respiratory tract irritation] – Category 3
<u>GHS Label Elements</u> Hazard Pictograms	
Hazard Statements/Classification of substance or mixture	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation.
Precautionary statements	
<u>Precautionary Statements</u> Prevention	P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace.

Response	<p>P280 Wear protective gloves/protective clothing/eye protection/face protection.</p> <p>P304 + 340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.</p> <p>P313 Call a POISON CENTER or doctor/physician if you feel unwell.</p> <p>P302+352+363 IF ON SKIN: Wash with soap and water. Take off contaminated clothing and wash before reuse.</p> <p>P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.</p>
Storage	P308 + P313 If exposed or concerned: Get medical attention.
Disposal	P401 Store at room temperature in a well-ventilated area.
	P501 Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards not otherwise classified (HNOC)	None Available.

3. Composition/Information On Ingredients

Chemical Name	CAS Number	Content (%)
Diglycidyl Ether of Bisphenol A	25068-38-6	70 – 80 %
Diglycidyl Ether of Bisphenol F	28064-14-4	5 – 10%
Benzyl Alcohol	100-51-6	5 – 10 %
Alkyl Glycidyl Ether	17557-23-2	5 – 10 %

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.

4. First-Aid Measures

Skin contact	Remove contaminated clothing and shoes and wipe excess off skin. Flush skin with water. Follow by washing in soap and water. If irritation occurs, seek medical attention. Do not reuse clothing until cleaned. Contaminated leather articles (shoes) cannot be decontaminated and should be destroyed.
Eye contact	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately.
Inhalation	Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	No specific treatment.

5. Fire-Fighting Measures

Suitable extinguishing media	Alcohol-resistant foam, carbon dioxide (CO ₂), dry chemical, water fog.
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous decomposition products	Decomposition products may include the following materials: Carbon dioxide Carbon monoxide
Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Further information	Do not allow run-off from firefighting to enter drains or water courses. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

6. Accidental Release Measures

Personal precautions	Wear proper personal protective equipment (PPE). Avoid direct contact with material. Proper PPE includes: disposable gloves, eye protection and skin protection.
Emergency procedures	If material is spilled, avoid contact with material. Persons not wearing appropriate protective equipment should leave the area of the spill until cleanup is complete.
Methods and materials for containment/cleanup	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

7. Handling and Storage

Precautions for safe handling	Avoid contact with skin and eyes. Emergency showers and eye wash stations should be readily accessible. Adhere to work practice rules established by government regulations. Use personal protective equipment. When using, do not eat, drink or smoke.
Precautions/Recommendations for safe/proper storage	Store epoxy products in temperature stable environment, out of the reach of pets or children. Securely fasten container lids and tops, and prevent products from sitting and below freezing temperatures.

8. Exposure Controls/Personal Protection

Occupational Exposure Limits	Not established.
Appropriate engineering controls	Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	Use appropriate containment to avoid environmental contamination. Do not allow spill to enter sewers or waterways.
Individual protection measures/Personal protective equipment	
Eye/face protection	Splash-proof goggles or safety spectacles with side shields are recommended. Always wear eye protection when sanding cured epoxy resins to avoid dust in eyes.
Hand protection	Always wear impervious gloves: butyl rubber, nitrile rubber, Neoprene, PVC disposable gloves,
Skin protection	Wear clean, body-covering clothing to avoid skin contact.
Respiratory protection	Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Special instructions for protection and hygiene	Wear gloves at all times when handling product, avoid direct contact with skin. When finished using product, dispose of gloves properly and wash hands with warm, soapy water.

9. Physical and Chemical Properties

Chemical family	Epoxy Resin
Appearance	Clear liquid
Physical State	Epoxy polymer mixture
Form	Liquid
Color	Water clear
Odor	Mild
Density (Specific Gravity)	9.47 lb/gal (1.1-1.3)
Viscosity	700 cps @ 25°C
pH	Not available
Melting point/freezing point	Not available
Initial boiling point and boiling range	Not available
Flash point	>300°F, Pensky-Martens Closed Cup
Evaporation rate	Slower than ether
Flammability (solid, gas)	Not available
Upper/lower flammability limit (by volume)	Not available
Material VOC	None
Vapor density	Heavier than air
Relative density	Not determined
Solubility in water	Negligible, in water

Partition coefficient: n-octanol/water	3
Auto-ignition temperature	300°C (572.00°F)
Decomposition temperature	Not available

10. Stability and Reactivity

Reactivity	No specific test data related to reactivity available for this product.
Chemical Stability	Stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization will not occur.
Conditions to avoid	Epoxy resins and epoxy resin hardeners react with each other producing heat. They should not be mixed with each other under uncontrolled conditions or in large mass as the ensuing exotherm may result in heat and smoke, resulting in hazardous decomposition products.
Incompatible materials	Strong oxidizing and reducing agents. Lewis and mineral acids.
Hazardous decomposition products	Oxides of carbon, aldehydes, and acids.
Other hazards	None known.

11. Toxicological Information

Acute Health Hazard (components) No comprehensive data (ingestion, inhalation, dermal) on mixture (product).

Component	Result	Species	Dose	Exposure
Diglycidyl Ether of Bisphenol A	LD50 Oral	Rat	11,400 mg/kg	-
	LD50 Dermal	Rat	2,000 mg/kg	-
Diglycidyl Ether of Bisphenol F	LD50 Oral	Rat	>2,000 mg/kg	-
	LD50 Dermal	Rat	>2,000 mg/kg	-
Alkyl Glycidyl Ether	LD50 Oral	Rat	4,500 mg/kg	-
	LD50 Dermal	Rabbit	>2,000 mg/kg	-
Benzyl Alcohol	LD50 Oral	Rat	1620 mg/kg	-
	LC50 Inhalation	Rat	>4178 mg/m3	4 h, aerosol

Irritation/Corrosion (components) No information on product itself.

Component	Result	Species	Test	Exposure
Diglycidyl Ether of Bisphenol A	Moderate to severe irritation	Rabbit	Skin	4 h
	Mild irritation	Rabbit	Eye	24 h
Diglycidyl Ether of Bisphenol F	Mild irritant	Rabbit	Skin	-
	Mild irritant	Rabbit	Eye	-
Benzyl Alcohol	Irritant	Rabbit	Eye	-

Sensitization No information on product itself.

Mutagenicity No information on product itself.

Carcinogenicity No information on product itself.

Reproductive Toxicity No information on product itself.

Teratogenicity No information on product itself.

Specific target organ toxicity (single exposure) No information on product itself.

Component	Category	Route of exposure	Target organs
Diglycidyl Ether of Bisphenol A	Category 3	-	Respiratory tract irritation
Diglycidyl Ether of Bisphenol F	Category 3	-	Respiratory tract irritation
Alkyl Glycidyl Ether	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure) No information on product itself.

Aspiration hazard No information on product itself.

Potential acute health effects

- Eye Contact** Causes serious eye irritation.
- Inhalation** May cause respiratory irritation.
- Skin Contact** Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** Irritating to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye Contact** Adverse symptoms may include the following:
Pain
Watering
Redness
- Inhalation** Adverse symptoms may include the following:
Respiratory tract irritation
Coughing
- Skin Contact** Adverse symptoms may include the following:
Irritation
Redness
- Ingestion** No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Potential chronic health effects

- General** Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** No known significant effects or critical hazards.
- Mutagenicity** No known significant effects or critical hazards.
- Teratogenicity** No known significant effects or critical hazards.
- Developmental effects** No known significant effects or critical hazards.
- Fertility effects** No known significant effects or critical hazards.

Numerical measures of toxicity

- Acute toxicity estimates (ATEmix)** Not available

12. Ecological Information

Ecotoxicity

No information on product itself.

Component	Result	Species	Exposure
Diglycidyl Ether of Bisphenol A	Acute LC50 1.3 mg/l	Fish	96 h
	Acute LC50 2.1 mg/l	Daphnia	48 h
Diglycidyl Ether of Bisphenol F	Acute LC50 1.5 mg/l	Fish	96 h
	Acute LC50 1.7 mg/l	Daphnia	48 h
	Chronic NOEC 0.3 mg/l	Daphnia	21 d
Benzyl Alcohol	Acute LC50 460 mg/l	Fish	96 h
	Acute EC50 230 mg/l	Invertebrates	48 h
	Chronic NOEC 310 mg/l	Algae	72 h

Persistence and degradability

No information on product itself.

Bioaccumulative Potential

No information on product itself.

Component	LogPow	BCF	Potential
Diglycidyl Ether of Bisphenol A	2.64 – 3.78	3 – 31 31.00	low
Diglycidyl Ether of Bisphenol F	3	-	low
Benzyl Alcohol	1.05	1.37 (calculated)	-

Mobility in Soil**Soil/water partition coefficient (KOC)**

No information on product itself.

Other adverse effects

No known significant effects or critical hazards.

13. Disposal Considerations**Waste from residues/ unused products**

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Product should not be allowed to enter drains, water courses or the soil; dispose of this material and its containers in a safe way. Contact supplier if guidance is required.

Contaminated packaging

Dispose of container and unused contents in accordance with federal, state and local requirements.

14. Transport Information

The data provided in this section is for information only and may not be specific to your package size or mode of transport. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

International Transport Regulations

Regulatory information	UN/NA number	Proper Shipping Name	Classes/*PG	Additional Information
DOT		Non-regulated		
TDG		Non-regulated		

IMO/IMDG	UN3082	Environmentally hazardous substance, liquid, n.o.s. (Bisphenol-A Epichlorohydrin Resin)	Class 9 III
IATA	UN3082	Environmentally hazardous substance, liquid, n.o.s. (Bisphenol-A Epichlorohydrin Resin)	Class 9 III

*PG: Packing group

Special precautions for user:

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

15. Regulatory Information

UNITED STATES

U.S. Federal Regulations

United States – TSCA 12(b) – Chemical export notification: None Required.
United States – TSCA 5(a)2 – Final significant new use rules: Not Listed.
United States – TSCA 5(a)2 – Proposed significant new use rules: Not Listed.
United States – TSCA 5(e) – Substance consent order: Not listed.

Clean Air Act – Ozone Depleting Substances (ODS)

This product does not contain nor is it manufactured with ozone depleting substances.

**Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)
California Prop. 65**

None

WARNING: This product contains less than 0.1% of a chemical known to the State of California to cause cancer. WARNING: This product contains less than 1% of a chemical known to the State of California to cause birth defects or other reproductive harm.

Ingredient Name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
Oxirane, 2-(phenoxyethyl)-	Yes	No	5 µg/day	No
Oxirane, 2-(chloromethyl)-	Yes	Yes	9 µg/day	No

EPA SARA 302 Extremely Hazardous Substances

None required

EPA SARA 302/304/311/312 Hazardous Chemicals

Acute Health Hazard

SARA 313

None required

**Form R – Reporting requirements
United States inventory (TSCA 8b)**

All components are listed or exempted.

CANADA

WHMIS (Canada)

Class D-2B: Material causing other toxic effects (Toxic).

**Canadian NPRI
CEPA Toxic substances**

None required
None required

INTERNATIONAL REGULATIONS

International Lists

Australia inventory (AICS): All components are listed or exempted.
Canada inventory: All components are listed or exempted.
Korea inventory: All components are listed or exempted.
Japan inventory: All components are listed or exempted.
China inventory (IECSC): All components are listed or exempted.
New Zealand inventory (NZIoC): All components are listed or exempted.
Philippines inventory (PICCS): All components are listed or exempted.
Taiwan inventory (CSNN): All components are listed or exempted.

16. Other Information, Including Date of Preparation or Last Revision

HMIS Rating

Health 2
Flammability 1
Physical Hazard 0

Date of Preparation	January 14, 2020
Date of Last Revision	September 27, 2019
Revision #	5.0
More Information	1-253-333-8118
Prepared by	System Three Resins Inc.

The information contained herein is based on the data available to us and is believed to be correct. However, System Three Resins, Inc. makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. System Three assumes no responsibility for injury from the use of the product described herein.

1. Product Identification

Product name	SilverTip Fast Hardener, Part B
SDS Number	0900B
Product type	Amine curing agent.
Recommended use of the chemical and restrictions on use	Directed at, but not limited to, the laminating and coating of composite materials, wood, and inorganic substrates.
Restrictions	None known.
Manufacturer/Supplier information	
Company name	SYSTEM THREE RESINS, INC.
Address	8517 Commerce Place Dr NE Lacey, WA 98516 United States
Telephone	1-253-333-8118
Website	www.systemthree.com
Email	support@systemthree.com
Emergency Contact	CHEMTEL (U.S. and CANADA) 1-800-704-9215 CHEMTEL (Outside the U.S.) – Call Collect accepted +1-360-256-7365

2. Hazard(s) Identification

Classification of substance or mixture/Signal Word	DANGER Acute Toxicity: Oral – Category 4 Acute Toxicity: Inhalation – Category 4 Skin Corrosion/Irritation – Category 1 Serious Eye Damage/Eye Irritation – Category 1 Skin Sensitization – Category 1 Reproductive Toxicity – Category 1 Specific Target Organ Toxicity (Single Exposure) [Respiratory tract irritation] – Category 3 Aquatic Hazard (Acute) – Category 1 Aquatic Hazard (Long-term) – Category 1
---	---

GHS Label Elements
Hazard Pictograms

Hazard Statements/Classification of substance or mixture	H302 Harmful if swallowed. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H332 Harmful if inhaled. H335 May cause respiratory irritation. H360 May damage fertility or the unborn child. H400 Very toxic to aquatic life.
---	---

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

Precautionary Statements

Prevention

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P261 Avoid breathing vapor.
P264 Wash hands thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.

Response

P273 Avoid release to the environment.
P280 Wear protective gloves. Wear eye or face protection.
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER or doctor/physician.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Storage

P362 + P364 Take off contaminated clothing and wash it before reuse.
P405 Store locked up.

Disposal

P501 Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazards not otherwise classified (HNOC)

None known.

3. Composition/Information On Ingredients

Chemical Name	CAS Number	Content (%)
Isophorone Diamine	2855-13-2	60 – 70%
p-tert-Butylphenol	98-54-4	5 – 10%
Benzyl Alcohol	100-51-6	15 – 20%
1,3-benzenedimethanamine	1477-55-0	5 – 10%
Nonyl Phenol	84852-15-3	5 – 10%

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.

4. First-Aid Measures

Skin contact

Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Eye contact

Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and

lower eyelids. Check for and remove contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

Ingestion

Do not induce vomiting without medical advice. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Prevent aspiration of vomit. Never give anything by mouth to an unconscious person.

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.

Specific treatments

No specific treatment.

5. Fire-Fighting Measures

Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide (CO₂), dry chemical, water fog.

Unsuitable extinguishing media

None known.

Specific hazards arising from the chemical

In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous decomposition products

Decomposition products may include the following materials:
Carbon dioxide
Carbon monoxide

Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Further information

Do not allow run-off from firefighting to enter drains or water courses. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

6. Accidental Release Measures

Personal precautions

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Wear proper protective clothing, gloves and eye/face protection.

Emergency procedures

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

Methods and materials for containment/cleanup

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal

contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

7. Handling and Storage

Precautions for safe handling

Put on appropriate personal protective equipment. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid contact with skin and eyes. Emergency showers and eye wash stations should be readily accessible. When using, do not eat, drink or smoke.

Precautions/Recommendations for safe/proper storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure Controls/Personal Protection

Occupational Exposure Limits

None established.

Appropriate engineering controls

Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. Do not allow spill to enter sewers or waterways.

Individual protection measures/Personal protective equipment

Eye/face protection

Splash-proof goggles or safety spectacles with side shields are recommended. Always wear eye protection when sanding cured epoxy resins to avoid dust in eyes.

Hand protection

Always wear impervious gloves: butyl rubber, nitrile rubber, Neoprene, PVC disposable gloves.

Skin protection

Wear clean, body-covering clothing to avoid skin contact.

Respiratory protection

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Special instructions for protection and hygiene

Discard contaminated leather articles. Remove contaminated clothing. Wash at the end of each work shift and before eating smoking or using the toilet. Provide readily accessible eye wash stations and safety showers.

9. Physical and Chemical Properties

Chemical family	Amine curing agent
Appearance	Clear liquid
Physical State	Amine mixture
Form	Liquid
Color	Colorless
Odor	Ammoniacal
Density (Specific Gravity)	0.9 – 1.0
Viscosity	525 CPS @77°F (25°C)
pH	N/A
Melting point/freezing point	N/A
Initial boiling point and boiling range	N/A
Flash point	N/A
Evaporation rate	Slower than ether
Flammability (solid, gas)	N/A
Upper/lower flammability limit (by volume)	N/A
Material VOC	None
Vapor density	Heavier than air
Relative density	N/A
Solubility in water	Negligible
Partition coefficient: n-octanol/water	N/A
Auto-ignition temperature	N/A
Decomposition temperature	N/A

10. Stability and Reactivity

Reactivity	None.
Chemical Stability	Stable under normal conditions.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	Do not freeze. Avoid exposure to air, moisture, ignition sources and elevated temperatures.
Incompatible materials	Reactive or incompatible with the following materials: Organic acids Mineral acids Sodium hypochlorite Oxidizing agents
Hazardous decomposition products	Carbon monoxide Carbon dioxide Nitrogen oxides
Other hazards	None known.

11. Toxicological Information

Acute Health Hazard (components)

No comprehensive data (ingestion, inhalation, dermal) on mixture (product).

Component	Result	Species	Dose	Exposure
Isophorone Diamine	LD50 Oral	Rat	1,030 mg/kg	-
	LD50 Dermal	Rat	>2,000 mg/kg	-
	LC50 Inhalation	Rat	>5.01 mg/l	4 h
Nonyl Phenol	LD50 Dermal	Rabbit	2,031 mg/kg	-
	LD50 Oral	Rat	1,412 mg/kg	-
Benzyl Alcohol	LD50 Oral	Rat	1,620 mg/kg	-
	LC50 Inhalation	Rat	>4,178 mg/kg	4 h, aerosol
2-Methyl-1,5-pentamethylenediamine	LD50 Dermal	Rabbit	1870 mg/kg	-
	LD50 Oral	Rat	1170 mg/kg	-
	LC50 Inhalation	Rat	4.9 mg/l/1h	-
Para-tertiary-butylphenol	LD50 Dermal	Rabbit	2,520 mg/kg	-
	LD50 Oral	Rat	5,660 mg/kg	-
1,3-Benzenedimethanamine	LD50 Dermal	Rabbit	2,000 mg/kg	-
	LD50 Oral	Rat	930 mg/kg	-

Irritation/Corrosion (components)

Classifies as corrosive per positive GHS calculation on additivity.

Component	Result	Species	Test	Exposure
Isophorone Diamine	Skin – Corrosive	Rabbit	OECD 404 Acute Dermal Irritation/Corrosion	-
	Eyes – Corrosive	Rabbit	OECD 405 Acute Eye Irritation/Corrosion	-
Benzyl Alcohol	Eye – Irritant	Rabbit	OECD 405 Acute Eye Irritation/Corrosion	-
Para-tertiary-butylphenol	Irritation	-	Skin	-
	Serious eye irritation	-	Eye	-

Sensitization

No data is available on the product itself.

Mutagenicity

No data is available on the product itself.

Carcinogenicity

No data is available on the product itself.

Reproductive Toxicity

No data is available on the product itself.

Teratogenicity

No data is available on the product itself.

Specific target organ toxicity (single exposure)

No data is available on the product itself.

Component	Category	Route of exposure	Target organs
2-Methyl-1,5-pentamethylenediamine	Category 3		Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

No data is available on the product itself.

Aspiration hazard

No data is available on the product itself.

Potential acute health effects

Eye Contact	Causes serious eye damage.
Inhalation	May cause respiratory irritation.
Skin Contact	Causes severe burns. Harmful in contact with skin. May cause an allergic skin reaction.
Ingestion	Harmful if swallowed. May cause burns to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

Eye Contact	Adverse symptoms may include the following: Pain or irritation Watering Redness
Inhalation	Adverse symptoms may include the following: Respiratory tract irritation Coughing
Skin Contact	Adverse symptoms may include the following: Pain or irritation Redness Blistering may occur
Ingestion	Adverse symptoms may include the following: Stomach pains

Delayed and immediate effects and also chronic effects from short and long term exposure

No data is available on the product itself.

Potential chronic health effects

General	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates (ATEmix)

Route	ATE value
Oral	1614.6 mg/kg
Dermal	3194.6 mg/kg
Inhalation (vapors)	13.75 mg/l

12. Ecological Information

Ecotoxicity

No data is available on the product itself.

Component	Endpoint	Exposure	Species	Result
Isophorone Diamine	Acute LC50	96 h	Fish	110 mg/l
	Acute EC50	48 h	Daphnia magna	23 mg/l

	Acute EC50	72 h	Scenedesmus subspicatus	>50 mg/l
Nonyl Phenol	Acute EC50	3 h Static	Bacteria	950 mg/l
	Acute EC50	48 h Static	Daphnia	0.085 mg/l
	Acute LC50	96 h Static	Fish	0.05 mg/l
Benzyl Alcohol	Acute LC50	96 h	Fish	460 mg/l
	Acute EC50	48 h	Invertebrates	230 mg/l
	Chronic NOEC	21 d	Invertebrates	51 mg/l
	Acute EC50	72 h	Algae	770 mg/l
	Chronic NOEC	72 h	Algae	310 mg/l
2-Methyl-1,5-pentamethylenediamine	Acute EC50	72 h	Algae	>100 mg/l
	Acute EC50	48 h	Daphnia	19.8 mg/l
	-	-	Fish	1825 mg/l
Para-tertiary-butylphenol	LC50	96 h	Fish	5.14 mg/l
	EC50	48 h	Daphnia magna	4.8 mg/l
1,3-Benzenedimethanamine	LC50 OECD 203	96 h	Fish	87.6 mg/l
	EC50 OECD 202	48 h	Daphnia magna	15.2 mg/l
	NOEC OECD 211	21 d	Daphnia magna	4.7 mg/l

Persistence and degradability No data is available on the product itself.

Component	Test	Period	Result
Nonyl Phenol	OECD 301B Ready Biodegradability – CO2 Evolution Test	35 days	48.2%
Benzyl Alcohol	-	-	Readily biodegradable
1,3-Benzenedimethanamine	OECD 301B	28 d	49%

Bioaccumulative Potential No data is available on the product itself.

Component	LogPow	BCF	Potential
Nonyl Phenol	5.4	740	High
Benzyl Alcohol	1.05	1.37 (calculated)	-
Para-tertiary-butylphenol	3.31	-	-
1,3-Benzenedimethanamine	-	3.16 l/kg (calculated)	-

Mobility in Soil No data is available on the product itself.

Soil/water partition coefficient (KOC) No data is available on the product itself.

Other adverse effects No known significant effects or critical hazards.

13. Disposal Considerations

Waste from residues/ unused products

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Product should not be allowed to enter drains, water courses or the soil; dispose of this material and its containers in a safe way. Contact supplier if guidance is required.

Contaminated packaging

Dispose of container and unused contents in accordance with federal, state and local requirements.

14. Transport Information

The data provided in this section is for information only and may not be specific to your package size or mode of transport. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

International Transport Regulations

Regulatory information	UN/NA number	Proper Shipping Name	Classes/*PG	Additional Information
DOT	UN2735	Amines, liquid, corrosive, n.o.s. (Isophorone diamine, para-tert-butylphenol)	Class 8 III	Marine pollutant
TDG	UN2735	Amines, liquid, corrosive, n.o.s. (Isophorone diamine, para-tert-butylphenol)	Class 8 III	Marine pollutant
IMO/IMDG	UN2735	Amines, liquid, corrosive, n.o.s. (Isophorone diamine, para-tert-butylphenol)	Class 8 III	Marine pollutant
IATA	UN2735	Amines, liquid, corrosive, n.o.s. (Isophorone diamine, para-tert-butylphenol)	Class 8 III	

*PG: Packing group

Special precautions for user:

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

15. Regulatory Information

UNITED STATES**U.S. Federal Regulations**

United States – TSCA 12(b) – Chemical export notification: None Required.
United States – TSCA 5(a)2 – Final significant new use rules: Not Listed.
United States – TSCA 5(a)2 – Proposed significant new use rules: Not Listed.
United States – TSCA 5(e) – Substance consent order: Not listed.

Clean Air Act – Ozone Depleting Substances (ODS)

This product does not contain nor is it manufactured with ozone depleting substances.

Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)

Product Name	Concentration %
Phenol	0 – 1%

Pennsylvania – RTK

Phenol, 4-tert-Butylphenol

California Prop. 65

This product does not contain any chemicals known to the state of California to cause cancer, birth defects or any other harm.

EPA SARA 302 Extremely Hazardous Substances

None required.

EPA SARA 302/304/311/312 Hazardous Chemicals

Acute Health Hazard, Chronic Health Hazard

SARA 313**Form R – Reporting requirements**

Product Name	Concentration %
Phenol	0 – 1%

CERCLA Hazardous substances

Component	%	Section 304 CERCLA	CERCLA Reportable	Product Reportable

		Hazardous Substance	Quantity (Lbs)	Quantity (Lbs)
Phenol	1	Listed		

United States inventory (TSCA 8b)

All components are listed or exempted.

CANADA

WHMIS (Canada)

Class D-2B: Material causing other toxic effects (Toxic).
Class E: Corrosive material.

**Canadian NPRI
CEPA Toxic substances**

None required.
None required.

INTERNATIONAL REGULATIONS

International Lists

Australia inventory (AICS): All components are listed or exempted.
Canada inventory: All components are listed or exempted.
Korea inventory: All components are listed or exempted.
Japan inventory: All components are listed or exempted.
China inventory (IECSC): All components are listed or exempted.
New Zealand inventory (NZIoC): All components are listed or exempted.
Philippines inventory (PICCS): All components are listed or exempted.
Taiwan inventory (CSNN): All components are listed or exempted.

16. Other Information, Including Date of Preparation or Last Revision

HMIS Rating

Health 3
Flammability 1
Physical Hazard 0

Date of Preparation January 14, 2020
Date of Last Revision September 27, 2019
Revision # 4.0
More Information 1-253-333-8118
Prepared by System Three Resins Inc.

The information contained herein is based on the data available to us and is believed to be correct. However, System Three Resins, Inc. makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. System Three assumes no responsibility for injury from the use of the product described herein.

1. Product Identification

Product name	SilverTip Slow Hardener, Part B
SDS Number	0901B00
Product type	Amine curing agent.
Recommended use of the chemical and restrictions on use	Directed at, but not limited to, the laminating and coating of composite materials, wood, and inorganic substrates.
Restrictions	None known.
Manufacturer/Supplier information	
Company name	SYSTEM THREE RESINS, INC.
Address	8517 Commerce Place Dr NE Lacey, WA 98516 United States
Telephone	1-253-333-8118
Website	www.systemthree.com
Email	support@systemthree.com
Emergency Contact	CHEMTEL (U.S. and CANADA) 1-800-704-9215 CHEMTEL (Outside the U.S.) – Call Collect accepted +1-360-256-7365

2. Hazard(s) Identification

Classification of substance or mixture/Signal Word	DANGER Acute Toxicity: Oral – Category 4 Skin Corrosion/Irritation – Category 1 Serious Eye Damage/Eye Irritation – Category 1 Skin Sensitization – Category 1 Specific Target Organ Toxicity (Single Exposure) – Category 3 Aquatic Hazard (Acute) – Category 3 Aquatic Hazard (Long-term) – Category 3
---	---

GHS Label Elements
Hazard Pictograms



Hazard Statements/Classification of substance or mixture	H302 Harmful if swallowed. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H335 May cause respiratory irritation. H402 Harmful to aquatic life. H412 Harmful to aquatic life with long lasting effects.
---	---

Precautionary statements

Precautionary Statements
Prevention

P201 Obtain special instructions before use.

	P202 Do not handle until all safety precautions have been read and understood.
	P261 Avoid breathing vapor.
	P264 Wash hands thoroughly after handling.
	P270 Do not eat, drink or smoke when using this product.
	P271 Use only outdoors or in a well-ventilated area.
	P272 Contaminated work clothing should not be allowed out of the workplace.
	P273 Avoid release to the environment.
	P280 Wear protective gloves. Wear eye or face protection.
Response	P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
	P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
	P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
	P310 Immediately call a POISON CENTER or doctor/physician.
Storage	P362 + P364 Take off contaminated clothing and wash it before reuse.
Disposal	P405 Store locked up.
	P501 Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards not otherwise classified (HNOC)	None known.

3. Composition/Information On Ingredients

Chemical Name	CAS Number	Content (%)
Aliphatic Amine Mixture	Trade Secret	70 – 80%
Alkyl Phenol Mixture	Trade Secret	15 – 20%
Benzyl Alcohol	100-51-6	15 – 15%

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.

4. First-Aid Measures

Skin contact

Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Eye contact

Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

Ingestion

Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting without medical advice. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical

attention if adverse health effects persist or are severe. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain open airway. Loosed tight clothing such as a collar, tie, belt, or waistband.

Inhalation

Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain open airway. Loosen tight clothing such as a collar, tie, belt, or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.

Specific treatments

No specific treatment.

5. Fire-Fighting Measures

Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide (CO₂), dry chemical, water fog.

Unsuitable extinguishing media

None known.

Specific hazards arising from the chemical

In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous decomposition products

Decomposition products may include the following materials:

Carbon dioxide

Carbon monoxide

Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Further information

Do not allow run-off from firefighting to enter drains or water courses. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

6. Accidental Release Measures

Personal precautions

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Wear proper protective clothing, gloves and eye/face protection.

Emergency procedures

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

Methods and materials for containment/cleanup

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material

e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

7. Handling and Storage

Precautions for safe handling

Put on appropriate personal protective equipment. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid contact with skin and eyes. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. When using, do not eat, drink or smoke. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Precautions/Recommendations for safe/proper storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure Controls/Personal Protection

Occupational Exposure Limits

None established.

Appropriate engineering controls

Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. Do not allow spill to enter sewers or waterways.

Individual protection measures/Personal protective equipment

Eye/face protection

Splash-proof goggles or safety spectacles with side shields are recommended. Always wear eye protection when sanding cured epoxy resins to avoid dust in eyes.

Hand protection

Always wear impervious gloves: butyl rubber, nitrile rubber, Neoprene, PVC disposable gloves.

Skin protection

Wear clean, body-covering clothing to avoid skin contact.

Respiratory protection

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator

Special instructions for protection and hygiene

selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Discard contaminated leather articles. Remove contaminated clothing. Wash at the end of each work shift and before eating smoking or using the toilet. Provide readily accessible eye wash stations and safety showers.

9. Physical and Chemical Properties

Chemical family	Amine curing agent
Appearance	Clear liquid
Physical State	Amine mixture
Form	Liquid
Color	Colorless
Odor	Ammoniacal
Density (Specific Gravity)	0.9 – 1.0
Viscosity	525 CPS @77°F (25°C)
pH	N/A
Melting point/freezing point	N/A
Initial boiling point and boiling range	N/A
Flash point	N/A
Evaporation rate	Slower than ether
Flammability (solid, gas)	N/A
Upper/lower flammability limit (by volume)	N/A
Upper flammability limit (by volume)	N/A
Lower flammability limit (by volume)	N/A
Material VOC	None
Vapor density	Heavier than air
Relative density	N/A
Solubility in water	Negligible
Partition coefficient: n-octanol/water	N/A
Auto-ignition temperature	N/A
Decomposition temperature	N/A

10. Stability and Reactivity

Reactivity	None.
Chemical Stability	Stable under normal conditions.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	Do not freeze. Avoid exposure to air, moisture, ignition sources and elevated temperatures.
Incompatible materials	Reactive or incompatible with the following materials: Organic acids

Hazardous decomposition products	Strong acids Halogenated compounds Carbon monoxide Carbon dioxide
Other hazards	Nitrogen oxides None known.

11. Toxicological Information

Acute Health Hazard (components) No comprehensive data (ingestion, inhalation, dermal) on mixture (product).

Component	Result	Species	Dose	Exposure
Benzyl Alcohol	LD50 Oral	Rat	1,620 mg/kg	-
	LC50 Inhalation	Rat	>4,178 mg/kg	4 h, aerosol

Irritation/Corrosion (components) Classifies as corrosive per positive GHS calculation on additivity.

Component	Result	Species	Test	Exposure
Benzyl Alcohol	Eye – Irritant	Rabbit	OECD 405 Acute Eye Irritation/Corrosion	-
Aliphatic Amine Mixture	Corrosive		Calculated	

Sensitization No data is available on the product itself.

Mutagenicity No data is available on the product itself.

Carcinogenicity No data is available on the product itself.

Reproductive Toxicity No data is available on the product itself.

Teratogenicity No data is available on the product itself.

Specific target organ toxicity (single exposure) No data is available on the product itself.

Specific target organ toxicity (repeated exposure) No data is available on the product itself.

Aspiration hazard No data is available on the product itself.

Potential acute health effects

Eye Contact	Causes serious eye damage.
Inhalation	May cause respiratory irritation.
Skin Contact	Causes severe burns. Harmful in contact with skin. May cause an allergic skin reaction.
Ingestion	Harmful if swallowed. May cause burns to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

Eye Contact	Adverse symptoms may include the following: Pain or irritation Watering Redness
Inhalation	Adverse symptoms may include the following: Respiratory tract irritation Coughing
Skin Contact	Adverse symptoms may include the following: Pain or irritation Redness

Ingestion

Blistering may occur

Adverse symptoms may include the following:
Stomach pains**Delayed and immediate effects and also chronic effects from short and long term exposure**

No data is available on the product itself.

Potential chronic health effects**General**

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity

No known significant effects or critical hazards.

Mutagenicity

No known significant effects or critical hazards.

Teratogenicity

No known significant effects or critical hazards.

Developmental effects

No known significant effects or critical hazards.

Fertility effects

No known significant effects or critical hazards.

Numerical measures of toxicity**Acute toxicity estimates (ATEmix)**

Route	ATE value
Oral	1918.8 mg/kg
Dermal	3271.1 mg/kg
Inhalation (vapors)	N/A

12. Ecological Information**Ecotoxicity**

No data is available on the product itself.

Component	Endpoint	Exposure	Species	Result
Benzyl Alcohol	Acute LC50	96 h	Fish	460 mg/l
	Acute EC50	48 h	Invertebrates	230 mg/l
	Chronic NOEC	21 d	Invertebrates	51 mg/l
	Acute EC50	72 h	Algae	770 mg/l
	Chronic NOEC	72 h	Algae	310 mg/l

Persistence and degradability

No data is available on the product itself.

Component	Test	Period	Result
Benzyl Alcohol	-	-	Readily biodegradable

Bioaccumulative Potential

No data is available on the product itself.

Component	LogPow	BCF	Potential
Benzyl Alcohol	1.05	1.37 (calculated)	-

Mobility in Soil

No data is available on the product itself.

Soil/water partition coefficient (KOC)

No data is available on the product itself.

Other adverse effects

No known significant effects or critical hazards.

13. Disposal Considerations

Waste from residues/ unused products	The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Product should not be allowed to enter drains, water courses or the soil; dispose of this material and its containers in a safe way. Contact supplier if guidance is required.
Contaminated packaging	Dispose of container and unused contents in accordance with federal, state and local requirements.

14. Transport Information

The data provided in this section is for information only and may not be specific to your package size or mode of transport. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

International Transport Regulations

Regulatory information	UN/NA number	Proper Shipping Name	Classes/*PG	Additional Information
DOT	UN2735	Amines, liquid, corrosive, n.o.s. (Isophorone diamine, para-tert-butylphenol)	Class 8 III	Marine pollutant
TDG	UN2735	Amines, liquid, corrosive, n.o.s. (Isophorone diamine, para-tert-butylphenol)	Class 8 III	Marine pollutant
IMO/IMDG	UN2735	Amines, liquid, corrosive, n.o.s. (Isophorone diamine, para-tert-butylphenol)	Class 8 III	Marine pollutant
IATA	UN2735	Amines, liquid, corrosive, n.o.s. (Isophorone diamine, para-tert-butylphenol)	Class 8 III	

*PG: Packing group

Special precautions for user: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

15. Regulatory Information

UNITED STATES

U.S. Federal Regulations	United States – TSCA 12(b) – Chemical export notification: None Required. United States – TSCA 5(a)2 – Final significant new use rules: Not Listed. United States – TSCA 5(a)2 – Proposed significant new use rules: Not Listed. United States – TSCA 5(e) – Substance consent order: Not listed.
Clean Air Act – Ozone Depleting Substances (ODS)	This product does not contain nor is it manufactured with ozone depleting substances.
Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)	None known.
California Prop. 65	This product does not contain any chemicals known to the state of California to cause cancer, birth defects or any other harm.
EPA SARA 302 Extremely Hazardous Substances	None known.

EPA SARA 302/304/311/312 Hazardous Chemicals Acute Health Hazard
United States inventory (TSCA 8b) All components are listed or exempted.

CANADA

WHMIS (Canada) Class D-2B: Material causing other toxic effects (Toxic).
Class E: Corrosive material.

Canadian NPRI None required.
CEPA Toxic substances None required.

INTERNATIONAL REGULATIONS

International Lists
Australia inventory (AICS): All components are listed or exempted.
Canada inventory: All components are listed or exempted.
Korea inventory: All components are listed or exempted.
Japan inventory: All components are listed or exempted.
China inventory (IECSC): All components are listed or exempted.
New Zealand inventory (NZIoC): All components are listed or exempted.
Philippines inventory (PICCS): All components are listed or exempted.
Taiwan inventory (CSNN): All components are listed or exempted.

16. Other Information, Including Date of Preparation or Last Revision

HMIS Rating

Health 3
Flammability 1
Physical Hazard 0

Date of Preparation January 14, 2020
Date of Last Revision September 27, 2019
Revision # 4.0
More Information 1-253-333-8118
Prepared by System Three Resins Inc.

The information contained herein is based on the data available to us and is believed to be correct. However, System Three Resins, Inc. makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. System Three assumes no responsibility for injury from the use of the product described herein.