

Safety Data Sheets (SDS) Updated: January 1, 2023

This file contains Safety Data Sheets for EZ-Fillet. This is a two-component system. It is imperative that you know whether you need information on the Resin or the Hardener.

Resin: Pages 2-10 Hardener: Pages 11-19

If this is a medical emergency, call 911 or your local poison control center. Seek medical attention.

For technical assistance, call System Three Technical Support at 253-333-8118 option 2.

These SDS are provided pursuant to 29 CFR 1910.1200(g).



SAFETY DATA SHEET

1. Product Identification

Product name	EZ-Fillet Resin, Part A	
SDS Number	1430A00	
Product type	Epoxy polymer mixture.	
Recommended use of the chemical and restrictions on use	Directed at, but not limited to, the filling and reinfor	rcing of wood structures.
Restrictions	None known.	
Manufacturer/Supplier information		
Company name	SYSTEM THREE RESINS, INC.	
Address	8517 Commerce Place Dr NE Lacey, WA 98516 United States	
Telephone	1-253-333-8118	
Website	www.systemthree.com	
Email	support@systemthree.com	
Emergency Contact	CHEMTEL (U.S. and CANADA) CHEMTEL (Outside the U.S.) – Call Collect accepted	1-800-704-9215 +1-360-256-7365

2. Hazard(s) Identification

Classification of substance or mixture/Signal Word	WARNING. Skin Corrosion/Irritation - Category 2 Serious Eye Damage/Eye Irritation - Category 2 Skin Sensitizer – Category 1 Specific Target Organ Toxicity (Single Exposure) [Respiratory tract irritation] – Category 3
GHS Label Elements Hazard Pictograms	
Hazard Statements/Classification of substance or mixture	 H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation.
Precautionary statements	n355 May cause respiratory initiation.
<u>Precautionary Statements</u> Prevention	 P261 Avoid breathing vapors. P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves. Wear eye or face protection.
Response	P302 + P352 IF ON SKIN: Wash with soap and water.

Storage Disposal	 P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308 + P313 If exposed or concerned: Get medical attention. P312 Call a POISON CENTER/doctor if you feel unwell. P332 + P313 If skin irritation occurs: Get medical advice/attention. P337 + P313 If eye irritation persists: Get medical advice/attention. P362 + P364 Take off contaminated clothing and wash it before reuse. P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P501 Dispose of contents and container in accordance with all local,
Hazards not otherwise classified (HNOC)	regional, national and international regulations. None Available

3. Composition/Information On Ingredients

Chemical Name	CAS Number	Content (%)
Diglycidyl Ether of Bisphenol A	25068-38-6	50 – 60 %
Alkyl Glycidyl Ether	17557-23-2	10-15%
Benzyl Alcohol	100-51-6	1-10%
Diglycidyl Ether of Bisphenol F	28064-14-4	1-10%

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.

4. First-Aid Measures

Skin contact	Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation persists. Wash clothing before reuse. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watch bands.
Eye contact	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 15 minutes. Suitable emergency eye wash facility should be available in work area. Get medical attention immediately if irritation persists.
Ingestion	Get medical attention immediately. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Inhalation	Get medical attention immediately. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	No specific treatment.

5. Fire-Fighting Measures

Suitable extinguishing media Unsuitable extinguishing media Specific hazards arising from the chemical	Alcohol-resistant foam, dry chemical, water fog or carbon dioxide (CO2). None known. In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous decomposition products	Decomposition products may include the following materials: Carbon dioxide Carbon monoxide
Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire- fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Further information	Do not allow run-off from firefighting to enter drains or water courses. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

6. Accidental Release Measures

Personal precautions	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Wear proper protective clothing, gloves and eye/face protection.
Emergency procedures	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.
Methods and materials for containment/cleanup	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

7. Handling and Storage

Precautions for safe handlingPut on appropriate personal protective equipment. Persons with a history of
skin sensitization problems should not be employed in any process in which
this product is used. Avoid contact with skin and eyes. Do not ingest. Avoid
breathing vapor or mist. Use only with adequate ventilation. Wear appropriate
respirator when ventilation is inadequate. Keep in the original container or an
approved alternative made from a compatible material, kept tightly closed
when not in use. Empty containers retain product residue and can be
hazardous. Do not reuse container. When using, do not eat, drink or smoke.

Workers should wash hands and face before eating, drinking and smoking.
Remove contaminated clothing and protective equipment before entering
eating areas. See also Section 8 for additional information on hygiene
measures.Precautions/Recommendations for
safe/proper storageStore in accordance with local regulations. Store in original container protected
from direct sunlight in a dry, cool and well-ventilated area, away from
incompatible materials and food and drink. Store locked up. Keep container
tightly closed and sealed until ready for use. Containers that have been opened
must be carefully resealed and kept upright to prevent leakage. Do not store in
unlabeled containers. Use appropriate containment to avoid environmental

contamination.

8. Exposure Controls/Personal Protection

Occupational Exposure Limits	None established.
Appropriate engineering controls	Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	Use appropriate containment to avoid environmental contamination. Do not allow spill to enter sewers or waterways.
Individual protection measures/Personal	
protective equipment	
Eye/face protection	Splash-proof goggles or safety spectacles with side shields are recommended. Always wear eye protection when sanding cured epoxy resins to avoid dust in eyes.
Hand protection	Always wear impervious gloves: butyl rubber, nitrile rubber, Neoprene, PVC disposable gloves,
Skin protection	Wear clean, body-covering clothing to avoid skin contact.
Respiratory protection	Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Special instructions for protection and hygiene	Discard contaminated leather articles. Remove contaminated clothing. Wash at the end of each work shift and before eating smoking or using the toilet. Provide readily accessible eye wash stations and safety showers.

9. Physical and Chemical Properties

Chemical family	Epoxy Resin
Appearance	Reddish-Brown Paste
Physical State	Epoxy polymer mixture
Form	Paste
Color	Reddish-Brown
Odor	Little to no odor
Density (Specific Gravity)	1.13
Viscosity	150,000 – 250,000 CPS @77°F
рН	N/A
Melting point/freezing point	N/A
Initial boiling point and boiling range	N/A
Flash point	>300°F (Pensky-Martens Closed Cup)

Evaporation rate	Slower than ether
Flammability (solid, gas)	N/A
Upper/lower flammability limit (by volume)	N/A
Upper flammability limit (by volume)	N/A
Lower flammability limit (by volume)	N/A
Material VOC	None
Vapor density	Heavier than air
Relative density	N/A
Solubility in water	Negligible
Partition coefficient: n-octanol/water	N/A
Auto-ignition temperature	N/A
Decomposition temperature	N/A

10.Stability and Reactivity

Reactivity	Stable
Chemical Stability	Stable under normal conditions.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	Extremes of temperature and direct sunlight.
Incompatible materials	Reactive or incompatible with the following materials: Strong oxidizing agents Strong acids Aliphatic amines
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Other hazards	Reacts with considerable heat release with some curing agents.

11. Toxicological Information

Acute Health Hazard (components) No comprehensive data (ingestion, inhalation, dermal) on mixture (product).

Component	Result	Species	Dose	Exposure
Diglycidyl Ether of Bisphenol A	LD50 Oral	Rat	11,400 mg/kg	-
	LD50 Dermal	Rat	2,000 mg/kg	-
Alkyl Glycidyl Ether	LD50 Oral	Rat	4,500 mg/kg	-
Diglycidyl Ether of Bisphenol F	LD50 Oral	Rat	>2,000 mg/kg	-
	LD50 Dermal	Rat	>2,000 mg/kg	-
Benzyl Alcohol	LD50 Oral	Rat	1620 mg/kg	-
	LC50 Inhalation	Rat	>4178 mg/m3	4 h, aerosol
rritation/Corrosion (components) No data	is available for this	product.	ł
Component	Result	Species	Test	Exposure

Diglycidyl Ether of Bisphenol A	Moderate to severe irritation	Rabbit	Skin	4 h
	Mild irritation	Rabbit	Eye	24 h
Diglycidyl Ether of Bisphenol F	Mild irritant	Rabbit	Skin	-
	Mild irritant	Rabbit	Eye	-
Benzyl Alcohol	Non-irritant	Rabbit	Skin	-
	Irritant	Rabbit	Eye	-
<u>Sensitization</u>	No data is	available for this	s product.	
Mutagenicity	No data is	available for this	s product.	
Carcinogenicity	No data is	available for this	s product.	
Reproductive Toxicity	No data is	available for this	s product.	
Teratogenicity	No data is	available for this	s product.	
Specific target organ toxicity (sing	le No data is	available for this	s product.	
<u>exposure)</u> Component	Category	Route of exp	osure	Target organs
Diglycidyl Ether of Bisphenol A	Category 3			Respiratory tract irritation
Alkyl Glycidyl Ether	Category 3			Respiratory tract irritation
Diglycidyl Ether of Bisphenol F	Category 3			Respiratory tract irritation
Specific target organ toxicity (repe		available for this	product	
exposure)	<u>eated</u> No data is		s product.	
Aspiration hazard	No data is	available for this	s product.	
Potential acute health effects				
Eye Contact	Causes ser	rious eye irritatio	on.	
Inhalation	May cause	e respiratory irrit	ation.	
Skin Contact	Causes ski	n irritation. May	cause an allergic s	kin reaction.
Ingestion	Irritating t	o mouth, throat	and stomach.	
Symptoms related to the physical,	<u>chemical</u>			
and toxicological characteristics Eye Contact	Adverse sv	ymptoms may in	clude the following	2:
	Pain or irr			
	Watering Redness			
Inhalation		ymptoms may in	clude the following	2:
		ry tract irritation		
Irritation Pain		ymptoms may in	clude the following	<u>;</u> :
Ingestion	Redness No specifi	c data		
-				
Delayed and immediate effects an chronic effects from short and long		ue.		
<u>exposure</u> Potential chronic health effects				

General	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.
Numerical measures of toxicity	
Acute toxicity estimates (ATEmix)	Not available.

12. Ecological Information

Component	Test	Specie	es	Result		Exposure
Diglycidyl Ether of Bisphenol A	LC50	Fish		1.3 mg/l		96 h
	LC50	Daphr	nia	2.1 mg/l		48 h
Diglycidyl Ether of Bisphenol F	LC50	Fish		1.5 mg/l		96 h
	LC50	Daphr	nia	1.7 mg/l		48 h
	Chronic NOEC	Daphr	nia	0.3 mg/l		21 d
Benzyl Alcohol	LC50	Fish		460 mg/l		96 h
	EC50	Invert	ebrates	230 mg/l		48 h
	EC50	Algae		770 mg/l		72 h
	Chronic NOEC	Algae		310 mg/l		72 h
Persistence and degradability	No info	ormation o	n the produ	ct itself.		
Component	Test		Period		Resul	t
Diglycidyl Ether of Bisphenol A	OECD 302B		28 d		12%	
Diglycidyl Ether of Bisphenol F	OECD 301F Derived	k	28 d		5%	
Benzyl Alcohol					Readi	ly Biodegradable
Bioaccumulative Potential	No info	ormation o	n the produ	ct itself.		
Component	LogPow		BCF		Poten	tial
Diglycidyl Ether of Bisphenol A	2.64 - 3.78		3 - 31		Low	
Diglycidyl Ether of Bisphenol F	3.242		31		Low	
Alkyl glycidyl Ether	0.23		-		Low	

Soil/water partition coefficient (KOC)

No information on the product itself.

Other adverse effects

No know significant effects or critical hazards.

13. Disposal Considerations

Waste from residues/ unused products

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times

	comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Product should not be allowed to enter drains, water courses or the soil; dispose of this material and its containers in a safe way. Contact supplier if guidance is required.
Contaminated packaging	Dispose of container and unused contents in accordance with federal, state and local requirements.

14.Transport Information

The data provided in this section is for information only and may not be specific to your package size or mode of transport. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

International Transport Regulations					
Regulatory information	UN/NA number	Proper Shipping Name	Classes/*PG	Additional Information	
DOT		Non-regulated			
TDG		Non-regulated			
IMO/IMDG	UN3082	Environmentally Hazardous Substance, Liquid, N.O.S. (Bisphenol-A Epichlorohydrin Resin)	Class 9 III		
ΙΑΤΑ	UN3082	Environmentally Hazardous Substance, Liquid, N.O.S. (Bisphenol-A Epichlorohydrin Resin)	Class 9 III		
*PG: Packing group	0				
Special precautions for user:		Transport within user's premises: always upright and secure. Ensure that persons t do in the event of an accident or spillage.	ransporting the pro		

15. Regulatory Information

UNITED STATES

U.S. Federal Regulations	United States – TSCA 12(b) – Chemical export notification: None Required. United States – TSCA 5(a)2 – Final significant new use rules: Not Listed. United States – TSCA 5(a)2 – Proposed significant new use rules: Not Listed. United States – TSCA 5(e) – Substance consent order: Not listed.
California Prop. 65	WARNING: This product contains less than 0.1% of a chemical known to the State of California to cause cancer. WARNING: This product contains less than 1% of a chemical known to the State of California to cause birth defects or other reproductive harm.

Ingredient Name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
Oxirane, 2-(phenoxymethyl)-	Yes	No	5 μg/day	No
Oxirane, 2-(chloromethyl)-	Yes	Yes	9 μg/day	No

EPA SARA 302 Extremely
Hazardous Substances
EPA SARA 302/304/311/312
Hazardous Chemicals
United States inventory (TSCA 8b)

None.

Acute Health Hazard

All components are listed or exempted.

CANADA

WHMIS (Canada)	Class D-2B: Material causing other toxic effects (Toxic).	
Canadian NPRI CEPA Toxic substances	None required. None required.	
INTERNATIONAL REGULATIONS		
International Lists	Australia inventory (AICS): All components are listed or exempted. Canada inventory: All components are listed or exempted. Korea inventory: All components are listed or exempted. Japan inventory: All components are listed or exempted. China inventory (IECSC): All components are listed or exempted. New Zealand inventory (NZIoC): All components are listed or exempted. Philippines inventory (PICCS): All components are listed or exempted. Taiwan inventory (CSNN): All components are listed or exempted.	

16. Other Information, Including Date of Preparation or Last Revision

HMIS Rating

	Health 2 Flammability 1 Physical Hazard 0	
Date of Preparation		January 24, 2020
Date of Last Revision		September 16, 2019
Revision #		3.0
More Information		1-253-333-8118
Prepared by		System Three Resins Inc.

The information contained herein is based on the data available to us and is believed to be correct. However, System Three Resins, Inc. makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. System Three assumes no responsibility for injury from the use of the product described herein.



SAFETY DATA SHEET

1. Product Identification

Product name	EZ-Fillet Hardener, Part B			
SDS Number	1430B00			
Product type	Epoxy curing agent.			
Recommended use of the chemical and restrictions on use	Directed at, but not limited to, the filling and reinforcing of wood structures.			
Restrictions	None known.			
Manufacturer/Supplier information				
Company name	SYSTEM THREE RESINS, INC.			
Address	8517 Commerce Place Dr NE Lacey, WA 98516 United States			
Telephone	1-253-333-8118			
Website	www.systemthree.com			
Email	support@systemthree.com			
Emergency Contact	CHEMTEL (U.S. and CANADA) 1-800-704-9215 CHEMTEL (Outside the U.S.) – Call Collect accepted +1-360-256-7365			

2. Hazard(s) Identification

Classification of substance or mixture/Signal Word	DANGER ACUTE TOXCITY: ORAL – Category 4 SKIN CORROSION/IRRITATION – Catego SERIOUS EYE DAMAGE/EYE IRRITATION SKIN SENSITIZATION – Category 1 TOXIC TO REPRODUCTION [Fertility] – TOXIC TO REPRODUCTION [Unborn chi	– Category 1 Category 1
GHS Label Elements Hazard Pictograms		>
Hazard Statements/Classification of substance or mixture Precautionary statements	 Harmful if swallowed. Harmful in contact with skin. Causes severe skin burns and May cause an allergic skin rea Causes serious eye damage. May damage fertility or the u 	ction.
Precautionary Statements Prevention	2201 Obtain special instructions be 2202 Do not handle until all safety understood. 2261 Avoid breathing dust/fume/gi 2264 Wash hands thoroughly after	precautions have been read and as/mist/vapours/spray.

	P271 Use only outdoors or in a well-ventilated area.
	P272 Contaminated work clothing should not be allowed out of the
	workplace.
	P280 Wear protective gloves. Wear eye or face protection.
Response	P313 Call a POISON CENTER or doctor/physician if you feel unwell.
	P301+330 +331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
	P303+361+353 IF ON SKIN (or hair): Take off immediately all contaminated
	clothing. Rinse skin with water/shower.
	P304+340 IF INHALED: Remove person to fresh air and keep
	comfortable for breathing.
	P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes.
	Remove contact lenses if present and easy to do. Continue rinsing.
Storage	P401 Store at room temperature in a well-ventilated area.
Disposal	P501 Dispose of contents and container in accordance with all local,
	regional, national and international regulations.
Hazards not otherwise classified (HNOC)	None Available.

3. Composition/Information On Ingredients

Chemical Name	CAS Number	Content (%)
Modified Polyamines	Trade Secret	80 – 90%
Benzyl Alcohol	100-51-6	15 – 25%

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.

4. First-Aid Measures

Skin contact	Remove contaminated clothing and shoes and wipe excess off skin. Wash the affected area with plenty of soap and water until no evidence of the chemical remains (at least 15-20 minutes). Launder clothes before reuse. If skin irritation occurs: Get medical advice/attention.	
Eye contact	Rinse immediately with plenty of water for at least 15 minutes. Flush longer if there is an indication of residual chemical in the eye. Ensure adequate flushing of the eyes by separating the eyelids with fingers and roll eyes in a circular motion. Check for and remove any contact lenses. Continue rinsing for 10 minutes. If eye irritation persists: Get medical advice/attention.	
Ingestion	Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse out the mouth with water. Get medical attention immediately.	
Inhalation	If affected, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Call a POISON CENTER or doctor/physician if you feel unwell.	
Indication of immediate medical attention and special treatment needed, if necessary		
Notes to physician	Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.	
Specific treatments	No specific treatment.	

5. Fire-Fighting Measures

Suitable extinguishing media	Alcohol-resistant foam.
	Carbon dioxide (CO ₂).

	Dry chemical
	Water Fog
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	In a fire or if heated, a pressure increase will occur and the container may burst. Incomplete combustion may form carbon monoxide. May generate ammonia gas. May generate toxic nitrogen oxide gases. Burning produces noxious and toxic fumes. Downwind personnel must be evacuated.
Hazardous decomposition products	Decomposition products may include the following materials: Carbon dioxide Carbon monoxide Nitrogen oxides
Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire- fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Further information	Do not allow run-off from firefighting to enter drains or water courses. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Personal precautions	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Wear proper protective clothing, gloves and eye/face protection.
Emergency procedures	If material is spilled, avoid contact with material. Persons not wearing appropriate protective equipment should leave the area of the spill until cleanup is complete.
Methods and materials for containment/cleanup	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6. Accidental Release Measures

7. Handling and Storage

Precautions for safe handlingPut on appropriate personal protective equipment. Persons with a history of
skin sensitization problems should not be employed in any process in which
this product is used. Avoid contact with skin and eyes. Do not ingest. Avoid
breathing vapor or mist. Use only with adequate ventilation. Wear appropriate
respirator when ventilation is inadequate. Keep in the original container or an
approved alternative made from a compatible material, kept tightly closed
when not in use. Empty containers retain product residue and can be
hazardous. Do not reuse container. When using, do not eat, drink or smoke.
Workers should wash hands and face before eating, drinking and smoking.
Remove contaminated clothing and protective equipment before entering

eating areas. See also Section 8 for additional information on hygiene measures.

Precautions/Recommendations for safe/proper storage	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure Controls/Personal Protection

Occupational Exposure Limits	None established.
Appropriate engineering controls	Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. Do not allow spill to enter sewers or waterways.
Individual protection measures/Personal protective equipment	
Eye/face protection	Splash-proof goggles or safety spectacles with side shields are recommended. Always wear eye protection when sanding cured epoxy resins to avoid dust in eyes.
Hand protection	Always wear impervious gloves: butyl rubber, nitrile rubber, Neoprene, PVC disposable gloves,
Skin protection	Wear clean, body-covering clothing to avoid skin contact.
Respiratory protection	Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Special instructions for protection and hygiene	Wear gloves at all times when handling product, avoid direct contact with skin. When finished using product, dispose of gloves properly and wash hands with warm, soapy water.

9. Physical and Chemical Properties

Chemical family	Amine curing agent
Appearance	Green paste
Physical State	
Form	Paste
Color	Green
Odor	Amine-like odor
Density (Specific Gravity)	1.06
Viscosity	100,000 CPS @77°F (25°C)

рН	N/A
Melting point/freezing point	N/A
Initial boiling point and boiling range	N/A
Flash point	>250°F (Pensky-Martins Closed Cup)
Evaporation rate	Slower than Ether
Flammability (solid, gas)	N/A
Upper/lower flammability limit (by volume)	N/A
Upper flammability limit (by volume)	N/A
Lower flammability limit (by volume)	N/A
Material VOC	None
Vapor density	Heavier than Air
Relative density	N/A
Solubility in water	Negligible
Partition coefficient: n-octanol/water	N/A
Auto-ignition temperature	N/A
Decomposition temperature	N/A

10.Stability and Reactivity

Reactivity	Stable.
Chemical Stability	Stable under normal conditions.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	Epoxy resins and epoxy resin hardeners react with each other producing heat. They should not be mixed with each other under uncontrolled conditions or in large mass the ensuing exotherm may result in heat and smoke.
Incompatible materials	Strong oxidizing agents, mineral acids.
Hazardous decomposition products	Oxides of carbon, nitrogen.
Other hazards	None known.

11. Toxicological Information

Acute Health Hazard (components)

No comprehensive data (ingestion, inhalation, dermal) on mixture (product).

Component	Result	Species	Dose	Exposure		
Benzyl Alcohol	Inhalation LC50	Rat	>4178 mg/m3	4 h, aerosol		
	Oral LD50	Rat	1620 mg/kg			
Irritation/Corrosion (components) Classifies as skin corrosion Category 1 based on GHS cut-off						

Irritation/Corrosion (components)

Classifies as skin corrosion Category 1 based on GHS cut-off values/concentration limits in the product. Causes serious eye damage (Category 1).

Component	Result	Species	Test	Exposure
Benzyl Alcohol	Non-irritant	Rabbit	OECD 404 – Skin	-

	Irritant		Ra	bbit	OECD 405 – Ey	/e	-
Modified Polyamines	Corrosive				Calculated		
Sensitization		Weight of e	vide	nce classifies pr	oduct to be skin	sensitizing.	1
Component	Route of Exp	osure		Species		Results	
Modified Polyamines	Skin			Guinea pig		Sensitizing	
Mutagenicity	I	No informat	tion	on the product	itself.		
Carcinogenicity		No informat	tion	on the product	itself.		
Reproductive Toxicity		No informat	tion	on the product	itself.		
Teratogenicity		No informat	tion	on the product	itself.		
Specific target organ toxicity (s exposure)				on the product			
<u>Specific target organ toxicity (r</u> <u>exposure)</u> <u>Aspiration hazard</u>	<u>epeated</u>			on the product on the product			
Potential acute health effects							
Eye Contact		Causes serio	ous e	eye damage.			
Inhalation		respiratory	syste	em. Exposure to	that is very irrita decomposition delayed followin	products may	
Skin Contact		Causes seve reaction.	ere b	ourns. Toxic in co	ontact with skin.	May cause ar	allergic skin
Ingestion		Harmful if s	wall	owed. May caus	e burns to mout	th, throat, and	l stomach.
Symptoms related to the physi							
and toxicological characteristic: Eye Contact	<u>s</u>	Adverse syn Pain Watering Redness	npto	oms may include	the following:		
Inhalation		Adverse syn Reduced fet Increase in f	al w	0	the following:		
Skin Contact		Adverse syn Pain or irrita Redness Blistering m Reduced fet Increase in f	ation ay o al w	occur veight	the following:		
Ingestion		Adverse syn Stomach pa Reduced fet Increase in f	ins al w	-	the following:		
Delayed and immediate effects chronic effects from short and l exposure Potential chronic health effects	long term	No informat	tion	on the product	itself.		
General	2	Once sensit exposed to		-	c reaction may o	occur when su	ibsequently

Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	Suspected of damaging the unborn child.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	Suspected of damaging fertility.

Numerical measures of toxicity

Acute toxicity estimates (ATEmix)

Route	ATE value
Oral	1915.6 mg/kg
Dermal	3251 mg/kg
Inhalation (vapors)	50.99 mg/l

12. Ecological Information

<u>cotoxicity</u>	oxicity No comprehensive data of				elf.		
Component	Test	End	point	Exposure	Specie	S	Result
Benzyl Alcohol	-	Acu	te EC50	48 hrs	Inverte	ebrates	230 mg/l
	-	Acu	te LC50	96 hrs	Fish		460 mg/l
	-	Acu	te EC50	72 hrs	Algae		770 mg/l
Persistence and degradability	I	No information	on the pro	duct itself.	I		
Component	Test			Period		Result	
Benzyl Alcohol						Readily	Biodegradabl
Bioaccumulative Potential	I	No information	on the pro	duct itself.			
Component	LogPow		BCF		Pote	ntial	
Benzyl Alcohol	1.05		1.37 (calc	culated) Low			
Mobility in Soil		No information	on the pro	duct itself.			
Soil/water partition coefficient (KOC)		No information on the product itself.					
Other adverse effects		None known.					

Waste from residues/ unused products	Product should not be allowed to enter drains, water courses or the soil; dispose of this material and its containers in a safe way. Contact supplier if guidance is required.
Contaminated packaging	Dispose of container and unused contents in accordance with federal, state and local requirements.

14.Transport Information

The data provided in this section is for information only and may not be specific to your package size or mode of transport. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

Regulatory information	UN/NA number	Proper Shipping Name Classes/*PG		Additional Information
DOT	UN2735	Amines, liquid, corrosive, n.o.s. (n- Aminoethylpiperazine)	Class 8 III	
TDG	UN2735	Amines, liquid, corrosive, n.o.s. (n- Aminoethylpiperazine)	Class 8 III	
IMO/IMDG	UN2735	Amines, liquid, corrosive, n.o.s. (n- Aminoethylpiperazine)	Class 8 III	
ΙΑΤΑ	UN2735	Amines, liquid, corrosive, n.o.s. (n- Aminoethylpiperazine)	Class 8 III	
*PG: Packing group				
Special precautions	for user:	Transport within user's premises: always upright and secure. Ensure that persons t do in the event of an accident or spillage.	-	

15. Regulatory Information

UNITED STATES

U.S. Federal Regulations	United States – TSCA 12(b) – Chemical export notification: None Required. United States – TSCA 5(a)2 – Final significant new use rules: Not Listed. United States – TSCA 5(a)2 – Proposed significant new use rules: Not Listed. United States – TSCA 5(e) – Substance consent order: Not listed.						
Clean Air Act – Ozone Depleting Substances (ODS)	This product does not contain nor is it manufactured with ozone depleting substances.						
Clean Air Act Section 112(b) Hazardous	Product Name			Concentration %			
Air Pollutants (HAPs)	Diethanolamine						
Pennsylvania – RTK	N-Aminoethylpipe	razine, Dietha	nolamiı	ne			
California Prop. 65	WARNING: This product contains less than 0.1% of a chemical k State of California to cause cancer.						nown to the
	Ingredient Name Cance			er Reproductive			
	Diethanolamine Yes.		Yes.	No.			
EPA SARA 302 Extremely Hazardous Substances EPA SARA 302/304/311/312 Hazardous Chemicals	None. Acute Health Haza	ird, Chronic He	alth Ha	zard			
SARA 313	Product Name			Concentration %			
Form R – Reporting requirements	Diethanolamine			1%			
CERCLA Hazardous substances	CER			on 304 LA rdous tance	CERCL Repor Quant (Lbs)	table	Product Reportable Quantity (Lbs)

United States inventory (TSCA 8b)

All components are listed or exempted.

1%

Diethanolamine

CANADA

WHMIS (Canada)

Class D-2B: Material causing other toxic effects (Toxic).

100

	Class E: Corrosive material.
Canadian NPRI	None required.
CEPA Toxic substances	None required.
INTERNATIONAL REGULATIONS	
International Lists	Australia inventory (AICS): All components are listed or exempted.
	Canada inventory: All components are listed or exempted.
	Korea inventory: All components are listed or exempted.
	Japan inventory: All components are listed or exempted.
	China inventory (IECSC): All components are listed or exempted.
	New Zealand inventory (NZIoC): All components are listed or exempted.
	Philippines inventory (PICCS): All components are listed or exempted.
	Taiwan inventory (CSNN): All components are listed or exempted.

16. Other Information, Including Date of Preparation or Last Revision

HMIS Rating

	Health 3	
	Flammability 1	
	<mark>Physical Hazard 0</mark>	
Date of Preparation		January 24, 2020
Date of Last Revision		September 16, 2019
Revision #		5.0
More Information		1-253-333-8118
Prepared by		System Three Resins Inc.

The information contained herein is based on the data available to us and is believed to be correct. However, System Three Resins, Inc. makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. System Three assumes no responsibility for injury from the use of the product described herein.