

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/28/2021

Reviewed on 01/28/2021

1 Identification

- Product identifier
- Trade name: Epifanes Epoxy Primer Comp. A
- Application of the substance / the mixture
See our technical datasheet for application of this product.
- Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
W.Heeren & Zoon bv.
P.O. box 166
1430 AD Aalsmeer
Netherlands
tel.+31 297-360666
fax.+31 297-342078
email:info@epifanes.nl
- Information department: Research & Development.
- Emergency telephone number:
Emergency Phone Number (24 hours) CHEMTREC (800-424-9300)
Outside US: 703-527-3887

2 Hazard(s) identification

- Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer. Route of exposure:
Inhalation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated
exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- Label elements

- GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/28/2021

Reviewed on 01/28/2021

Trade name: Epifanes Epoxy Primer Comp. A

(Contd. of page 1)

· Hazard pictograms



GHS02

GHS07

GHS08

· Signal word Warning

· Hazard-determining components of labeling:

phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane]

titanium dioxide

Xylene

· Hazard statements

H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer. Route of exposure: Inhalation.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 1

Fire = 3

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 1

Fire = 3

Reactivity = 0

· Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

US

(Contd. on page 3)

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/28/2021

Reviewed on 01/28/2021

Trade name: Epifanes Epoxy Primer Comp. A

(Contd. of page 2)

3 Composition/information on ingredients

- Chemical characterization: Mixtures
- Description:
Resin mixture
Solvent mixture with pigment additives

· Dangerous components:

CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2	titanium dioxide ☠ Carc. 2, H351	10-25%
CAS: 107-98-2 EINECS: 203-539-1 Index number: 603-064-00-3	1-methoxy-2-propanol ☠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336	10-25%
CAS: 25036-25-3 EC number: 607-500-3	phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene) bis(4,1-phenyleneoxymethylene)] bis[oxirane] ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	10-25%
CAS: 1330-20-7 EINECS: 215-535-7	Xylene ☠ Flam. Liq. 3, H226 ☠ STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	2.5-10%

- Additional information:
For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation:
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact:
Immediately wash with water and soap and rinse thoroughly.
Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed
No further relevant information available.
- Indication of any immediate medical attention and special treatment needed
No further relevant information available.

US

(Contd. on page 4)

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/28/2021

Reviewed on 01/28/2021

Trade name: Epifanes Epoxy Primer Comp. A

(Contd. of page 3)

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture
During heating or in case of fire poisonous gases are produced.
- Advice for firefighters
- Protective equipment:
Wear fully protective suit.
Mouth respiratory protective device.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures
Wear protective clothing.
Ensure adequate ventilation
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- Environmental precautions:
Prevent seepage into sewage system, workpits and cellars.
Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- Protective Action Criteria for Chemicals

· PAC-1:

13463-67-7	titanium dioxide	30 mg/m ³
107-98-2	1-methoxy-2-propanol	100 ppm
25036-25-3	phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane]	12 mg/m ³
7631-86-9	silicon dioxide, chemically prepared	18 mg/m ³
14808-60-7	Quartz (SiO ₂)	0.075 mg/m ³

· PAC-2:

13463-67-7	titanium dioxide	330 mg/m ³
107-98-2	1-methoxy-2-propanol	160 ppm
25036-25-3	phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane]	130 mg/m ³

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/28/2021

Reviewed on 01/28/2021

Trade name: Epifanes Epoxy Primer Comp. A

(Contd. of page 4)

7631-86-9	silicon dioxide, chemically prepared	740 mg/m ³
14808-60-7	Quartz (SiO ₂)	33 mg/m ³
· PAC-3:		
13463-67-7	titanium dioxide	2,000 mg/m ³
107-98-2	1-methoxy-2-propanol	660 ppm
25036-25-3	phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane]	790 mg/m ³
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m ³
14808-60-7	Quartz (SiO ₂)	200 mg/m ³

7 Handling and storage

- Handling:
- Precautions for safe handling
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- Information about protection against explosions and fires:
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles:
Store only in the original receptacle.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems:
No further data; see item 7.
- Control parameters
- Components with limit values that require monitoring at the workplace:
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

107-98-2 1-methoxy-2-propanol

REL	Short-term value: 540 mg/m ³ , 150 ppm Long-term value: 360 mg/m ³ , 100 ppm
TLV	Short-term value: 369 mg/m ³ , 100 ppm Long-term value: 184 mg/m ³ , 50 ppm

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/28/2021

Reviewed on 01/28/2021

Trade name: Epifanes Epoxy Primer Comp. A

(Contd. of page 5)

1330-20-7 Xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI

107-98-2 1-methoxy-2-propanol

REL	Short-term value: 540 mg/m ³ , 150 ppm Long-term value: 360 mg/m ³ , 100 ppm
TLV	Short-term value: 369 mg/m ³ , 100 ppm Long-term value: 184 mg/m ³ , 50 ppm

1330-20-7 Xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI

· Regulatory information

- REL: Guide to Occupational Exposure Values (NIOSH RELs)
- TLV: Guide to Occupational Exposure Values (TLV)
- PEL: Guide to Occupational Exposure Values (OSHA PELs)

· Additional information:

The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the skin.
- Avoid contact with the eyes and skin.

· Breathing equipment:

- Suitable respiratory protective device recommended.
- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- Filter AX

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/28/2021

Reviewed on 01/28/2021

Trade name: Epifanes Epoxy Primer Comp. A

(Contd. of page 6)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Fluid
Color: According to product specification

· Odor: Characteristic

· Odor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: >100 °C (>212 °F)

· Flash point: >31 °C (>87.8 °F)

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 270 °C (518 °F)

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower: 2.3 Vol %
Upper: ~20 Vol %

· Vapor pressure at 20 °C (68 °F): 12 hPa (9 mm Hg)

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/28/2021

Reviewed on 01/28/2021

Trade name: Epifanes Epoxy Primer Comp. A

(Contd. of page 7)

· Density at 20 °C (68 °F):	1.734 g/cm ³ (14.47023 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C (68 °F):	100 s (DIN 53211/4)
· Solvent content:	
Organic solvents:	25.3 %
VOC content:	25.31 %
	VOC content: 438.9 g/l / 3.66 lb/gal
Solids content:	75.6 % (VB% 1h150 C)
· Other information	No further relevant information available.

10 Stability and reactivity

- Reactivity No further relevant information available.
- Chemical stability
- Thermal decomposition / conditions to be avoided:
No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- Information on toxicological effects
- Acute toxicity:

· LD/LC50 values that are relevant for classification:		
13463-67-7 titanium dioxide		
Oral	LD50	>20000 mg/kg bw (rat)
Dermal	LD50	>10000 mg/kg bw (rabbit)
Inhalative	LC50/4 h	>6.82 mg/l (rat)
107-98-2 1-methoxy-2-propanol		
Oral	LD50	5660 mg/kg bw (rat)
Dermal	LD50	13000 mg/kg bw (rabbit)
Inhalative	LC50/4 h	6 mg/l (rat)

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/28/2021

Reviewed on 01/28/2021

Trade name: Epifanes Epoxy Primer Comp. A

(Contd. of page 8)

- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
- Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
- Carcinogenic categories

· IARC (International Agency for Research on Cancer)

13463-67-7	titanium dioxide	2B
14807-96-6	Talc (Mg3H2(SiO3)4)	3
7631-86-9	silicon dioxide, chemically prepared	3
14808-60-7	Quartz (SiO2)	1

· NTP (National Toxicology Program)

14808-60-7	Quartz (SiO2)	K
------------	---------------	---

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.		
------------------------------------	--	--

12 Ecological information

- Toxicity
- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes:
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- Waste treatment methods
- Recommendation:
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/28/2021



Reviewed on 01/28/2021

Trade name: Epifanes Epoxy Primer Comp. A

(Contd. of page 9)

- Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

14 Transport information

- UN-Number
 - DOT, IATA
 - ADR, IMDG
- UN1263
Void
-
- UN proper shipping name
 - DOT
 - ADR
 - IMDG
 - IATA
- CONSUMER COMMODITY, ORM-D
Paint
Void
CONSUMER COMMODITY, ORM-D
Void
PAINT
-
- Transport hazard class(es)
 - DOT
- 
- Class
 - Label
- 3 Flammable liquids
3
-
- ADR, ADN, IMDG
 - Class
- Void
-
- IATA
- 
- Class
 - Label
- 3 Flammable liquids
3
-
- Packing group
 - DOT, IATA
 - ADR, IMDG
- III
Void
-
- Environmental hazards:
 - Marine pollutant:
- No
-
- Special precautions for user
- Not applicable.
-
- Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code
- Not applicable.

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/28/2021

Reviewed on 01/28/2021

Trade name: Epifanes Epoxy Primer Comp. A

(Contd. of page 10)

- Transport/Additional information:
- DOT
- Quantity limitations On passenger aircraft/rail: 60 L
On cargo aircraft only: 220 L
- Remarks: CERCLA/DOT RQ: 617gal./4786 lbs.
- ADR
- Remarks: > 450 1: 3 F1, III
- IMDG
- Remarks: > 450 1: 3, III
- UN "Model Regulation": Void

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

13463-67-7	titanium dioxide	ACTIVE
107-98-2	1-methoxy-2-propanol	ACTIVE
25036-25-3	phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bis[oxirane]	ACTIVE
7757-93-9	calcium hydrogenorthophosphate, with afluorine content of less than 0,005 per centby weight on the dry anhydrous product	ACTIVE
1330-20-7	Xylene	ACTIVE
14807-96-6	Talc (Mg3H2(SiO3)4)	ACTIVE
68611-44-9	Silicium hydrophobised high dispersion	ACTIVE
68953-58-2	Ditallowdimethylammonium	ACTIVE
7631-86-9	silicon dioxide, chemically prepared	ACTIVE
1589-47-5	2-methoxypropanol	ACTIVE
14808-60-7	Quartz (SiO2)	ACTIVE

· Hazardous Air Pollutants

1330-20-7 Xylene

· Proposition 65

· Chemicals known to cause cancer:

13463-67-7 titanium dioxide

14808-60-7 Quartz (SiO2)

(Contd. on page 12)

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/28/2021

Reviewed on 01/28/2021

Trade name: Epifanes Epoxy Primer Comp. A

(Contd. of page 11)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

13463-67-7	titanium dioxide	A4
14807-96-6	Talc (Mg3H2(SiO3)4)	A4
14808-60-7	Quartz (SiO2)	A2

· MAK (German Maximum Workplace Concentration)

13463-67-7	titanium dioxide	3A
14807-96-6	Talc (Mg3H2(SiO3)4)	3B
14808-60-7	Quartz (SiO2)	1

· NIOSH-Ca (National Institute for Occupational Safety and Health)

13463-67-7	titanium dioxide
14808-60-7	Quartz (SiO2)

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS02 GHS07 GHS08

· Signal word Warning

· Hazard-determining components of labeling:

phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane]
titanium dioxide
Xylene

· Hazard statements

H226 Flammable liquid and vapor.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer. Route of exposure: Inhalation.
H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P260 Do not breathe dust/fume/gas/mist/vapors/spray.

(Contd. on page 13)

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/28/2021

Reviewed on 01/28/2021

Trade name: Epifanes Epoxy Primer Comp. A

(Contd. of page 12)

- P270 Do not eat, drink or smoke when using this product.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P310 If swallowed: Immediately call a poison center/doctor.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- National regulations:
- Technical instructions (air):

Class	Share in %
NK	25-50

- Water hazard class:
Water hazard class 2 (Self-assessment): hazardous for water.
- Chemical safety assessment:
A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: Environment protection department.
- Contact: J.J. van Dijk
- Date of preparation / last revision 01/28/2021 / 5
- Abbreviations and acronyms:
 RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 ICAO: International Civil Aviation Organisation
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 Flam. Liq. 3: Flammable liquids - Category 3
 Acute Tox. 4: Acute toxicity - Category 4
 Skin Irrit. 2: Skin corrosion/irritation - Category 2
 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A
 Skin Sens. 1: Skin sensitisation - Category 1

(Contd. on page 14)

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/28/2021

Reviewed on 01/28/2021

Trade name: Epifanes Epoxy Primer Comp. A

(Contd. of page 13)

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

· * Data compared to the previous version altered.

None

US