

Page 1/12

Safety Data Sheet acc. to OSHA HCS

Printing date 02/11/2021 Reviewed on 02/11/2021

1 Identification

- · Product identifier
- · Trade name: Epifanes Rapidclear
- · CAS Number: RCC.750
- Application of the substance / the mixture
 See our technical datasheet for application of this product.
 quick and easy semigloss woodprotector
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

W.Heeren & Zoon bv.

P.O. box 166

1430 AD Aalsmeer

Netherlands

tel.+31 297-360666

fax.+31 297-342078

email:info@epifanes.nl

- · Information department: Research & Development.
- · Emergency telephone number:

Emergency Phone Number (24 hours) CHEMTREC (800-424-9300)

Outside US: 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02 GF

GHS07

Q11Q0C

· Signal word Warning

(Contd. on page 2)





Safety Data Sheet acc. to OSHA HCS

Printing date 02/11/2021 Reviewed on 02/11/2021

Trade name: Epifanes Rapidclear

(Contd. of page 1)

- · Hazard-determining components of labeling:
 - Naphtha (petroleum), hydrotreated heavy (Note-p)
- · Hazard statements
 - H226 Flammable liquid and vapor.
 - H361 Suspected of damaging fertility or the unborn child.
 - H336 May cause drowsiness or dizziness.
- · Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No

smoking.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face

protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated

clothing. Rinse skin with water/shower.

P501 Dispose of contents/container in accordance with local/regional/

national/international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 0
Fire = 3
Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 0
Fire = 3
Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Resin mixture

Solvent mixture with additives

· Dangerous components:

CAS: 64742-48-9 EC number: 919-857-5 Index number: 649-327-00-6 Naphtha (petroleum), hydrotreated heavy (Note-p)

Flam. Liq. 3, H226Asp. Tox. 1, H304

* STOT SE 3, H336

(Contd. on page 3)

50-100%



Page 3/12

Safety Data Sheet acc. to OSHA HCS

Printing date 02/11/2021 Reviewed on 02/11/2021

Trade name: Epifanes Rapidclear

(Contd. of page 2)

· Additional information:

For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- · Description of first aid measures
- \cdot General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Seek medical treatment.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures
 Ensure adequate ventilation

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 4)

US



Page 4/12

Safety Data Sheet acc. to OSHA HCS

Printing date 02/11/2021 Reviewed on 02/11/2021

Trade name: Epifanes Rapidclear

(Contd. of page 3)

· Protective Action Criteria for Chemicals

· PAC-1:				
64742-48-9	Naphtha (petroleum), hydrotreated heavy (Note-p)	350 mg/m ³		
7631-86-9	silicon dioxide, chemically prepared	18 mg/m³		
112-34-5	112-34-5 2-(2-butoxyethoxy)ethanol 30 ppm			
· PAC-2:	· PAC-2:			
64742-48-9	Naphtha (petroleum), hydrotreated heavy (Note-p)	1,800 mg/m ³		
7631-86-9	7631-86-9 silicon dioxide, chemically prepared 740 mg/m ³			
112-34-5	112-34-5 2-(2-butoxyethoxy)ethanol 33 ppm			
· PAC-3:				
64742-48-9	Naphtha (petroleum), hydrotreated heavy (Note-p)	40,000 mg/m ³		
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m ³		
112-34-5	2-(2-butoxyethoxy)ethanol	200 ppm		

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Work only in fume cabinet.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- Components with limit values that require monitoring at the workplace:
 The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

(Contd. on page 5)



Page 5/12

Safety Data Sheet acc. to OSHA HCS

Printing date 02/11/2021 Reviewed on 02/11/2021

Trade name: Epifanes Rapidclear

(Contd. of page 4)

- · Additional information:
 - The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Filter AX

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• For the permanent contact gloves made of the following materials are suitable: nitrile rubber;

recommended glove thickness> 0.45mm. permeability / permeation time:> 480 min. according to EN 374.

· As protection from splashes gloves made of the following materials are suitable:

chloropene; glove thickness> 0.7mm, breakthrough time> 60min. according to EN 374.

nitrile rubber; glove thickness> 0.3 mm, breakthrough time> 60min.volgens EN 374.

· Eye protection:



Tightly sealed goggles

(Contd. on page 6)



Page 6/12

Safety Data Sheet acc. to OSHA HCS

Printing date 02/11/2021 Reviewed on 02/11/2021

Trade name: Epifanes Rapidclear

(Contd. of page 5)

· Body protection: Use protective suit.

Physical and chemical properties	
· Information on basic physical and · General Information · Appearance:	chemical properties
Form:	Fluid
Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. Undetermined.
· Flash point:	>36 °C (>96.8 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	240 °C (464 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	0.6 Vol %
Upper:	7 Vol %
· Vapor pressure at 20 °C (68 °F):	1 hPa (0.8 mm Hg)
Density at 20 $^{\circ}$ C (68 $^{\circ}$ F):	0.89 g/cm ³ (7.42705 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
<pre>Partition coefficient (n-octanol/ water):</pre>	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C (68 °F):	25 s (DIN 53211/4)
· Solvent content:	
Organic solvents:	56.5 %



Page 7/12

Safety Data Sheet acc. to OSHA HCS

Printing date 02/11/2021 Reviewed on 02/11/2021

Trade name: Epifanes Rapidclear

(Contd. of page 6)

VOC content:	56.53 % VOC content: 503.1 g/l / 4.20 lb/gal
Solids content:	40.5 % (VB% 1h 150C)
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 val	· LD/LC50 values that are relevant for classification:			
64742-48-9 Naphtha (petroleum), hydrotreated heavy (Note-p)				
Oral	LD50	>5000 mg/kg bw (rat)		
Dermal	LD50	>5000 mg/kg bw (rabbit) ((24h))		
Inhalative	LC50	>5000 mg/m ³ (vapour) (rat) ((8h))		

- · Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
7631-86-9 silicon dioxide, chemically prepared		3
136-52-7 cobalt bis(2-ethylhexanoate) 2B		
· NTP (National Toxicology Program)		
None of the ingredients is listed.		
· OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients is listed.		

(Contd. on page 8)



Page 8/12

Safety Data Sheet acc. to OSHA HCS

Printing date 02/11/2021 Reviewed on 02/11/2021

Trade name: Epifanes Rapidclear

(Contd. of page 7)

12 Ecological information

· Toxicity

· Aquatic toxicity:				
64742-48-9 Naphtha (petroleum), hydrotreated heavy (Note-p)				
ErL (72h)	>1000 mg/l (Pseudokirchneriella subcapitata-OECD 201)			
EL50 (48h)	>1000 mg/l ((Daphnia magna-OECD 202))			
LL50 (96h)	(96h) >1000 mg/l ((Onorhynchus mykiss OECD 203))			
EbL50 (72h)	(72h) >1000 mg/l (Pseudokirchneriella subcapitata-OECD 201)			
NOELR (72h) 3 mg/l ((Pseudo. subcapitata-biomass-OECD 201))				
100 mg/l ((Pseudo. subcap. growth rate OECD 201))				

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- \cdot Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

	inform	

· UN-Number · DOT, ADR, IMDG, IATA	UN1263
UN proper shipping nameDOTADRIMDG	CONSUMER COMMODITY, ORM-D Paint 1263 PAINT CONSUMER COMMODITY, ORM-D PAINT

(Contd. on page 9)



Page 9/12

Safety Data Sheet acc. to OSHA HCS

Printing date 02/11/2021 Reviewed on 02/11/2021

Trade name: Epifanes Rapidclear

	(Contd. of pag
IATA	PAINT
Transport hazard class(es)	
DOT	
RAMMAC COO	
Class	3 Flammable liquids
Label	3
ADR	
Class	3 (F1) Flammable liquids
Label	3
Class	3 Flammable liquids
Label	3
Packing group	
DOT, ADR, IMDG, IATA	III
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
<pre>Hazard identification number (Kemler code):</pre>	30
EMS Number:	F-E,S-E
Stowage Category	A
Transport in bulk according to Annex	
II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 60 L
_	On cargo aircraft only: 220 L
Remarks:	CERCLA/DOT RQ: 617gal./4786 lbs.

(Contd. on page 10)



Page 10/12

Safety Data Sheet acc. to OSHA HCS

Printing date 02/11/2021 Reviewed on 02/11/2021

Trade name: Epifanes Rapidclear

(Contd. of page 9) · Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · IMDG · Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

UN 1263 PAINT, 3, III

15 Regulatory information

· UN "Model Regulation":

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara

· Section 355 (extremely hazardous substances):		
None of the ingredient is listed.		
· Section 313	(Specific toxic chemical listings):	
136-52-7 co	balt bis(2-ethylhexanoate)	
112-34-5 2-	(2-butoxyethoxy)ethanol	
· TSCA (Toxic	Substances Control Act):	
64742-48-9	Naphtha (petroleum), hydrotreated heavy (Note-p)	ACTIVE
7631-86-9	silicon dioxide, chemically prepared	ACTIVE
64742-94-5	Solvent naphtha (petroleum), heavy arom.	ACTIVE
127519-17-9		ACTIVE
	<pre>benzotriazol-2-yl)-5-(1,1-dimethyl-ethyl)-4- hydroxyphenyl]propionates</pre>	
129757-67-1		ACTIVE
	piperidinyl) ester, reaction products with tert-Bu	
	hydroperoxide and octane	
105-44-2	`4-methylpentan-2-one oxime	ACTIVE
22464-99-9	Zirconiumoctoate, 12 % Zr	ACTIVE
68409-80-3	Isomers of fatty acid calcium salts, C6-C19	ACTIVE
136-52-7	cobalt bis(2-ethylhexanoate)	ACTIVE
112-34-5 2-(2-butoxyethoxy)ethanol		ACTIVE
· Hazardous Ai	r Pollutants	

- Hazardous Air Pollutants
 - 136-52-7 cobalt bis(2-ethylhexanoate)
- Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

(Contd. on page 11)



Page 11/12

Safety Data Sheet acc. to OSHA HCS

Printing date 02/11/2021 Reviewed on 02/11/2021

Trade name: Epifanes Rapidclear

(Contd. of page 10)

- · Chemicals known to cause reproductive toxicity for females:

 None of the ingredients is listed.
- · Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Cancerogenity categories
- EPA (Environmental Protection Agency)

None of the ingredients is listed.

TLV (Threshold Limit Value)

None of the ingredients is listed.

· MAK (German Maximum Workplace Concentration)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02

GHS07

GHS08

- · Signal word Warning
- · Hazard-determining components of labeling:

Naphtha (petroleum), hydrotreated heavy (Note-p)

· Hazard statements

H226 Flammable liquid and vapor.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No

smoking.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face

protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated

clothing. Rinse skin with water/shower.

P501 Dispose of contents/container in accordance with local/regional/

national/international regulations.

(Contd. on page 12)



Page 12/12

Safety Data Sheet acc. to OSHA HCS

Printing date 02/11/2021 Reviewed on 02/11/2021

Trade name: Epifanes Rapidclear

(Contd. of page 11)

- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	50-100

· Water hazard class:

Water hazard class 3 (Self-assessment): extremely hazardous for water.

· Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: Environment protection department.
- · Contact: J.J. van Dijk
- $^{\circ}$ Date of preparation / last revision 02/11/2021 / 5
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European

Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit Flam. Liq. 3: Flammable liquids - Category 3

Repr. 2: Reproductive toxicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

 \cdot * Data compared to the previous version altered.

US