

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/15/2021

Reviewed on 02/15/2021

1 Identification

- Product identifier
- Trade name: Epifanes Spraythinner for Paint & Varnish
- EC number:
920-750-0
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics
- Index number:

- Application of the substance / the mixture
See our technical datasheet for application of this product.
- Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
W.Heeren & Zoon bv.
P.O. box 166
1430 AD Aalsmeer
Netherlands
tel.+31 297-360666
fax.+31 297-342078
email:info@epifanes.nl
- Information department: Research & Development.
- Emergency telephone number:
Emergency Phone Number (24 hours) CHEMTREC (800-424-9300)
Outside US: 703-527-3887

2 Hazard(s) identification

- Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- Label elements
- GHS label elements
The substance is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms



GHS02



GHS07



GHS08

(Contd. on page 2)



Safety Data Sheet
acc. to OSHA HCS

Printing date 02/15/2021

Reviewed on 02/15/2021

Trade name: Epifanes Spraythinner for Paint & Varnish

(Contd. of page 1)

- Signal word **Danger**
- Hazard-determining components of labeling:
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics
- Hazard statements
H225 Highly flammable liquid and vapor.
H336 May cause drowsiness or dizziness.
H304 May be fatal if swallowed and enters airways.
- Precautionary statements
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310 If swallowed: Immediately call a poison center/doctor.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- Classification system:
- NFPA ratings (scale 0 - 4)
 Health = 0
Fire = 3
Reactivity = 0
- HMIS-ratings (scale 0 - 4)
 Health = 0
Fire = 3
Reactivity = 0
- Other hazards
- Results of PBT and vPvB assessment
PBT: Not applicable.
vPvB: Not applicable.

3 Composition/information on ingredients

- Chemical characterization: Substances
- CAS No. Description
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics
- Identification number(s)
- EC number:
920-750-0
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics
- Index number:
- Description: Solvent mixture

(Contd. on page 3)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/15/2021

Reviewed on 02/15/2021

Trade name: Epifanes Spraythinner for Paint & Varnish

(Contd. of page 2)

· Dangerous components: Void

4 First-aid measures

- Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Seek medical treatment.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed
No further relevant information available.
- Indication of any immediate medical attention and special treatment needed
No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture
During heating or in case of fire poisonous gases are produced.
- Advice for firefighters
- Protective equipment:
Wear fully protective suit.
Mouth respiratory protective device.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures
Ensure adequate ventilation
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- Environmental precautions:
Prevent seepage into sewage system, workpits and cellars.
Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

(Contd. on page 4)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/15/2021

Reviewed on 02/15/2021

Trade name: Epifanes Spraythinner for Paint & Varnish

(Contd. of page 3)

· Protective Action Criteria for Chemicals

· PAC-1:

Substance is not listed.

· PAC-2:

Substance is not listed.

· PAC-3:

Substance is not listed.

7 Handling and storage

- Handling:
- Precautions for safe handling
 - Keep away from heat and direct sunlight.
 - Ensure good ventilation/exhaustion at the workplace.
 - Prevent formation of aerosols.
- Information about protection against explosions and fires:
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.
 - Keep respiratory protective device available.
- Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles:
 - Store only in the original receptacle.
 - Store in a cool location.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
 - Keep receptacle tightly sealed.
 - Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems:
 - No further data; see item 7.
- Control parameters
- Components with limit values that require monitoring at the workplace:
 - Not required.

Not required.

· Additional information:

The lists that were valid during the creation were used as basis.

- Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:
 - Keep away from foodstuffs, beverages and feed.
 - Immediately remove all soiled and contaminated clothing.
 - Wash hands before breaks and at the end of work.

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/15/2021

Reviewed on 02/15/2021

Trade name: Epifanes Spraythinner for Paint & Varnish

(Contd. of page 4)

- Breathing equipment:
Suitable respiratory protective device recommended.
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
Filter AX
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
- Penetration time of glove material
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- Information on basic physical and chemical properties
- General Information
- Appearance:

Form:	Fluid
Color:	Clear
- Odor: Characteristic
- Odor threshold: Not determined.
- pH-value: Not determined.
- Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	>90 °C (>194 °F)
- Flash point: <10 °C (<50 °F)
- Flammability (solid, gaseous): Not applicable.
- Decomposition temperature: Not determined.

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/15/2021

Reviewed on 02/15/2021

Trade name: Epifanes Spraythinner for Paint & Varnish

(Contd. of page 5)

· Auto igniting:	Not determined.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits: Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	Not determined.
· Density at 20 °C (68 °F):	0.738 g/cm ³ (6.15861 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/ water):	Not determined.
· Viscosity: Dynamic:	Not determined.
Kinematic at 20 °C (68 °F):	20 s ISO 4
Organic solvents:	100.0 %
VOC content:	100.00 %
	VOC content: 738.0 g/l / 6.16 lb/gal
· Other information	No further relevant information available.

10 Stability and reactivity

- Reactivity No further relevant information available.
- Chemical stability
- Thermal decomposition / conditions to be avoided:
No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- Information on toxicological effects
- Acute toxicity:
- Primary irritant effect:
 on the skin: No irritant effect.
 on the eye: No irritating effect.
- Sensitization:
Sensitizing effect by skin contact is possible with prolonged exposure.

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/15/2021

Reviewed on 02/15/2021

Trade name: Epifanes Spraythinner for Paint & Varnish

(Contd. of page 7)

· ADR, IATA	Void
· Transport hazard class(es)	
· DOT, ADR, ADN, IMDG, IATA	
· Class	Void
· Packing group	
· DOT, ADR, IMDG, IATA	Void
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Remarks:	CERCLA/DOT RQ: 617gal./4786 lbs.
· UN "Model Regulation":	Void

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):
Substance is not listed.

· Section 313 (Specific toxic chemical listings):
Substance is not listed.

· TSCA (Toxic Substances Control Act):
Substance is not listed.

· Hazardous Air Pollutants
Substance is not listed.

· Proposition 65

· Chemicals known to cause cancer:
Substance is not listed.

· Chemicals known to cause reproductive toxicity for females:
Substance is not listed.

· Chemicals known to cause reproductive toxicity for males:
Substance is not listed.

· Chemicals known to cause developmental toxicity:
Substance is not listed.

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/15/2021

Reviewed on 02/15/2021

Trade name: Epifanes Spraythinner for Paint & Varnish

(Contd. of page 8)

· Cancerogenity categories

· EPA (Environmental Protection Agency)

Substance is not listed.

· TLV (Threshold Limit Value)

Substance is not listed.

· MAK (German Maximum Workplace Concentration)

Substance is not listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

Substance is not listed.

· GHS label elements

The substance is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS02



GHS07



GHS08

· Signal word Danger

· Hazard-determining components of labeling:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

· Hazard statements

H225 Highly flammable liquid and vapor.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

· Technical instructions (air):

Class	Share in %
NK	50-100

· Water hazard class:

Water hazard class 3 (Self-assessment): extremely hazardous for water.

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/15/2021

Reviewed on 02/15/2021

Trade name: Epifanes Spraythinner for Paint & Varnish

(Contd. of page 9)

- Chemical safety assessment: A Chemical Safety Assessment has been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Contact:
- Date of preparation / last revision 02/15/2021 / 5
- Abbreviations and acronyms:
 - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 - ICAO: International Civil Aviation Organisation
 - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - DOT: US Department of Transportation
 - IATA: International Air Transport Association
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - NFPA: National Fire Protection Association (USA)
 - HMIS: Hazardous Materials Identification System (USA)
 - VOC: Volatile Organic Compounds (USA, EU)
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
 - NIOSH: National Institute for Occupational Safety
 - OSHA: Occupational Safety & Health
 - TLV: Threshold Limit Value
 - PEL: Permissible Exposure Limit
 - REL: Recommended Exposure Limit
 - Flam. Liq. 2: Flammable liquids - Category 2
 - STOT SE 3: Specific target organ toxicity (single exposure) - Category 3
 - Asp. Tox. 1: Aspiration hazard - Category 1
- * Data compared to the previous version altered.