

Epifanes Teak Oil Sealer

Impregnating oil for Teak and other wood types



PRODUCT DESCRIPTION

Impregnating oil for maintenance and protection of teak and any other wood type. There will be no build-up when using this sealer. All product will impregnate fully into the wood. It makes the natural colour of the wood stronger and protects it for a longer period of time against discoloration and moisture coming in to the wood. The application of the product is extremely easy and can be done during almost all weather types.

Field of use: For the maintenance and protection of decks or teak objects that need protection and that won't be varnished. Do not use for furniture, as the oil can be sticky and can leave marks on clothes when it is freshly applied.

PRODUCT INFORMATION

Type	Slow oxidative drying
Base	Linseed oil and alkyd resin
Gloss	Not applicable
Colour	Amber
Density at 68°F.	0,887 g/cm ³
Viscosity	14 seconds DIN-cup 4 mm
Solids Contents	55 ± 2 vol. %
VOC-level	339 g/l
Packing	1000ml.
Shelf life	In closed unopened container stored in a dry room at temperatures between 41 - 86°F approx. 3 years.
Thinning	No thinning
Application	Flat brush or lint free cloth.
Theoretical coverage	60-90 ft ² per ltr. depending on the application technique and the type of wood (roughness, surface and suction power of the wood.)
Surface preparation	Apply this product only when the surface is dry. Remove all dirt or stains from the wood with a non-bleaching cleaner. Degrease once more with Epifanes Spraythinner for 1 component paint & varnish. When the colour of the wood is so damaged, it might help to apply 1 coat of Epifanes Teak-O-Clean & Bright to restore the original colour of the wood.

APPLICATION

Apply the oil wet-on-wet and repeat this treatment until the wood is saturated with oil. The number of coats depends on the remaining concentration of oil and the suction power in the wood. On average two coats will be sufficient. Use a brush or a lint free cloth for application. Do not use a roller, as this won't distribute the sealer well.

Important	This sealer has an effect on the rubber compounds in a teak deck system. The Teak-Oil-Sealer can activate the plastisizer in the sealant. This will create a situation where the sealant will become softer and loses its power to seal off the surface.
Maintenance intervall	Between 1 month and 1 year depending of the intensity of usage and weather conditions.
Health & Safety	Due to the flammable hazard of linseed oil, saturated cloths should be placed in water or hung out to dry. Do not keep in a closed place. The user of this product should obey all national laws and legislation concerning health, safety and environmental hazard. For more information on health and safety, we refer to the Material Safety Data Sheet of this product.

Although the facts and suggestions in this product information sheet are based on our own research and field experiences and are believed reliable, we cannot simply be held responsible for performance or results obtained through the use of this product. Ineffectiveness or other unintended consequences may result, because of such factors as weather, conditions, presence or other materials or the manner of preparation, use or application all of which are beyond W. Heeren & Zoon's control. All such risks are assumed by user.

DISCLAIMER OF WARRANTIES. Seller makes no express warranties.

THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXCLUDED. In the event a warranty is created by law, buyer's EXCLUSIVE REMEDY shall be the replacement of any defective product. No other remedy (including, but not limited to, incidental or consequential damages for lost profits, lost sales, injury to person or property, or any other incidental or consequential loss) shall be available to buyer.

Postbus 166
1430 AD Aalsmeer
tel. 0297 – 360366
info@epifanes.nl
www.epifanes.nl

EPIFANES[®]
Yacht Coatings