

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/10/2021

Reviewed on 02/10/2021

1 Identification

- Product identifier
- Trade name: Epifanes Yacht Enamel (all colours)
- Application of the substance / the mixture
See our technical datasheet for application of this product.
- Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
W.Heeren & Zoon bv.
P.O. box 166
1430 AD Aalsmeer
Netherlands
tel.+31 297-360666
fax.+31 297-342078
email:info@epifanes.nl
- Information department: Research & Development.
- Emergency telephone number:
Emergency Phone Number (24 hours) CHEMTREC (800-424-9300)
Outside US: 703-527-3887

2 Hazard(s) identification

- Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Repr. 1B H360 May damage fertility or the unborn child.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

- Label elements

- GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

- Hazard pictograms



GHS02



GHS07



GHS08

- Signal word Danger

(Contd. on page 2)

Safety Data Sheet
acc. to OSHA HCS


Printing date 02/10/2021




Reviewed on 02/10/2021

Trade name: Epifanes Yacht Enamel (all colours)

(Contd. of page 1)

- Hazard-determining components of labeling:
Naphtha (petroleum), hydrotreated heavy (Note-p)
cobalt bis(2-ethylhexanoate)
2-methoxy-1-methylethyl acetate
- Hazard statements
H226 Flammable liquid and vapor.
H317 May cause an allergic skin reaction.
H360 May damage fertility or the unborn child.
H336 May cause drowsiness or dizziness.
- Precautionary statements
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310 If swallowed: Immediately call a poison center/doctor.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- Classification system:
- NFPA ratings (scale 0 - 4)

	Health = 0
	Fire = 2
	Reactivity = 0
- HMIS-ratings (scale 0 - 4)

	Health = 0
	Fire = 2
	Reactivity = 0
- Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

3 Composition/information on ingredients

- Chemical characterization: Mixtures
- Description:
Resin mixture
Solvent mixture with pigment additives

(Contd. on page 3)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/10/2021

Reviewed on 02/10/2021

Trade name: Epifanes Yacht Enamel (all colours)

(Contd. of page 2)

· Dangerous components:		
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2	titanium dioxide ☠️ Carc. 2, H351	25-50%
CAS: 64742-48-9 EC number: 919-857-5 Index number: 649-327-00-6	Naphtha (petroleum), hydrotreated heavy (Note-p) 🔥 Flam. Liq. 3, H226 ☠️ Asp. Tox. 1, H304 ⚠️ STOT SE 3, H336	25-50%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7	2-methoxy-1-methylethyl acetate 🔥 Flam. Liq. 3, H226 ⚠️ STOT SE 3, H336	≤2.5%
CAS: 136-52-7 EINECS: 205-250-6	cobalt bis(2-ethylhexanoate) ☠️ Carc. 2, H351; Repr. 1B, H360 ⚠️ Eye Irrit. 2A, H319; Skin Sens. 1A, H317	<0.3%

· Additional information:
For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation:
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact:
Immediately wash with water and soap and rinse thoroughly.
Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed
No further relevant information available.
- Indication of any immediate medical attention and special treatment needed
No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture
During heating or in case of fire poisonous gases are produced.

(Contd. on page 4)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/10/2021

Reviewed on 02/10/2021

Trade name: Epifanes Yacht Enamel (all colours)

(Contd. of page 3)

- Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures
Ensure adequate ventilation
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- Environmental precautions:
Prevent seepage into sewage system, workpits and cellars.
Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- Protective Action Criteria for Chemicals

· PAC-1:

13463-67-7	titanium dioxide	30 mg/m ³
64742-48-9	Naphtha (petroleum), hydrotreated heavy (Note-p)	350 mg/m ³
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
34590-94-8	Dipropylene glycol monomethyl ether	150 ppm
108-83-8	2,6-dimethylheptan-4-one	75 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	30 ppm
70657-70-4	2-methoxypropyl acetate	50 ppm

· PAC-2:

13463-67-7	titanium dioxide	330 mg/m ³
64742-48-9	Naphtha (petroleum), hydrotreated heavy (Note-p)	1,800 mg/m ³
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
34590-94-8	Dipropylene glycol monomethyl ether	1700* ppm
108-83-8	2,6-dimethylheptan-4-one	330 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	33 ppm
70657-70-4	2-methoxypropyl acetate	1,000 ppm

· PAC-3:

13463-67-7	titanium dioxide	2,000 mg/m ³
64742-48-9	Naphtha (petroleum), hydrotreated heavy (Note-p)	40,000 mg/m ³
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
34590-94-8	Dipropylene glycol monomethyl ether	9900** ppm
108-83-8	2,6-dimethylheptan-4-one	2000* ppm
112-34-5	2-(2-butoxyethoxy)ethanol	200 ppm

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/10/2021

Reviewed on 02/10/2021

Trade name: Epifanes Yacht Enamel (all colours)

(Contd. of page 4)

70657-70-4 2-methoxypropyl acetate

5,000 ppm

7 Handling and storage

- Handling:
- Precautions for safe handling
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- Information about protection against explosions and fires:
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems:
No further data; see item 7.
- Control parameters
- Components with limit values that require monitoring at the workplace:
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

108-65-6 2-methoxy-1-methylethyl acetate

WEEL	Long-term value: 50 ppm
------	-------------------------

136-52-7 cobalt bis(2-ethylhexanoate)

TLV	Long-term value: 0.02* mg/m ³ as Co, *inhalable; DSEN; RSEN; BEI
-----	--

108-65-6 2-methoxy-1-methylethyl acetate

WEEL	Long-term value: 50 ppm
------	-------------------------

136-52-7 cobalt bis(2-ethylhexanoate)

TLV	Long-term value: 0.02* mg/m ³ as Co, *inhalable; DSEN; RSEN; BEI
-----	--

- Regulatory information
WEEL: Guide to Occupational Exposure Values (AIHA WEELs)
TLV: Guide to Occupational Exposure Values (TLV)
- Additional information:
The lists that were valid during the creation were used as basis.

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/10/2021

Reviewed on 02/10/2021

Trade name: Epifanes Yacht Enamel (all colours)

(Contd. of page 5)

- Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
- Breathing equipment:
Not necessarily with good ventilation, however, use a filter AX when ventilation is inadequate!
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact gloves made of the following materials are suitable: nitrile rubber;
recommended glove thickness > 0.45mm. permeability / permeation time: > 480 min. according to EN 374.
- As protection from splashes gloves made of the following materials are suitable:
chloroprene; glove thickness > 0.7mm, breakthrough time > 60min. according to EN 374.
nitrile rubber; glove thickness > 0.3 mm, breakthrough time > 60min. volgens EN 374.
- Eye protection:



Tightly sealed goggles

US

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/10/2021

Reviewed on 02/10/2021

Trade name: Epifanes Yacht Enamel (all colours)

(Contd. of page 6)

9 Physical and chemical properties

<ul style="list-style-type: none"> · Information on basic physical and chemical properties · General Information · Appearance: <ul style="list-style-type: none"> Form: Fluid Color: According to product specification · Odor: Characteristic · Odor threshold: Not determined. 	
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	150 °C (302 °F)
· Flash point:	>42 °C (>107.6 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	240 °C (464 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	0.6 Vol %
Upper:	7 Vol %
· Vapor pressure at 20 °C (68 °F):	1 hPa (0.8 mm Hg)
· Density at 20 °C (68 °F):	1.1 g/cm ³ (9.1795 lbs/gal) (ISO 2811)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C (68 °F):	40 s (ISO 6 mm)
· Solvent content:	
Organic solvents:	30.8 %
VOC content:	30.76 %
	VOC content: 338.3 g/l / 2.82 lb/gal
Solids content:	45.9 % (SC% 1h 150C)

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/10/2021

Reviewed on 02/10/2021

Trade name: Epifanes Yacht Enamel (all colours)

(Contd. of page 7)

· Other information No further relevant information available.

10 Stability and reactivity

- Reactivity No further relevant information available.
- Chemical stability
- Thermal decomposition / conditions to be avoided:
No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- Information on toxicological effects
- Acute toxicity:

· LD/LC50 values that are relevant for classification:

13463-67-7 titanium dioxide

Oral	LD50	>20000 mg/kg bw (rat)
Dermal	LD50	>10000 mg/kg bw (rabbit)
Inhalative	LC50/4 h	>6.82 mg/l (rat)

64742-48-9 Naphtha (petroleum), hydrotreated heavy (Note-p)

Oral	LD50	>5000 mg/kg bw (rat)
Dermal	LD50	>5000 mg/kg bw (rabbit) ((24h))
Inhalative	LC50	>5000 mg/m ³ (vapour) (rat) ((8h))

108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8532 mg/kg bw (rat)
Inhalative	LC50/4 h	35.7 mg/l (rat)

136-52-7 cobalt bis(2-ethylhexanoate)

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50 (Konijn)	5000 mg/kg (rabbit)

- Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
- Carcinogenic categories

· IARC (International Agency for Research on Cancer)

13463-67-7 titanium dioxide

2B

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/10/2021

Reviewed on 02/10/2021

Trade name: Epifanes Yacht Enamel (all colours)

(Contd. of page 8)

136-52-7	cobalt bis(2-ethylhexanoate)	2B
· NTP (National Toxicology Program)		
None of the ingredients is listed.		
· OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients is listed.		

12 Ecological information

· Toxicity

· Aquatic toxicity:

64742-48-9 Naphtha (petroleum), hydrotreated heavy (Note-p)

ErL (72h)	>1000 mg/l (Pseudokirchneriella subcapitata-OECD 201)
EL50 (48h)	>1000 mg/l ((Daphnia magna-OECD 202))
LL50 (96h)	>1000 mg/l ((Onorhynchus mykiss OECD 203))
EbL50 (72h)	>1000 mg/l (Pseudokirchneriella subcapitata-OECD 201)
NOELR (72h)	3 mg/l ((Pseudo. subcapitata-biomass-OECD 201)) 100 mg/l ((Pseudo. subcap. growth rate OECD 201))

108-65-6 2-methoxy-1-methylethyl acetate

EC50	408-500 mg/l (daphnia magna) (48 uur/hour)
IC 50	>1000 mg/l (Algae, Growth inhibition test) (72 uur/hour)
LC50	100-180 mg/l (Fish Acute Toxicity Study) (96 uur/hour)

136-52-7 cobalt bis(2-ethylhexanoate)

LC50	0.1-1 mg/l (Fish Acute Toxicity Study)
EC50	0.1-1 mg/l (daphnia magna)
EC50	0.1-1 mg/l (Algae, Growth inhibition test)

- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes:
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

US

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/10/2021

Reviewed on 02/10/2021



Trade name: Epifanes Yacht Enamel (all colours)

(Contd. of page 9)

13 Disposal considerations

- Waste treatment methods
- Recommendation:
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

14 Transport information

- UN-Number
 - DOT, IATA
 - ADR, IMDG
- UN1263
Void
-
- UN proper shipping name
 - DOT
 - ADR
 - IMDG
 - IATA
- CONSUMER COMMODITY, ORM-D
Paint
Void
CONSUMER COMMODITY, ORM-D
Void
PAINT
-
- Transport hazard class(es)
 - DOT
- 
- Class
 - Label
- 3 Flammable liquids
3
-
- ADR, ADN, IMDG
 - Class
- Void
-
- IATA
- 
- Class
 - Label
- 3 Flammable liquids
3
-
- Packing group
 - DOT, IATA
 - ADR, IMDG
- III
Void
-
- Environmental hazards:
 - Marine pollutant:
- No

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/10/2021

Reviewed on 02/10/2021

Trade name: Epifanes Yacht Enamel (all colours)

(Contd. of page 10)

· Special precautions for user	Not applicable.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· Remarks:	CERCLA/DOT RQ: 617gal./4786 lbs.
· ADR	
· Remarks:	Packaging <450L: exemption viscous substances according to 2.2.3.1.5 > 450 l: 3 F1, III
· IMDG	
· Remarks:	> 450 l: 3, III
· UN "Model Regulation":	Void

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

136-52-7 cobalt bis(2-ethylhexanoate)

112-34-5 2-(2-butoxyethoxy)ethanol

· TSCA (Toxic Substances Control Act):

13463-67-7	titanium dioxide	ACTIVE
64742-48-9	Naphtha (petroleum), hydrotreated heavy (Note-p)	ACTIVE
108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE
34590-94-8	Dipropylene glycol monomethyl ether	ACTIVE
68409-80-3	Isomers of fatty acid calcium salts, C6-C19	ACTIVE
100-64-1	cyclohexanone oxime	ACTIVE
22464-99-9	Zirconiumoctoate, 12 % Zr	ACTIVE
105-44-2	4-methylpentan-2-one oxime	ACTIVE
8002-43-5	Soyalecithine	ACTIVE
108-83-8	2,6-dimethylheptan-4-one	ACTIVE
136-52-7	cobalt bis(2-ethylhexanoate)	ACTIVE
112-34-5	2-(2-butoxyethoxy)ethanol	ACTIVE

· Hazardous Air Pollutants

136-52-7 cobalt bis(2-ethylhexanoate)

(Contd. on page 12)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/10/2021

Reviewed on 02/10/2021

Trade name: Epifanes Yacht Enamel (all colours)

(Contd. of page 11)

· Proposition 65

· Chemicals known to cause cancer:	
13463-67-7	titanium dioxide

· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	

· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	

· Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	

· Cancerogenity categories

· EPA (Environmental Protection Agency)	
None of the ingredients is listed.	

· TLV (Threshold Limit Value)		
13463-67-7	titanium dioxide	A4

· MAK (German Maximum Workplace Concentration)		
13463-67-7	titanium dioxide	3A

· NIOSH-Ca (National Institute for Occupational Safety and Health)	
13463-67-7	titanium dioxide

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

Naphtha (petroleum), hydrotreated heavy (Note-p)
cobalt bis(2-ethylhexanoate)
2-methoxy-1-methylethyl acetate

· Hazard statements

H226 Flammable liquid and vapor.
H317 May cause an allergic skin reaction.
H360 May damage fertility or the unborn child.
H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310 If swallowed: Immediately call a poison center/doctor.

(Contd. on page 13)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/10/2021

Reviewed on 02/10/2021

Trade name: Epifanes Yacht Enamel (all colours)

(Contd. of page 12)

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- National regulations:
- Technical instructions (air):

Class	Share in %
NK	25-50

- Water hazard class:
Water hazard class 1 (Self-assessment): slightly hazardous for water.
- Chemical safety assessment:
A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: Environment protection department.
- Contact: J.J. van Dijk
- Date of preparation / last revision 02/10/2021 / 8
- Abbreviations and acronyms:
 RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 ICAO: International Civil Aviation Organisation
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 Flam. Liq. 3: Flammable liquids - Category 3
 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A
 Skin Sens. 1: Skin sensitisation - Category 1
 Skin Sens. 1A: Skin sensitisation - Category 1A
 Carc. 2: Carcinogenicity - Category 2
 Repr. 1B: Reproductive toxicity - Category 1B
 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3
 Asp. Tox. 1: Aspiration hazard - Category 1
- * Data compared to the previous version altered.