



## Safety Data Sheet

Copyright, 2022, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	31-9671-4	<b>Version number:</b>	4.00
<b>Issue Date:</b>	2022/12/08	<b>Supersedes Date:</b>	2021/11/17

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Finesse-It™ Polish - Extra Fine, 6002

##### Product Identification Numbers

LA-B100-2281-5	LB-K100-1364-1	LB-K100-1364-2	LB-K100-1522-8	60-4402-4028-5
60-4402-4173-9	60-4402-4359-4	60-4403-6208-9	60-4403-6214-7	60-9801-0518-7
H0-0022-4388-1	HC-0005-6798-8	JC-3100-1010-6		

#### 1.2. Recommended use and restrictions on use

##### Intended Use

Industrial use

##### Specific Use

Polish

##### Restrictions on use

Not applicable

#### 1.3. Supplier's details

<b>Company:</b>	3M Canada Company
<b>Division:</b>	Abrasive Systems Division
<b>Address:</b>	1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1
<b>Telephone:</b>	(800) 364-3577
<b>Website:</b>	www.3M.ca

#### 1.4. Emergency telephone number

Medical Emergency Telephone: 1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

Not classified according to the Canadian Hazardous Products Regulation.

#### 2.2. Label elements

**Signal word**

Not applicable.

**Symbols**

Not applicable.

**Pictograms**

Not applicable.

**2.3. Other hazards**

None known.

**SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Water	7732-18-5	60 - 80	Water
ALUMINUM OXIDE MINERAL	1344-28-1	5 - 7	Aluminum oxide (Al <sub>2</sub> O <sub>3</sub> )
Distillates (Petroleum), Acid Treated, Light	64742-14-9	5 - 7	Distillates (petroleum), acid-treated light
Hydrotreated Heavy Naphtha (Petroleum)	64742-48-9	5 - 7	Naphtha, petroleum, hydrotreated heavy
Hydrotreated Light Petroleum Distillates	64742-47-8	5 - 7	Distillates, petroleum, hydrotreated light
Mineral Oil	8042-47-5	1 - 2	White mineral oil (petroleum)

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**

If exposed, wash with soap and water. If signs/symptoms develop, get medical attention.

**Eye Contact:**

If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable.

**SECTION 5: Fire-fighting measures****5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

**5.2. Special hazards arising from the substance or mixture**

None inherent in this product.

**Hazardous Decomposition or By-Products****Substance**

Hydrocarbons  
Carbon monoxide  
Carbon dioxide  
Oxides of Nitrogen

**Condition**

During Combustion  
During Combustion  
During Combustion  
During Combustion

**5.3. Special protective actions for fire-fighters**

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA). Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Observe precautions from other sections.

**6.2. Environmental precautions**

Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

Avoid breathing dust/fume/gas/mist/vapours/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment.

**7.2. Conditions for safe storage including any incompatibilities**

No special storage requirements.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

<b>Ingredient</b>	<b>C.A.S. No.</b>	<b>Agency</b>	<b>Limit type</b>	<b>Additional Comments</b>
Aluminum, insoluble compounds	1344-28-1	ACGIH	TWA(respirable fraction):1 mg/m <sup>3</sup>	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit  
CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

None required.

#### Skin/hand protection

No chemical protective gloves are required.

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Emulsion
Colour	White
Odour	Slight Solvent
Odour threshold	<i>No Data Available</i>
pH	<i>Not Applicable</i>
Melting point/Freezing point	<i>Not Applicable</i>
Boiling point	100 °C
Flash Point	Flash point > 93 °C (200 °F)
Evaporation rate	<i>No Data Available</i>
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	<i>No Data Available</i>
Flammable Limits(UEL)	<i>No Data Available</i>
Vapour Pressure	2,399.8 Pa [ <i>@ 20 °C</i> ]
Vapour Density and/or Relative Vapour Density	<i>No Data Available</i>
Density	0.96 - 0.99 g/ml
Relative density	0.96 - 0.99 [ <i>Ref Std: WATER=1</i> ]
Water solubility	Moderate
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Viscosity/Kinematic Viscosity	16,000 - 20,000 mPa-s [ <i>Test Method: Brookfield</i> ]
Volatile Organic Compounds	20.8 % weight [ <i>Details: Calculated</i> ]

Percent volatile	70.7 % weight [ <i>Details: Calculated including water</i> ]
VOC Less H2O & Exempt Solvents	395 g/l [ <i>Details: Calculated</i> ]
Molecular weight	<i>No Data Available</i>

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

None known.

### 10.5. Incompatible materials

None known.

### 10.6. Hazardous decomposition products

#### Substance

#### Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

**Based on test data and/or information on the components, this material may produce the following health effects:**

#### **Inhalation:**

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

#### **Skin Contact:**

Contact with the skin during product use is not expected to result in significant irritation.

#### **Eye Contact:**

Contact with the eyes during product use is not expected to result in significant irritation.

#### **Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Hydrotreated Heavy Naphtha (Petroleum)	Inhalation-Vapor	Professional judgement	LC50 estimated to be 20 - 50 mg/l
Hydrotreated Heavy Naphtha (Petroleum)	Dermal	Rabbit	LD50 > 5,000 mg/kg
Hydrotreated Heavy Naphtha (Petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Distillates (Petroleum), Acid Treated, Light	Inhalation-Vapor	Professional judgement	LC50 estimated to be 20 - 50 mg/l
Hydrotreated Light Petroleum Distillates	Inhalation-Vapor	Professional judgement	LC50 estimated to be 20 - 50 mg/l
Distillates (Petroleum), Acid Treated, Light	Dermal	Rabbit	LD50 > 5,000 mg/kg
Hydrotreated Light Petroleum Distillates	Dermal	Rabbit	LD50 > 5,000 mg/kg
Distillates (Petroleum), Acid Treated, Light	Ingestion	Rat	LD50 > 5,000 mg/kg
Hydrotreated Light Petroleum Distillates	Ingestion	Rat	LD50 > 5,000 mg/kg
ALUMINUM OXIDE MINERAL	Dermal		LD50 estimated to be > 5,000 mg/kg
ALUMINUM OXIDE MINERAL	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
ALUMINUM OXIDE MINERAL	Ingestion	Rat	LD50 > 5,000 mg/kg
Mineral Oil	Dermal	Rabbit	LD50 > 2,000 mg/kg
Mineral Oil	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Hydrotreated Heavy Naphtha (Petroleum)	Rabbit	Mild irritant
Distillates (Petroleum), Acid Treated, Light	Rabbit	Minimal irritation
Hydrotreated Light Petroleum Distillates	Rabbit	Minimal irritation
ALUMINUM OXIDE MINERAL	Rabbit	No significant irritation
Mineral Oil	Rabbit	No significant irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
Hydrotreated Heavy Naphtha (Petroleum)	Rabbit	Mild irritant
Distillates (Petroleum), Acid Treated, Light	Rabbit	Mild irritant
Hydrotreated Light Petroleum Distillates	Rabbit	Mild irritant
ALUMINUM OXIDE MINERAL	Rabbit	No significant irritation
Mineral Oil	Rabbit	Mild irritant

**Skin Sensitization**

Name	Species	Value
Hydrotreated Heavy Naphtha (Petroleum)	Guinea pig	Not classified
Distillates (Petroleum), Acid Treated, Light	Guinea pig	Not classified
Hydrotreated Light Petroleum Distillates	Guinea pig	Not classified
Mineral Oil	Guinea pig	Not classified

**Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
Hydrotreated Heavy Naphtha (Petroleum)	In Vitro	Not mutagenic
Hydrotreated Heavy Naphtha (Petroleum)	In vivo	Not mutagenic
Distillates (Petroleum), Acid Treated, Light	In Vitro	Not mutagenic
Distillates (Petroleum), Acid Treated, Light	In vivo	Not mutagenic
Hydrotreated Light Petroleum Distillates	In Vitro	Not mutagenic
Hydrotreated Light Petroleum Distillates	In vivo	Not mutagenic
ALUMINUM OXIDE MINERAL	In Vitro	Not mutagenic
Mineral Oil	In Vitro	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
Hydrotreated Heavy Naphtha (Petroleum)	Not Specified	Not available	Not carcinogenic
Distillates (Petroleum), Acid Treated, Light	Not Specified	Not available	Not carcinogenic
Hydrotreated Light Petroleum Distillates	Not Specified	Not available	Not carcinogenic
ALUMINUM OXIDE MINERAL	Inhalation	Rat	Not carcinogenic
Mineral Oil	Dermal	Mouse	Not carcinogenic
Mineral Oil	Inhalation	Multiple animal species	Not carcinogenic

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Hydrotreated Heavy Naphtha (Petroleum)	Not Specified	Not classified for female reproduction	Rat	NOAEL Not available	1 generation
Hydrotreated Heavy Naphtha (Petroleum)	Not Specified	Not classified for male reproduction	Rat	NOAEL Not available	28 days
Hydrotreated Heavy Naphtha (Petroleum)	Not Specified	Not classified for development	Rat	NOAEL Not available	during gestation
Distillates (Petroleum), Acid Treated, Light	Not Specified	Not classified for female reproduction	Rat	NOAEL Not available	1 generation
Distillates (Petroleum), Acid Treated, Light	Not Specified	Not classified for male reproduction	Rat	NOAEL Not available	1 generation
Distillates (Petroleum), Acid Treated, Light	Not Specified	Not classified for development	Rat	NOAEL Not available	1 generation
Hydrotreated Light Petroleum Distillates	Not Specified	Not classified for female reproduction	Rat	NOAEL Not available	1 generation
Hydrotreated Light Petroleum Distillates	Not Specified	Not classified for male reproduction	Rat	NOAEL Not available	28 days
Hydrotreated Light Petroleum Distillates	Not Specified	Not classified for development	Rat	NOAEL Not available	during gestation
Mineral Oil	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
Mineral Oil	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
Mineral Oil	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Hydrotreated Heavy Naphtha (Petroleum)	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
ALUMINUM OXIDE MINERAL	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
ALUMINUM OXIDE MINERAL	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Mineral Oil	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
Mineral Oil	Ingestion	liver   immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days

**Aspiration Hazard**

Name	Value
Hydrotreated Heavy Naphtha (Petroleum)	Aspiration hazard
Distillates (Petroleum), Acid Treated, Light	Aspiration hazard
Hydrotreated Light Petroleum Distillates	Aspiration hazard
Mineral Oil	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

No data available.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Prior to disposal, consult all applicable authorities and regulations to insure proper classification. Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty and clean product containers may be disposed as non-hazardous waste. Consult your specific regulations and service providers to determine available options and requirements.

**SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Global inventory status**



Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

## SECTION 16: Other information

**National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.**

**Health: 1 Flammability: 1 Instability: 0 Special Hazards: None**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document group:</b>	31-9671-4	<b>Version number:</b>	4.00
<b>Issue Date:</b>	2022/12/08	<b>Supersedes Date:</b>	2021/11/17

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

**3M Canada SDSs are available at [www.3M.ca](http://www.3M.ca)**