## DURAL CO INC -- NO. 2672-5 CONTACT CEMENT -- 5330-01-268-7590

Product ID:NO. 2672-5 CONTACT CEMENT MSDS Date:01/03/1994 FSC:5330 NIIN:01-268-7590 Kit Part:Y MSDS Number: CGMKM === Responsible Party === Company Name: DURAL CO INC Address: 5724 W FLORIST AVE City:MILWAUKEE State:WI ZIP:53218-1623 Country:US Info Phone Num: 414-466-7060 Emergency Phone Num:414-466-7060 CAGE:25999 === Contractor Identification === Company Name: DURAL CO INC Address: 5724 W. FLORIST AVE Box:City:MILWAUKEE State:WI ZIP:53218 Country:US Phone: 414-466-7060 CAGE:25999 Ingred Name: HEXANE (N-HEXANE) (CERCLA) CAS:110-54-3 RTECS #:MN9275000 Fraction by Wt: 60% Other REC Limits:NONE RECOMMENDED OSHA PEL:500 PPM ACGIH TLV:50 PPM; 9596 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB Ingred Name: TOLUENE (SARA 313) (CERCLA) CAS:108-88-3 RTECS #:XS5250000 Fraction by Wt: 20% Other REC Limits:NONE RECOMMENDED OSHA PEL:200 PPM; Z-2 ACGIH TLV:S, 50 PPM; 9596 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ingred Name: NEOPRENE (MFR GAVE CAS# 14807-96-6 WHICH IS TALC) CAS:9010-98-4 RTECS #:EI9640000 Fraction by Wt: 10% Other REC Limits:NONE RECOMMENDED

Ingred Name:PHENOLIC RESIN CAS:28085-50-1 Fraction by Wt: 10% Other REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYE CONTACT CAN CAUSE SEVERE IRRITATION. SKIN PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE MODERATE IRRITATION OR DERMATITIS. INHALATION MAY CAUSE CNS DEPRESSION, NASAL & RESPIRATORY IRRITATION. INGES TION MAY CAUSE GI TRACT IRRITATION. ASPIRATION MAY CAUSE CHEMICAL PNEUMONITIS. Explanation of Carcinogenicity: NO INGREDIENT OR A CONCENTRATION OF 0.1% OR GREATER IS LISTED BY NTP, IARC OR REGULATED BY OSHA AS A CARCINOGEN. Effects of Overexposure: EYES-REDNESS, TEARING, BLURRED VISION. SKIN-IRRITATION, DEFATTING, DERMATITIS. INHALED-NASAL & RESPIRATORY IRRITATION, DIZZINESS, NAUSEA, FATIGUE, HEADACHE & POSSIBLE UNCONSCIOUSNESS, DEATH. INGESTED- GI TRACT IRRITATION, VOMITING, DIRRHEA. Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER. First Aid:EYES-FLUSH WITH WATER FOR AT LEAST 15 MINUTES, LIFT LIDS. GET MEDICAL ATTENTION. SKIN-REMOVE CONTAMINATED CLOTHES. WASH WITH SOAP & WATER. INHALED-REMOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF B REATHING STOPPED. GIVE OXYGEN IF BREATHING DIFFICULT. GET MEDICAL ATTENTION. INGESTED-DO NOT INDUCE VOMITING! GET MEDICAL ATTENTION. Flash Point Method:TOC Flash Point: -25F, -32C Lower Limits:1.0 Extinguishing Media: REGULAR FOAM OR CARBON DIOXIDE. Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND

FULL FIREFIGHTERS PROTECTIVE GEAR. COOL CONTAINERS EXPOSED TO FIRE WITH WATER.

Unusual Fire/Explosion Hazard:MATERIAL IS HIGHLY VOLATILE, VAPORS TRAVEL ALONG GROUND TO DISTANT IGNITION SOURCE AND FLASHBACK.

Spill Release Procedures: ABSORB ON PAPER, VERMICULITE, FLOOR ABSORBENT OR OTHER ABSORBENT MATERIAL AND TRANSFER TO HOOD. Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE AWAY FROM SOURCES OF IGNITION AND STRONG OXIDIZING AGENTS.

Other Precautions: CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED SINCE EMPTIED CONTAINERS MAY RETAIN PRODUCT RESIDUES (VAPOURS, LIQUID, AND/OR BOTH). ALL HAZARD PRECAUTIONS GIVEN IN THIS MSDS MUST BE OBSERVE D FOR EMPTY CONTAINERS. Respiratory Protection: IF AN EMERGENCY OR UNUSUAL PROCEDURE OCCURS, USE APPROPRIATE RESPIRATORY PROTECTION AS REQUIRED. USE/WEAR IAW 29 CFR 1910.134. Ventilation: PROVIDE SUFFICIENT EXPLOSION-PROOF MECHANICAL VENTILATION (GENERAL/LOCAL) TO MAINTAIN LEVELS BELOW PEL/TLV(S). Protective Gloves: IMPERVIOUS SUCH AS NITRILE, RUBBER. Eye Protection: SAFETY GLASSES/CHEMICAL SPLASH GOGGLES. Other Protective Equipment: IMPERVIOSU CLOTHING & BOOTS. DLA-HMIS: EYE WASH STATION & SAFETY SHOWER. Work Hygienic Practices: WASH WITH SOAP & WATER BEFORE EATING, DRINKING, SMOKING OR USING THE TOILET. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE. Supplemental Safety and Health HCC:F2 Boiling Pt:B.P. Text:100F,38C Vapor Pres:145 Vapor Density: 3.0 Spec Gravity:0.872 Evaporation Rate & Reference:7.0 (N-BUTYL ACETATE=1) Appearance and Odor: NONE SPECIFIED BY MANUFACTURER. Percent Volatiles by Volume:100% Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid: NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products: CARBON MONOXIDE AND CARBON DIOXIDE, VARIOUS HYDROCARBONS, ETC. Conditions to Avoid Polymerization: CANNOT OCCUR. Waste Disposal Methods: CONTAMIANTED ABSORBENT MAY BE DISPOSED OF IN A LANDFILL IAW LOCAL, STATE AND FEDERAL REGULATIONS. Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.