

<b>Reolink-Floodlight-WiFi-Specifications</b>		
	<b>Model</b>	<b>Reolink Floodlight WiFi</b>
<b>General</b>	Light	40pcs, 18W, 4200K, 2000lm
	Indicator Light	Support
	PIR	8m
	Daylight Sensor	Support
<b>Power</b>	DC Power	DC 12.0V~2A, <25W
<b>Interface</b>	Power	DC power port
	System	Reset button
	Ethernet	One 10M/100Mbps; RJ45
	Audio	Built-in speaker (can only be triggered by linked device)
<b>Software Features</b>	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
	Smart Alarm	PIR
	Max. User Access	10 users (1 admin account & 9 user accounts)
	Work with	Google Assistant
<b>Wi-Fi</b>	Wireless Standard	IEEE 802.11b/g/n
	Operating Frequency	2.4GHz
	Wireless Security	WPA-PSK/WPA2-PSK
<b>Working Environment</b>	Temperature	Operating temperature: -10°C~+55°C (14°F~131°F)
	Humidity	Operating humidity: 10% ~ 90%
	Waterproof	IP65
<b>Size &amp; Weight</b>	Dimension	216x118x160mm
	Weight	630g
<b>Warranty</b>	Limited Warranty	2-year limited warranty. For support, visit <a href="https://support.reolink.com/hc/en-us/">https://support.reolink.com/hc/en-us/</a>