

UA-Hub-Elevator

Mechanical

Dimensions 129.3 x 244.7 x 33.6 mm (5.1 x 9.6 x 1.3")

Weight 537 g (1.2 lb)

Enclosure material Polycarbonate

Mounting material Polycarbonate

Hardware

Networking interface (4) 10/100/1000 Base-T

Management interface (1) 10/100/1000 Base-T

Power method PoE++

Max. power consumption 7W (Without PoE output)

PoE input (1) PoE++, 50V DC, 1.2A

PoE output PoE passthrough, (4) PoE, 50V DC, total 42W

ESD/EMP protection Air: ±8kV, contact: ±4kV

Digital input (6) Car position; Up/down/stop/full/door open/door close
(1) Emergency

Outputs (18) Relays
Rating 30V DC/2A

LEDs System: white/blue/red
Output relays: white

Buttons (1) Factory-reset
Terminal blocks

Operating temperature -10 to 40° C (14 to 104° F)

Operating humidity 5 to 95% noncondensing

Certifications CE, FCC, IC

UACC-Extender-2Wire-Tx/Rx

Mechanical

Dimensions 40 x 105 x 25 mm (1.6 x 4.1 x 1")

Weight PoE in: 77 g (2.7 oz)
PoE out: 79 g (2.8 oz)

Enclosure material Polycarbonate

Mounting material Polycarbonate

Hardware

Networking interface (1) 10/100 MbE
(1) Homeplug AV

Management interface (1) 10/100 MbE

Power method PoE++

Max. power consumption 3W (Without PoE output)

PoE input (1) PoE++, 50V DC, Max. 1.2A

PoE output (1) PoE+, 48V DC, 0.72A

ESD/EMP protection Air: ±8kV, contact: ±4kV

LED White

Operating temperature -10 to 40° C (14 to 104° F)

Operating humidity 5 to 95% noncondensing

Certifications CE, FCC, IC

UA-G2

Mechanical

Dimensions 93 x 40 x 36.5 mm (3.7 x 1.6 x 1.4")

Weight 82 g (2.9 oz)

Enclosure material Polycarbonate, glass

Mounting In wall, gang box

Weatherproofing IP55

Hardware

Networking interface (1) 10/100 MbE RJ45 port

Connectivity BLE 4.1

Power method	PoE
Supported voltage range	48V DC
Max. power consumption	5W
ESD/EMP protection	Air: ±15kV, contact: ±8kV
Sensors	Proximity sensor
Speaker	(1) 8 ohm, 0.7W
LEDs	R/G/B/W
Button	(1) Factory-reset
NFC frequency	13.56 MHz
NFC read range	< 30 mm
NFC standards	ISO 14443A, 14443B, 15693
NFC technology	NFC Tag 1,2,3,4,5 MIFARE Classic MIFAREPlus MIFARE Ultralight MIFARE DESFire
Operating temperature	-30 to 45° C (-22 to 113° F)
Operating humidity	5 to 90% noncondensing
Certifications	CE, FCC, IC
UA-Card	
Mechanical	
Dimensions	85.6 x 54 x 0.8 mm (3.4 x 2.1 x 0.03")
Weight	5 g (0.18 oz)
Format	ISO 7810 ID-1
NFC frequency	13.56 MHz
NFC technology	ISO/IEC 14443 Type A MIFARE DESFire UniFi Access Proprietary Security Protocol