

Mechanical

Dimensions 442.4 x 325 x 43.7 mm (17.4 x 12.8 x 1.7")

Weight Without mounting brackets: 5.1 kg (11.3 lb)
With mounting brackets: 5.2 kg (11.5 lb)

Enclosure material SGCC steel

Hardware

Management interface Ethernet In-Band

Networking interface (16) GbE RJ45 ports
(8) 1/2.5 GbE RJ45 ports
(2) 10G SFP+ ports

PoE interface (8) PoE/PoE+ (Pins 1, 2+; 3, 6-)
(16) 60W PoE++ (Pair A 1, 2+; 3, 6-) (Pair B 4, 5+; 7, 8-)

Total non-blocking throughput 56 Gbps

Switching capacity 112 Gbps

Power method Universal input, 100–240V AC, 50/60 Hz
USP RPS DC input

Power supply AC/DC, internal, 450W

Supported voltage range 100–240V AC

Max. power consumption 50W (Excluding PoE output)

Total available PoE 400W

Max. PoE wattage per port by PSE PoE: 15.4W
PoE+: 30W
PoE++: 60W

Voltage range PoE mode PoE: 44–57V
PoE+: 50–57V

LCM display (1) 1.3" touchscreen

Button Factory reset

Operating temperature -5 to 40° C (23 to 104° F)

Operating humidity 10 to 90% noncondensing

Certifications CE, FCC, IC

Etherlighting™

Ethernet

Locating
Speed/link
Native VLAN/network

SFP+

Locating
Speed/link
Native VLAN/network

LEDs

System

Status

RPS

Status