

## Mechanical

Dimensions	98 x 98 x 30 mm (3.9 x 3.9 x 1.2")
Weight	320 g (11.3 oz)
Enclosure materials	Polycarbonate

## Hardware

Processor	Dual-core ARM® Cortex®-A53 at 1 GHz
Memory information	1 GB DDR3L
Management interface	Ethernet Bluetooth 5.1
Networking interface	(1) GbE RJ45 WAN port (1) GbE RJ45 LAN port
Power method	USB type C (5V/3A)
Supported voltage range	100–240V
Max. power consumption	3.83W
Operating temperature	-10 to 40° C (14 to 104° F)
Operating humidity	5 to 95% noncondensing
Certifications	CE, FCC, IC

## Gateway Features

Performance	WiFi QoS with UniFi APs Application, domain, and country-based QoS Application and device type identification Additional internet failover with LTE Backup Internet quality and outage reporting
Next-generation security	Application-aware firewall rules Signature-based IPS/IDS threat detection Content, country, domain, and ad filtering VLAN/subnet-based traffic segmentation Full stateful firewall

## Advanced networking

License-free SD-WAN\*  
WireGuard, L2TP and OpenVPN server  
OpenVPN client  
OpenVPN and IPsec site-to-site VPN  
One-click Teleport\* and UID VPN\*\*  
Policy-based WAN and VPN routing  
DHCP relay  
Customizable DHCP server  
IGMP proxy  
IPv6 ISP support

\*When paired with a Cloud Key or Official UniFi Hosting.

\*\*When paired with a Cloud Key.