

## Easy To Reach Cabinet Assembly Guide

---

- 1.) Clamp the two sections of the face frame together and screw them together with 1 ¼” screws on both ends.
- 2.) Apply wood glue to the face frame dado. Insert cabinet sides and staple at a 45-degree angle into the face frame.
- 3.) Apply Wood Glue and insert the cabinet bottom into the dados. Then, staple them at a 45-degree angle at the bottom into the cabinet sides. Using the assembly blocks, secure the bottom to the face frame and both sides by placing a pair of staples into each leg of the block.
- 4.) Notice that one piece of the toe kick is ½” longer than the other piece. At a 90-degree angle, line up the end of the longer piece on top of the end of the shorter piece. Staple along the end and then reinforce it with two screws.
- 5.) Attach assembly blocks to the toe kick at each end and in the center of each section. Then, line the toe kick up to the bottom of the cabinet and secure with the assembly blocks.
- 6.) Install shelf clips into the sides and insert the shelf into the cabinet.
- 7.) **\*\*\*If you are installing a Lazy Susan Kit, please follow the Lazy Susan Kit instructions on page 2 and install before proceeding to the next step.\*\*\***
- 8.) Apply Wood Glue and insert the cabinet top into the dados. Then, staple them at a 45-degree angle at the top into the cabinet sides. Using the assembly blocks, secure the top to the face frame and to both sides.
- 9.) Insert the cabinet back into the dados of the cabinet sides. Using a jig, mark the cabinet back. Then screw the back to the top and bottom.
- 10.) Install the 2 ¼” hinge blocks onto the cabinet side up against the face frame.

**\*Instructions continued on next page.**

# Lazy Susan Insert

---

- 1.) Place the lazy susan shelf on the easy reach shelf, lining up the corner of the hardware plate to the pie cut out on the easy reach shelf.
- 2.) Line up the pre-drilled hole on the shelf with the hole located on the underneath hardware plate, then secure in place with a screw.
- 3.) Spin the shelf to line up the other three holes and secure them with screws.
- 4.) After you have secured the hardware plate to the shelf, spin the lazy susan to ensure that it spins correctly.
- 5.) Repeat the steps to install the lazy susan shelf to the bottom of the easy reach cabinet.