



## NZ5313

### PET Backlit

#### Description:

Ingredient: PET / Coating

Width: 0.914/1.07/1.27/1.37/1.52/1.83m

#### Features:

1. Perfect color reproduction with stable ink absorption and faster drying ability.
2. UV resistance, high tearing strength, suitable for indoor and outdoor light box advertising.

#### Applications:

1. Suitable for indoor and outdoor advertising, exhibition display, sports and election activities.
2. The product is mainly suitable for digital inkjet printing and other printing method with **Solvent, Eco-solvent ink, Latex and UV.**

#### Technical Data:

Testing condition: Indoor temperature  $23\pm 2^{\circ}\text{C}$ , Relative humidity  $50\pm 5\%$ .

Test Term	Units	Test Method	Average
Weight-finished product	g/m <sup>2</sup>	GB/T4669	260±20
Tensile strength at MD	N/5cm	GB/T1040	≥1200
Tensile strength at CD	N/5cm	GB/T1040	≥1100
Whiteness		GB/T1040	60±10
Applicable Temperature	°C		-20~+70

- All technical data is subject to change without prior notice.

#### Storage Condition:

All NAR products need to be stored in the original packing and with the original protection materials, preferable stored hermetically and vertically, do not expose to direct sunlight or heat sources. In order to avoid loss of quality, NAR products should also be stored in suitable conditions, that is at a temperature of  $25\pm 5^{\circ}\text{C}$  and a relative humidity of  $50\pm 15\%$ .

Under these conditions, NAR products can be stored up to one year.

#### Production and Application Environment:

Production environment: temperature of  $25\pm 5^{\circ}\text{C}$ , relative humidity of  $50\pm 10\%$ , clean dust-free environment without suspended matter; Please move the materials to the printing environment 24 hours before printing. Printing test before use, Printing ink temperature of  $18^{\circ}\text{C}$  - $28^{\circ}\text{C}$ , Equipment preheating temperature of  $30^{\circ}\text{C}$ .

Application environment: temperature of  $18^{\circ}\text{C}$  to  $28^{\circ}\text{C}$ , relative humidity of  $50\pm 15\%$ .



Linea 146 S.A. de C.V. Castilla #54, Centro de Azcapotzalco, Azcapotzalco, C.P. 02000, CDMX  
RFC: LCC190308QA4 Tel: (+5255) 1742 2166 ó 67 E-mail: ventas@faunadigital.com Website: www.linea146.com

### Warranty Condition:

1. One year service life: stored in suitable conditions, preferably use within 6 months.
2. One year prosecution period: from the product manufacture date, no-acceptance for overdue product

### Important Remark:

The information mentioned in this product data sheet is based upon tests that were executed by NAR, and that we consider to be reliable. Advise to use the same batch. Please evaluate on the project environment in advance to confirm the products suitability.

### Application:

