



NT1615

Premium Backlit Fabric

Description:

Base fabric: 300D*300d;
Width: 1.60/2.60/3.20m

Features:

1. Light weight; soft; good tensile; environment friendly; excellent appearance; no fading under strong light.
2. Good compatibility with UV printing machine, 3.20m wide.
3. Good adhesion and anti-scratch.

Applications:

1. Suitable for indoor and outdoor advertising, exhibition display, sports and election activities.
2. The product is mainly suitable for **UV printing**.

Technical Data:

Testing condition: Indoor temperature $23\pm 2^{\circ}\text{C}$, Relative humidity $50\pm 5\%$.

Test Term	Units	Test Method	Average
Base Fabric Yarn	Denier	GB/T16604	300DX300D
Weight-finished product	g/m ²	GB/T4669	180 \pm 20
Tensile strength at MD	N/5cm	GB/T1040	\geq 1000
Tensile strength at CD	N/5cm	GB/T1040	\geq 800
Tearing Strength at break MD	N/5cm	GB/T16578	\geq 20
Tearing Strength at break CD	N/5cm	GB/T16578	\leq 20
Applicable Temperature	$^{\circ}\text{C}$		-20 $^{\circ}$ +70
Flame Retardancy			B1

- All technical data is subject to change without prior notice.

Storage Condition:

All NAR products always need to be stored in the original packing and with the original protection materials, preferably stored hermetically and vertically, do not expose to direct sunlight of heat sources. In order to avoid loss of quality, NAR products should also be stored in suitable conditions, that is at a temperature of $25^{\circ}\text{C}\pm 5^{\circ}\text{C}$ and a relative humidity of $50\pm 15\%$. Under these conditions, NAR products can be stored up to one year.

Production and Application Environment:

Production environment: temperature of $25\pm 5^{\circ}\text{C}$, relative humidity of $50\%\pm 10\%$, clean dust-free environment without suspended matter; Please move the materials to the printing environment 24 hours before printing. Printing test before use, Printing ink temperature of 18°C - 28°C , Equipment preheating temperature of 30°C .
Application environment: temperature of 18°C to 28°C , relative humidity of $50\pm 15\%$.



Linea 146 S.A. de C.V. Castilla #54, Centro de Azcapotzalco, Azcapotzalco, C.P. 02000, CDMX
RFC: LCC190308QA4 Tel: (+5255) 1742 2166 ó 67 E-mail: ventas@faunadigital.com Website: www.linea146.com

Warranty Condition:

1. One year service life: stored in suitable conditions, preferably use within 6 months.
2. One year prosecution period: from the product manufacture date, no-acceptance for overdue product

Important Remark:

The information mentioned in this product data sheet is based upon tests that were executed by NAR, and that we consider to be reliable. Advise to use the same batch. Please evaluate on the project environment in advance to confirm the products suitability.

Application:

