



6.35mmx0.8mm Brass Tin Plated Fashion Female Connector STS:704-BS-2

6.35mmx0.8mm Brass Tin Plated Fashion Female Connector STS:704-BS-2
 plastic insulation boot

1000⁺⁵⁰

Rotation

Ø246±1.5

Air flow direction

79±2

69±1

4.5

29

4-Ø4.2

Ø236±0.3

Label

Label

Specification

1. Fan type: EXR150-200R-S-1600-M02
2. Ring material: PP
3. Impeller material: PC+10%GF
4. Duty: Continuous
5. Rated Voltage: 120/230VAC 50/60Hz
6. Rotation: CCW (Viewed from rotor)
7. Bearing: ball bearing
8. Dielectric strength: 1500VAC 1min 10mA
9. Operating temperature: -40°C~+50°C
10. Storage temperature: -40°C~+60°C
11. Type of protection: IP55
12. Insulation class: B
13. Totally electronic protection: Yes
14. Balancing accuracy: G6.3

EXR150-15-6301		FAN:	
120/230VAC	50/60Hz	0.3A	EXR150-200R-
CONT-AC-TP-CCW-	IP55		S-1600-M02
CE	RoHS	UL	n: 1600/r/min
DD/MM/YYYY Made In China			

Airflow calculated with fan assembled inside EXR150-200mm plastic fan ring

Voltage range	Rated Voltage	Frequency	Speed	Static Pressure	Air flow	Power input
VAC	VAC	Hz	r/min	Pa	CFM	W
85~265	120/230	50/60	1600	0	276	8

EC Fans & Drives

EXR150-200R-S-1600-M02

APPROVED

Mark	Number of piece	Partition	Change the file number	Signature	Date	Revision		Quality proportion
						Standardization	Approval	
Design						A		1:1
Check								
Process						Total 1 Leaf	The first 1 Leaf	

2016.9.29