



PROVAC

SALES

PHONE: 831-462-8900

FAX: 831-462-3536

WWW.PROVAC.COM

Alcatel 2008AC, 2012AC

Technical Specifications

50 Hz						60 Hz	
2008 AC	2012 AC					2008 AC	2012 AC
10	15	m ³ /h	Nominal pumping speed	Free air displacement	cfm	7	11
170	260	l/mn			l/mn	195	310
2	2	Stages				2	2
1 × 10 ⁻⁴	1 × 10 ⁻⁴	mbar	Ultimate vacuum*		mbar	1 × 10 ⁻⁴	1 × 10 ⁻⁴
1	0.8	l	Oil capacity		qt	1.06	0.85
0.37	0.37	kW	Motor rating		hp	1/2	3/4
1500	1500	RPM nominal				1800	1800
220 V/50 Hz		1 ph	Electrical rating		1 Ø	115-230 V/60 Hz	
220-380 V/50 Hz		3 ph			3 Ø	230-460 V/60 Hz	
25	25	NW	Inlet/Exhaust flanges		NW	25	25
27/24	28/22	kg	1 Ph/3 Ph Weight		lb	48/41	56/51
59/53	62/48	lb	1 Ø/3 Ø		kg	21.7/18.6	25.3/23

* Partial pressure measurement according to PNEUROP specifications.