



Alcatel ACT-200TH, ACT-600TH

Technical Specifications

Characteristics	Unit	ACT 20X TH
Single-phase voltage	V	100 - 240
- voltage	Hz	50/60
- frequency	VA	250
- power max.		
Weight	kg (lbs)	2.8 (6.2)
Maximum leakage current	mA	< 10
Dimensions HxLxP)	mm (inch)	128.4 x 107 x 258 - (5.0 x 4.2 x 10.15) - 1/4 Rack 19"
Storage temperature	°C	- 15 < T < + 70
Sound level	dB(A)	< 70
W.E.E.E. (2002/96/CE)		in compliance
R.O.H.S (2002/95/CE)		in compliance



Controller	Pump
ACT 600 TH	ATH 300

Sophisticated pump monitoring

Display of:

- Rotational speed
- Pump current consumption
- Pump and controller temperature
- Total running time
- Pump fault detection
- Diagnostic mode with last ten alarm codes

Control of:

- Rotational speed
- Venting
- Auto start
- Start delay
- Maintenance schedule

Multiple interfaces

- PC/PLC controlled processes RS 232/R5485 (configurable)

Remote control

Inputs:

- Remote start/stop
- Remote stand-by
- External safety

Outputs:

- Pump starting
- Pump at speed
- Stand-by on
- Vent valve on/off
- Power supply for air cooling kit
- Selectable 0 - 10 Volts output (speed/pump current/temperatures)

