



PROVAC

SALES

PHONE: 831-462-8900

FAX: 831-462-3536

WWW.PROVAC.COM

Seiko Seiki SCU-300

Technical Specifications

| Item | | Specifications | |
|--|------------------------|---|-----|
| Input voltage | V AC | 200±10%, 220±10%, 240±10%, 100±10%, 110±10%, 120±10% (Depends on voltage spec.) | |
| Input power | At start: | VA | 500 |
| | Under rated operation: | VA | 150 |
| Input frequency | Hz | 50/60±2 | |
| Input phase | | Single phase | |
| Motor drive system | | 3-phase transistor-inverter | |
| Output voltage or less rated operation (3-phase) | V AC | 45 | |
| Output frequency or less rated operation | Hz | 800 | |
| Ambient temperature range | °C | 0 to 40 | |
| Storage temperature range | °C | - 25 to + 55 (excluding a battery) | |
| Battery storage temperature range | °C | - 20 to + 40 | |
| Weight | kg | 27 | |
| Dimensions | mm | W482.6 × H132.6 × D473 | |
| Battery used | | 12 V 7 Ah x 2 (Japan Storage Battery Co., Ltd./Small-Sized Sealed Lead-Acid Battery/PORTALAC series PE12V7F1) | |

Dimensions

