



# PROVAC

## SALES

PHONE: 831-462-8900

FAX: 831-462-3536

WWW.PROVAC.COM

## Leybold TD-20

### Technical Specifications

Mains connection	100 to 240 V AC -15%/+10%, 50/60 Hz
Power consumption tolerance including options	< 500 VA
Power consumption of the TURBOVAC	< 400 VA
Power output (motor)	
Nominal voltage	47 V
Motor current limitation	
Acceleration (max. 10 min.)	5 A
Continuous operation	3.5 A
Frequency	0 to 835 Hz

#### **TURBOVAC speed ratings**

TURBOVAC 151	49,980 min <sup>-1</sup>
TURBOVAC 361	45,000 min <sup>-1</sup>
TURBOVAC 600	36,000 min <sup>-1</sup>
TURBOVAC 1000	36,000 min <sup>-1</sup>
TURBOVAC 1100	30,000 min <sup>-1</sup>

Ambient temperature	0-45 °C
Storage temperature	-25 °C...+70 °C
Relative air humidity	5 to 85 % (non-condensing)
Type of protection to EN 6059	IP 20
Electrical safety to EN 61010-1	
Interference radiation to 61326-1	Class A
EMC to IEC 801-2	Severity 2
Dimensions	1/2 19", 3HU
Weight	4 kg



# PROVAC

## SALES

PHONE: 831-462-8900

FAX: 831-462-3536

WWW.PROVAC.COM

## Leybold TD-20 Dimensions

