

Linear Dec Four Way Fall - Technical Data

Thickness	All 22mm in height					
Handing	Universal (not handed)					
Sizes Available	1200 x 900 AD4L1290	900 x 900 AD4L9090	1000 x 1000 AD4L1010	1200 x 1200 AD4L1212	1400 x 900 AD4L1490	1600 x 900 AD4L1690
Waste outlet position	Off centre by 83mm - see drawings, 220mm from back edge					
Trap Size	Impey Universal Drain System - 50mm water seal					
Waste options	Horizontal 43mm outlet, Vertical 43mm or 110mm outlet					
Features	Creates reliable and consistent gradient for wet floor showers. Easy installation, no special skills required. Fully removable trap for easy cleaning. Height adjustable tiling frame - catering for different thickness tiles. Drain outlet position is adjustable to avoid joists or other obstructions.					
Construction	Multi Layer GRP with solid core and durable Polyester Gel outer surface					
Installation	Only suitable for tiled floor finishes. Must be fully supported on the underside by minimum 18mm thickness plywood. Must be installed with a suitable waterproofing floor membrane (Impey Waterguard recommended)					
Supplied with	Linear Drain (600mm or 800mm depending on Dec size). Fixing screws and full installation guide. (Drain available in a choice of finishes)					
Flow rates	Approximately 40 l/min. Test conducted on 400mm drain with 10mm tile thickness (tested in accordance with BS 274-1 and 2:2002).					
Weight (approx.)	AD4L1290 20kg	AD4L9090 15kg	AD4L1010 22kg	AD4L1212 28kg	AD4L1490 23kg	AD4L1690 26kg