

Linear Dec Three Way Fall - Technical Data

Thickness	All 22mm in height				
Handing	Universal (not handed)				
Sizes Available	1200 x 900 AD3LI290	1500 x 800 AD3LI580	1500 x 900 AD3LI590	1800 x 800 AD3LI880	1800 x 900 AD3LI890
Waste outlet position	Off centre by 83mm - see drawings				
Trap Size	Impey Universal Drain System - 50mm water seal				
Waste options	Horizontal 43mm outlet, Vertical 43mm or 110mm outlet				
Features	Creates reliable and consistent gradient for wet floor showers. Easy installation, no special skills required. Fully removable trap for easy cleaning. Height adjustable tiling frame - catering for different thickness tiles. Drain outlet position is adjustable to avoid joists or other obstructions.				
Construction	Multi Layer GRP with solid core and durable Polyester Gel outer surface				
Installation	Only suitable for tiled floor finishes. Must be fully supported on the underside by minimum 18mm thickness plywood. Must be installed with a suitable waterproofing floor membrane (Impey Waterguard recommended).				
Supplied with	Linear Drain (600mm or 800mm depending on Dec size). Fixing screws and full installation guide. (Drain available in a choice of finishes)				
Flow rates	Approximately 40 l/min. Test conducted on 400mm drain with 10mm tile thickness (tested in accordance with BS 274-1 and 2:2002).				
Weight (approx.)	AD3LI290 20kg	AD3LI580 23kg	AD3LI590 24kg	AD3LI880 28kg	AD3LI890 28kg