

900/1400 SERIES



PRESSURE WASHERS / SINCE 1970

FEATURES

4.0 - 5.0 GPM @ 2000 to 3000 PSI

208V or 230V, 1PH; 208V, 230V, 460V or 575V, 3PH

HOT WATER

ELECTRIC

BELT DRIVE

Locking lid prevents accidental removal of both panels around the belt and pulley

Pressure relief valve protects the machine and user from thermal expansion

Auto-tensioning system maintains belt tension on the pump with a torsion bar for precise tension adjustment

Triple banded belt for more efficient power transmission

Adjustable upstream detergent injection ensures high-pressure sudsing for better cleaning

Sleek side and front removable **panels** provide easy access to the entire washer for service and maintenance



Float tank helps maintain constant water pressure and flow while helping to prevent sediment from entering the machine's components

Upright, vertical coil with 1/2-inch schedule 80 pipe is wrapped with a thick foil blanket insulation, delivering high efficiency and maintains constant temperature using Natural Gas or LP Gas

Hotsy-designed Triplex pumps carry a 7-year limited warranty

Concealed but accessible **Thermostat**

50-ft. length of high-pressure hose for easy cleaning in a large working area and **insulated Hotsy trigger gun and insulated wand** with ergonomic, adjustable side handle



Programmable Smart Control Automation provides complete control over the machine's runtime, auto start/stop and time-delay shutdown functionality.

OPTIONS FOR 900/1400 SERIES

Remote Controls for startup, shutdown

8" Gas-Fired Draft Diverter - for natural draft burner operation; prevents downward/upward air affecting burner efficiency

Water Inlet Solenoid - prohibits water flow to float tank during idle

Soap Solenoid - use with remote station for on/off detergent control

U.S. Design Patent No. 740,501 S

HOTSY.COM THE BRAND THE PROS USE

900 / 1400 SERIES

Hot-Water **ELECTRIC** Models

STATIONARY PRESSURE WASHERS FOR HEAVY-DUTY CLEANING.

■ NG-Fired or LP-Fired ■ 4.0 to 5.0 GPM @ 2000 to 3000 PSI ■ Hotsy Triplex Pump with 7-yr warranty

MODEL	PART NO.	GPM	PSI	HP	MOTOR RPM	VOLT/PH	AMPS	FUEL	BTU/HR	PUMP MODEL	DIMENSIONS (LXWXH)	SHIP WT (LBS)
921P	1.109-948.0	4.0	2300	6.2	3450	208/1	32	LP	364,835	HM4030R.3	47.5"x21"x51"	700
921N	1.109-691.0	4.0	2300	6.2	3450	208/1	32	NG	364,835	HM4030R.3	47.5"x21"x51"	700
926P	1.109-949.0	4.0	2000	5	1800	575/3	7	LP	364,835	HM4030R.3	47.5"x21"x51"	660
926N	1.109-692.0	4.0	2000	5	1800	575/3	7	NG	364,835	HM4030R.3	47.5"x21"x51"	660
942P	1.109-693.0	4.0	2000	5	1725	208/3	18	LP	360,997	HM4030R.3	47.5"x21"x51"	590
942N	1.109-694.0	4.0	2000	5	1725	208/3	18	NG	364,835	HM4030R.3	47.5"x21"x51"	655
943P	1.109-695.0	4.0	2000	5	1725	230/1	25	LP	360,997	HM4030R.3	47.5"x21"x51"	685
943N	1.109-696.0	4.0	2000	5	1725	230/1	25	NG	364,835	HM4030R.3	47.5"x21"x51"	685
944P	1.109-697.0	4.0	2000	5	1725	230/3	16	LP	360,997	HM4030R.3	47.5"x21"x51"	580
944N	1.109-698.0	4.0	2000	5	1725	230/3	16	NG	364,835	HM4030R.3	47.5"x21"x51"	680
945P	1.109-699.0	4.0	2000	5	1725	460/3	8	LP	360,997	HM4030R.3	47.5"x21"x51"	585
945N	1.109-700.0	4.0	2000	5	1725	460/3	8	NG	364,835	HM4030R.3	47.5"x21"x51"	670
1451P	1.109-950.0	4.0	3000	8.2	3450	208/1	39	LP	364,835	HM4030R.3	47.5"x21"x51"	730
1451N	1.109-701.0	4.0	3000	8.2	3450	208/1	39	NG	364,835	HM4030R.3	47.5"x21"x51"	730
1452P	1.109-702.0	4.0	3000	7.5	1725	208/3	24	LP	360,997	HM4030R.3	47.5"x21"x51"	625
1452N	1.109-703.0	4.0	3000	7.5	1725	208/3	24	NG	364,835	HM4030R.3	47.5"x21"x51"	625
1453P	1.109-704.0	4.0	3000	7.5	1725	230/1	34	LP	360,997	HM4030R.3	47.5"x21"x51"	735
1453N	1.109-705.0	4.0	3000	7.5	1725	230/1	34	NG	364,835	HM4030R.3	47.5"x21"x51"	735
1454P	1.109-706.0	4.0	3000	7.5	1725	230/3	24	LP	360,997	HM4030R.3	47.5"x21"x51"	625
1454N	1.109-707.0	4.0	3000	7.5	1725	230/3	24	NG	364,835	HM4030R.3	47.5"x21"x51"	700
1455P	1.109-708.0	4.0	3000	7.5	1725	460/3	12	LP	360,997	HM4030R.3	47.5"x21"x51"	630
1455N	1.109-709.0	4.0	3000	7.5	1725	460/3	12	NG	364,835	HM4030R.3	47.5"x21"x51"	780
1456P	1.109-951.0	4.0	3000	8.2	3450	575/3	10	LP	364,835	HM4030R.3	47.5"x21"x51"	621
1456N	1.109-710.0	4.0	3000	8.2	3450	575/3	10	NG	364,835	HM4030R.3	47.5"x21"x51"	621
1473P	1.109-711.0	5.0	3000	10	1725	230/1	42	LP	378,617	HM4035R.3	47.5"x21"x51"	735
1473N	1.109-713.0	5.0	3000	10	1725	230/1	42	NG	390,025	HM4035R.3	47.5"x21"x51"	735
1474P	1.109-712.0	5.0	3000	10	1770	230/3	29	LP	378,617	HM4035R.3	47.5"x21"x51"	740
1474N	1.109-714.0	5.0	3000	10	1770	230/3	29	NG	390,025	HM4035R.3	47.5"x21"x51"	740
1475P	1.109-952.0	5.0	3000	10	1725	208/3	34	LP	378,617	HM4030R.3	47.5"x21"x51"	740
1475N	1.109-953.0	5.0	3000	10	1725	208/3	34	NG	378,617	HM4030R.3	47.5"x21"x51"	740


* includes connectors and flue outlet

DETERGENTS



To clean like a pro, you need to include detergents. Hotsy offers a full line of detergents for cleaning grease, dirt, road grime, aluminum, sanitation and so much more. Our detergents help you clean faster and save money.

PARTS & ACCESSORIES



Clean faster and more efficiently with pressure washer accessories like flat surface cleaners and turbo nozzles.

SERVICE



Hotsy factory-trained technicians keep your equipment running with on-site or in shop maintenance and tune-ups. Plus, we repair all brands.



The Pressure Washer The Pros Use.
EST. 1970

HOTSY.COM

Tel: 800.525.1976

Fax: 888.880.9631

Email: info@hotsy.com

Distributed by:

Specifications & product descriptions subject to change without notice. Hotsy's manufacturing facilities have established and apply a quality and environmental management system to be ISO 9001:2008 and ISO 14001:2001 certified.

© 2022 Kärcher North America

NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We meet the CETA testing specs for machine performance at $\pm 10\%$ and in some cases are tighter within $\pm 5\%$ of listed specifications.

P/N HOT_900-1400 Effective 09/22