# LEGEND LX & LEGEND LX SUPREME A Q U A L U N G° LEGEND TWILIGHT, LEGEND LUX



RELEASE DATE: LEGEND LX (& SUPREME VERSION), LEGEND LUX: JANUARY 2012 - LEGEND TWILIGHT: JANUARY 2013















# **FEATURES**

1st stage
-----------

1st stage technology Diaphragm, over-balanced

Mechanism T-shaped

Wet chamber Legend version Wet/dry chamber and on Legend Supreme version

300 bar on DIN version

Maximum working pressure 232 bar on yoke version

**ACD** system Yes

**Number of HP ports** 2 (7/16" UNF)

Number of MP ports 4 (3/8" UNF)

8,5 bar  $\pm 0,5$  bar on Legend version Average pressure

1500 l/min (53,0 cubic feet/min) Airflow (surface, hose)

with HP = 200 bar

Legend LX: Brass with multi-layer

chrome

egend LX Supreme: satin finish

Legend LUX: Black PVD brass

**Protector** 

Insert seat, spring Stainless steel

**Conical filter** Nickel-plated bronze

**O-Rings EPDM** 

# 2<sup>nd</sup> stage

**Body** 

2<sup>nd</sup> stage technology **Balanced** 

Mechanism Downstream valve

2,5 à 3,5 mbar in Legend LX version **Cracking effort** 

3.3 to 4.3 mbar in Legend Supreme version

MBS patented adjustment Yes

Housing, exhaust diffuser ABS-PC

Rubber overmoulded PC Cover

Mouthpiece, exhaust valve, diaphragm, valve,

lip shield (Supreme version)


Adjustable seat

Nickel-plated bronze

Silicone

# **Breathing Performance**

Optimal breathing work W = 0.70 J/Litre, with a 62.5 l/min (2.21 cubic feet/min) breathing cycle, at a depth of 50 m (164 ft) and with 50 bar working pressure.



Weight	In grams	In pounds
Yoke	1230	2,71
DIN	1010	2,23
HP Yoke	885	1,95
HP DIN	665	1,47
LP	210	0,46
Yoke Supreme	1240	2,73
DIN Supreme	1015	2,24
HP Yoke Supreme	890	1,96
HP DIN Supreme	665	1,47
LP Supreme	220	0,48

#### Hose

Braided hose

Length: black = 730 mm (2,39 ft)

#### Certification

Certification EN250A for water > 10°C (50°F) (version Legend LX)

Certification EN250A for cold water (< 10°C (50°F)) (version Legend LX Supreme)

# **Nitrox Compatibility**

40 % O2 max. on yoke ou DIN version outside EU

Contents	
Regulator box	Legend LX + instructions
Twilight Regulator box	Legend Twilight + instructions + Women regulator bag
LUX Regulator box	Legend LUX + instructions + Legend LUX regulator bag
Regulator pack box	Legend LX + Octopus + instructions

Packaging	In centimetres (I x h x p)	In inches (I x h x p)
Regulator box	35 x 9,5 x 18	13,8 x 3,5 x 7,1
Regulator pack box	35 x 11 x 23,5	13,8 x 4,3 x 9,0

# **PRODUCT BENEFITS**

## 1st stage

#### ACD

Patented ACD system protects the regulator inner mechanism from the ingress of water and particles

#### **Dry Chamber**

- Enables over-balancing
- Helps withstand icing
- Keeps internal components clean and dry

#### DIN and yoke handwheel

Triangular and bi-material with «Soft Grip» surface for better grip on assembly and disassembly.

#### Yoke handwheel open

Avoids water retention.

#### Anti-dust cap adjoining regulator body

Protects the connection and the ACD system against impacts. Valid for both the DIN and yoke versions.

#### MP and HP ports

MP and HP ports perfectly positioned enabling ideal orientation of the hoses.

#### Aqua Flex braided hose (with two protectors)

- Flexible and light, only 135g (0.3lb)
- Enhances mouth comfort
- Makes storage easier

# 2<sup>nd</sup> stage

#### Comfobite mouthpiece

Mouthpiece with bridge that fits across the upper palate (patented system): reduces jaw fatigue.

#### Special women's comfobite mouthpiece

(for Legend Twilight and Legend Twilight Supreme) Small mouthpiece with bridge that fits across the upper palate (patented system): reduces jaw fatique.

#### Removable and reusable collar

Mouthpieces can be changed quickly without any tools required.

#### Overmoulded cover

- Controls the regulator purging through the firm stop of the movement of the cover
- Easy purging of the regulator thanks to the wide surface
- Smart look thanks to the bright polycarbonate

# Radial vents enabling water to flow on the diaphragm

Prevents continuous flow when diving in currents

#### Whiskers

Exhaust diffuser oriented to ensure optimal visibility in swimming position and canalisation of expired gas.

#### Exhaust diffuser in the mouthpiece tube

- Channels airflow evenly in the mouthpiece while breathing in
- Two-material exhaust diffuser reduces its thickness and reduces exhaling effort

#### Closing system

- Enables constraints in the housing to be eliminated (no threading or tightening)
- Enables the cover to be indexed

#### Heat exchanger

Allows to evacuate the frigories created by the air release (patented system).

## MBS (Master Breathing System)

2 functions in 1: adjustment button combined with sensitivity and Venturi effect to master breathing effort. Quick adjustment by turning the knob just once. Made with two materials. Soft surface makes gripping easier.

#### **Legend LUX version**

Black and pink gold PVD treatment on the metal parts. This treatment increases abrasion resistance

# **PRODUCT REFERENCES, ACCESSORIES & KITS**

Legend LX ACD 129620	EAN	3661666049924	
	129020	UPC	846713017719
Legend LX ACD DIN	420420	EAN	3661666049931
	129630	UPC	846713017733
Legend LX Supreme ACD	120600	EAN	3661666049962
	129680	UPC	846713017818
	129690	EAN	3661666049979
Legend LX Supreme ACD DIN	129690	UPC	846713017825
Legend LX ACD Twilight	129770	EAN	3661666103541
		UPC	846713064379
Legend LX Supreme ACD DIN Twilight	129780	EAN	3661666103558
		UPC	846713064386
Legend LUX ACD 12964	120640	EAN	3661666051910
	129040	UPC	846713018549
Laward LUV Curvers ACD DIN	129710	EAN	3661666051941
Legend LUX Supreme ACD DIN		UPC	846713018570
Legend LX ACD HP	129635	EAN	3661666050012
		UPC	846713017740
Legend LX Supreme ACD HP	129645	EAN	3661666050029
		UPC	846713017757
Legend LX Supreme ACD HP	129745	EAN	3661666071123
		UPC	846713034952

HP Legend LX Supreme ACD DIN	129755	EAN	3661666071130
		UPC	846713034976
Legend LX LP		EAN	3661666050043
	129655	UPC	846713017764
1 1 V C 1 D	129675	EAN	3661666050067
Legend LX Supreme LP	1290/5	UPC	846713017801
Aqua Flex 3/8" MP 0.70m black	129807	EAN	3661666149747
hose with 2 protectors	129807	UPC	888183000037
Over-balanced diaphragm mainte-	120017	EAN	3661666345040
nance kit	128017	UPC	888183197980
Balanced LP maintenance kit	128019	EAN	3661666345064
		UPC	888183198000
Post-2012 yoke/DIN Legend 2 ACD conversion kit	129021	EAN	3661666107280
		UPC	846713065390
Pre-2012 yoke/DIN Legend 2 conversion kit 1:	129803	EAN	3661666072816
		UPC	846713035294
Yoke/DIN 300B Legend conversion kit	129015	EAN	3661666008303
		UPC	846713034907
Pre-2012 Legend/Legend ACD conversion kit	129226	EAN	3661666008280
Pre-2012 Legend DIN/ Legend ACD DIN conversion kit	129227	EAN	3661666008297