

● Electric guillotine shears: CGS

The CGS is perfectly designed to meet the business requirements for thin sheet metal work, as well as zinc, metal construction, maintenance, professional education, etc.

Machine sizes available: 1 m, 1.5 m, 2 m, 2.5 m and 3 m

Technical advantages

- Back gauge with rack-and-pinion from 15 to 500 mm, counter with digital display for perfect alignment
- Extendable table front supports large sizes
- Rubber protector on automatic clamping beam for scratch-free cutting
- Slanted collecting tray returns cut sheets to the front
- Foot switch
- Monobloc blades reversible once
- 300 mm table with a 650 mm graduated squaring gauge on the left side
- Engraved tabletop, in 10 mm increments for easy and precise measuring
- Illuminated cut line indicator ①
- Cut counter with reset
- CE Conformity



Model shown
Ref. CGS2030-15

Features	CGS1030-20	CGS1530-20	CGS2030-15	CGS2530-12	CGS3030-12
Useful cutting length (mm)	1030	1530	2030	2530	3030
Capacity S235JR steel (mm) *	0,4 - 2,5	0,4 - 2,0	0,4 - 1,8	0,4 - 1,2	0,5 - 1,2
Dimensions (mm)	1340 x 1340 1240	1840 x 1340 1240	2370 x 1370 1240	2900 x 1370 1240	3370 x 1370 1240
Weight (kg)	1020	1250	1270	1446	1610
Power (kW)	2,2	2,2	2,2	2,2	2,2
Power supply **	400 V three-ph + neutral + ground	400 V three-ph + neutral + ground	400 V three-ph + neutral + ground	400 V three-ph + neutral + ground	400 V three-ph + neutral + ground
Rate (cuts / min)	26	26	26	26	26

* min.-max. ** Voltage choice to be specified upon order

● Options

- Front operated electric back gauge with 15-500 mm cutting range, adjustable to 1/10 mm, for easy precision cutting, Ref. **CGS-BAS**
- Sheet holding plate: the back gauge, manual or electric, can be equipped with a sheet holding plate for large dimensions and thin sheets, Ref. **CGS-PST** ②



Sheet holding plate