

DVS1000D

The most practical on the market!

Product **PLUS**

This model of decoiler is perfect for quickly switching materials depending on the work to be done or to feed simultaneously two machines in stationary use.

The low floor space requirement combined with the controls set up on the same side and reversible from left to right, make it decoiler which is very easy to position and to use, whatever the workshops layout.

Besides its decoiling function, the DVS1000D also enables rewinding thanks to a sheet clamp with integrated gauge, without any action on the hub expansion required.



Decoiler for 1-m wide coils

Application areas

- Roofing
- Insulation
- HVAC
- Decoiling

Advantages

- Perfectly suitable to uncoil in stationary use
- Reduces space requirement in the workshop
- Cranks with 2 functions: opening **1a** and closing the hub **1b** / rewinding **2**
- Manual brake and crank on the same side
- Controls reversible, depending on the position in the workshop
- Rewinding function without action onto the hub expander
- Uncoiling from the top or the bottom



Features DVS1000D

	DVS1000D
Maximum coil width (mm)	1 000
Maximum coil weight (kg)	1 200
Maximum outer diameter (mm)	1 000
Inside diameter of the coils (mm)	from 285 to 540
Overall dimensions (L x l x h mm)	1 760 x 1 540 x 1 380
Net weight (kg)	239
Net weight of one expanding hub (kg)	77

Standard equipment

- Floor space requirement of the frame: L.1270 x l.1335 mm
- 2 hubs for 1000-mm wide coils
- Manual expansion of the mandrel \varnothing , from \varnothing 285 to 540 mm
- Maximum outer diameter of the coil: 1000 mm

