


Model DVS1000 and DVS1250

All the controls
on the same side!

Product **PLUS**

Besides its decoiling function, the DVS1000 and DVS1250 also enable rewinding thanks to a sheet clamp with integrated gauge, without any action on the hub expansion required.



Decoilers for width of the coil 1 M and 1,25 M

Application area

- Roofing
- Insulation
- Air Duct Manufacturing
- Uncoiling

Advantages

- Cranks with 2 functions : opening **1a** and closing the hub **1b** / rewinding **2**
- Manual brake and crank on the same side
- Controls reversible, depending on the position in the workshop
- Device allowing the rewind without action on the hub expander
- Uncoiling from the top or the bottom



Features

	DVS1000	DVS1250
Maximum width of the coil (mm)	1 000	1 250
Maximum load by coil (kg)	1 200	1 000
Maximum external diameter (mm)	1 000	1 000
Internal diameter of the coil (mm)	from 285 to 540	from 285 to 540
Dimensions (L x l x h mm)	1550 x 800 x 760	1850 x 800 x 770
Net weight (kg)	126	130
Net weight of one expanding hub (kg)	77	86

Standard equipment

- 1 hub of coil largeur 1000 ou 1250 mm according to the model
- Maximum external diameter of the coil 1000 mm
- Manual mandrel expansion from Ø 285 to 540 mm
- Equipped with 4 swiveling wheels with brake
- Wheel axis mounted on ball bearings
- 2 adjustable stabilisers to balance the decoiler **3**

