

The TF 4RN separate AIR cooled wire feeder s compatible with PROMIG 400 G.DV and 400-4S DUO welding machines.

SYNERGIC


- **Synergic function** : The wire speed setting is controlled from the wire feeder.






INDUSTRIAL

- Its heavy duty construction ensures a long service life.
- Its 4 wheel drive system combined with a 50W motor ensures effective wire feeding with solid wires up to Ø 1.2 mm.

MOBILE

- Supplied with its wire feeder support to attach on the welding generator. The wire feeder can be placed on the wire feeder support or placed on the ground.
- 5m and 10m inter connection cables.




PACK TYPE : ref. 036109 (no regulator)				
	+		+	
PROMIG 400 G.DV ref. 035904		TF 4RN wire feeder ref. 061699		Connection cables 5m - 70 mm ² ref. 034839
			+	
				Earth cable 4m - Ø 50 mm ² ref. 043824
				
				Steel / Stainless steel 350A - 4m (AIR) ref. 040946

OPTIONS



Regulator 30L/min

-  041622
-  041219
-   041646

Connection cables

L.	Air	
5m	50 mm ²	034822
5m	70 mm ²	034839
10m	50 mm ²	034853
10m	70 mm ²	034860

U ₁	jeg ₁	Ø		Ø		Electro-nisk Styling	originalt utstyr	EN60974-5 (40 °C)	IP	cm/kg
		GASS	INGEN GASS	200	300					
24V	3A	0,6 - 1.2	0,9 - 1.2	✓	✓	 50W	1.0 - 1.2	270A @ 60 % 220A @ 100 %	21	60x26x51,5 / 18