PX701HDH 3,500 ANSI Lumens 1080p Projector for Home and Business



Key Features

- 3,500 ANSI Lumens with native Full HD 1080p
- Energy-efficient SuperEco+ Mode for lamp life up to 20,000hrs
- Vertical lens shift
- vColorTuner to exchange color profile and adjustment easier
- Projector software update tool to easily upgrade your functionality up to date



Product **Description**

The ViewSonic PX701HDH is a high brightness 3,500 ANSI lumens projector featuring a Full HD 1080p resolution that offers impressive visual performance in a brightly lit living room or meeting room. The projector adopts the latest lamp design to extend lamp life of up to 20,000 hours under SuperEco+ mode, effectively reducing lamp replacement and maintenance costs. A digital lens shift allows users to make adjustments by remote control, it's also compatible with the vColorTuner function for color profile exchange and adjustments. The dual HDMI inputs and USB power supply allow users to connect to a multitude of multimedia devices for gaming, movies, or a wireless dongle for wireless presentation.

1. Keypad 2. LED Indicator 3. Power Key 4. Zoom/Focus 5. Projection Lens 6. Front IR 7. Audio In/Out 8. HDMI 9. USB Type A 10. RS232 11. Kensington Lock

Visit Us – www.viewsonic.com

PX701HDH 3,500 ANSI Lumens 1080p Projector for Home and Business

/ENDOR		OTHERS	
Vendor:	Qisda		100-240V+/- 10%,
SPECIFICATION		Power Supply Voltage:	50/60Hz(AC in)
Native Resolution:	1920x1080	Power Consumption:	Normal: 300WStandby: <0.5W
DMD Type:	DC3	Operating Temperature:	0~40°C
Brightness:	3500 (ANSI Lumens)	Carton:	Brown
Contrast Ratio with SuperEco	12000:1	Net Weight:	2.59kg
Mode:		Gross Weight:	3.75kg
Display Color:	1.07 Billion Colors	Dimensions (WxDxH) with	312x222x108mm
Light Source Type:	Lamp	Adjustment Foot:	312822281001111
Light Source Life (hours) with Normal Mode:	5000	Packing Dimensions: OSD Language:	415x168x297mm English, French, Spanish, Thai, Korean, German, Italian, Russiar Swedish, Dutch, Polich
Light Source Life (hours) with SuperEco Mode:	20000		
Lamp Watt:	203W		Swedish, Dutch, Polish, Czech, T-Chinese, S-
Lens:	F=2.0-2.05, f=15.843- 17.445mm		Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese, Greek, Tota
Projection Offset:	110%+/-6%		
Throw Ratio:	1.5-1.65		23 languages
Optical Zoom:	1.1x	User Guide Language:	English, S-Chinese, T- Chinese, Indonesian, Finnish, French, Germa Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, Total
Digital Zoom:	0.8x-2.0x		
Image Size:	30"-300"		
Throw Distance:	1m- 10.96m(100"@3.32m)		
Keystone:	+/- 40° (V)		20 languages
Lens Shift V. Range:	+/- 5% (Digital)	STANDARD ACCESSORY	
Audible Noise (Normal):	31dB	Power Cord:	1
Audible Noise (Eco):	27dB	Remote Control:	1
Input Lag:	16ms	QSG:	Yes
Resolution Support:	VGA(640 x 480) to WUXGA_RB(1920 x 1200)*RB-Reduced Blanking	Warranty Card: OPTIONAL ACCESSORY	Yes (CN Only)
	480i, 480p, 576i, 576p,	Lamp/Light Source:	RLC-119
HDTV Compatibility:	720p, 1080i, 1080p	Wall/Ceiling Mount:	PJ-WMK-007
Video Compatibility:	NTSC, PAL, SECAM	Carry Bag:	PJ-CASE-008
Horizontal Frequency:	15K-102KHz		
Vertical Scan Rate:	23-120Hz		
INPUT			
HDMI:	2 (HDMI 1.4/ HDCP 1.4)		
Audio-in (3.5mm):	1		
OUTPUT			
Audio-out (3.5mm):	1		
Speaker:	10W		
USB Type A (Power):	1 (5V/1.5A)		
CONTROL			
RS232 (DB 9-pin male):	1		
USB Type A (Services):	1(share with USB A Output)		

Copyright $\ensuremath{\mathbb{C}}$ ViewSonic Corporation 2000-2022. All rights reserved.