

Key **Features**

- Ultra Fine Touch Technology offering up to 40-point touch for a pen-on-paper writing experience
- myViewBoard Whiteboard software with engaging classroom tools
- Screen share via USB-C or wirelessly via myViewBoard Display and ViewBoard Cast with Airplay and Chromecast
- Intuitive remote device control and multimedia broadcast
 with myViewBoard Manager
- Android 11 OS powered by an octacore CPU for optimized efficiency and security



Product **Description**

Designed with modern educators in mind, the ViewBoard® 50-5 Series offers an intuitive and interactive interface for a multi-user writing experience. With a single-cable USB-C for instant, worry-free connectivity, teachers can seamlessly plug-in and control their devices while continuing the lesson. Both students and educators enjoy smooth writing with Ultra Fine Touch Technology offering 40-point touch, and the dual-pen that comes in a range of colors and sizes. Rest assured you and your students' eyes are cared for and protected as the ViewBoard® 50-5 Series comes with Flicker-Free technology and an integrated TÜV certified blue light filter for all brightness levels. Fully integrated with the myViewBoard suite, the ViewBoard® 50-5 Series brings together hardware and software for a complete classroom solution. Compatible with a full line of accessories, the ViewBoard® 50-5 Series enables you to effectively teach with a variety of engaging tools.

Visit Us

www.viewsonic.com

| | https://www.vie |
|--|---|
| DISPLAY | |
| Panel Size: | 65" |
| Panel Type: | TFT LCD Module with DLED Backlight.IPS |
| Display Area (mm): | 1428.48(H) × 803.52(V) |
| Aspect Ratio: | 16:9 |
| Resolution: | UHD 3840x2160 |
| Colors: | 1.07B colors (10bit) |
| Brightness: | 350 nits (typ.) |
| Contrast Ratio: | 1200:1 (typ.) 5000:1 (DCR) |
| Response Time: | 8ms |
| Viewing Angles: | H = 178, V = 178 typ. |
| Backlight Life: | 50,000 hours (Min) |
| Surface Treatment: | Hardness: 7H, Anti-glare coating |
| Bezel: | Slim |
| Orientation: | Landscape |
| PLATFORM | |
| Processor: | ARM Cortex-A73*4 + Cortex-A53*4 |
| RAM: | 4GB |
| Storage: | 32GB |
| гоисн | |
| Type/ Tech: | Ultra Fine Touch Techology (IR |
| * | Recognition) |
| Touch Resolution: | 32768 ×32768 |
| Touch Point: | Windows: 40 points of touch, Android : 20 points of touch |
| NPUT | |
| | 2.0 x 3 (3840x2160 @60Hz, |
| HDMI: | HDCP2.2, HDMI1 with CEC/ARC) |
| RS232: | x1 |
| OPS: | x1 |
| WiFi: | x 1 module slot |
| DUTPUT | |
| HDMI: | x1 (4K@60Hz) |
| Audio: | x1 (Earphone out) |
| SPDIF: | x1 (optical) |
| LAN | |
| RJ45: | x2 |
| JSB | |
| Type A: | 2.0 x 2 3.0 x 4 |
| Type B: | x2, for touch |
| | x1 (DP 1.2, USB2.0, PD65W, |
| Type C: | Ethernet 100M) |
| SPEAKERS | |
| 12W x 2 + 16W x 1 subwoofer | |
| TOP CAMERA PLATE | |
| Yes | |
| EMBEDDED OS | |
| Android 11 | |
| BUNDLE SOFTWARE | |
| Basic Annotation Software: | myViewBoard |
| Pro Annotation Software: | myViewBoard for Windows (Embedded in Windows Slot-in PC) |
| Wireless Presentation: | vCast/myViewBoard Display App |
| SPECIAL FEATURES | |
| All-in-one USB port: | "SmartPort™ USB" to all channels. |
| Simple LAN sharing between IFP and slot-in device: | Yes |
| Light Sensor: | Yes |
| POWER | |
| Voltage: | 100-240VAC +/- 10% Wide Range |
| | |
| Consumption: | 95W(typ.), 0.5W (off) |
| ERGONOMICS | 95W(typ.), 0.5W (OII) |

OPERATING CONDITIONS

0°C to 40°C Temperature (° C): Humidity: $10\% \sim 90\%$ RH non-condensing

DIMENSIONS (W X H X D)

58.6 x 35.3 x 3.5 in / 1488 x 897 x 90 Physical (inch / mm): 65.7 x 39.8 x 8.8 in / 1669 x 1010 x 223 mm Packaging (inch / mm):

WEIGHT

89.3lb/40.5kg Net (lb / kg): Gross (lb / kg): 109.6lb/49.7kg

REGULATIONS

cTUVus, FCC/ICES003, Energy Star 8.0, EMC/CE, CB/LVD, GOST-R/EAC, UKrSEPRO, EPEAT, Mexico NOM, Mexico Energy, UKCA, UK-EEL, BSMI, BIS, LBL(Low Blue Light Certification), Flicker Free, Green BOM, RoHS, ErP-Eco, REACH, SCIP, WEEE, TPCH, Packing waste, CA65, PAIA

PACKAGE CONTENTS

- 2. Remote control with AAA battery
- 3. Touch USB cable
- 4. Touch pen x 2

(VB-PEN-009)

1. Power cord

- 5. Quick Start Guide + Compliance statement
- 6. RS232 adapter
- 7. Clamp x 5
- 8. Camera Plate
- 9. Screw x 8
- 10. HDMI cable

COMPATIBLE SLOT-IN PC

- VPC2-O series VPC2-O-B series VPC25-W33-O1-1B VPC27-W53-O1-1B VPC12-WPO-17 VPC12-WPO-18

Copyright © ViewSonic Corporation 2000-2023. All rights reserved.