

# ViewSonic® PROJECTOR LS550WHE

## Key Features

- 3rd generation LED technology with 30,000 hour lifespan
- 3,000 ANSI Lumens offering bright images in any environment
- Instant power on/off for efficient use
- 0.49 short throw ratio for minima space consumption
- 360° projection and H/V keystone for easy instalation



## Product Description

The LS550WHE is ViewSonic's first lamp-free high brightness WXGA short throw projector for business and education. Built with advanced 3rd generation LED technology, the LS550WHE provides 3,000 ANSI Lumens and eliminates frequent lamp replacement and toxic mercury for a safer and greener environment, offering a phenomenal lifespan of 30,000 hours, less power consumption, true-to-life colors with 125% Rec.709, and instant power on/off capability for efficient use. The 0.49 short throw lens provides a 100" screen from just 1.06m away, delivering exceptional space efficiency and freeing presenters from blinding lights. Installation and setup are hassle-free with 360° tilt angle projection, H/V Keystone, and 4 corner adjustment capabilities while its comprehensive LAN control eases multiple device management and is compatible with Crestron, AMX, Extron, PJ Link, ATEN, and ViewSonic's vController.



- |                  |                               |
|------------------|-------------------------------|
| 1. LED Indicator | 8. Audio Out                  |
| 2. Keypad        | 9. HDMI                       |
| 3. Power Button  | 10. USB Type A(5V/2A,Service) |
| 4. Focus Ring    | 11. LAN                       |
| 5. Lens          | 12. RS-232                    |
| 6. Front IR      |                               |
| 7. Audio In      |                               |

Visit Us  [www.viewsonic.com](http://www.viewsonic.com)

**VENDOR**

Vendor:	Qisda
---------	-------

**SPECIFICATION**

Native Resolution:	1280x800
DMD Type:	DC3
Brightness:	3000 (ANSI Lumens)
Contrast Ratio:	3000000:1
Display Color:	1.07 Billion Colors
Light Source Type:	LED
Light Source Life (hours) with Normal Mode:	up to 30000
Lamp Watt:	RGB LED
Lens:	F=2.6, f=6.9mm
Projection Offset:	110% +/-5%
Throw Ratio:	0.49
Optical Zoom:	Fixed
Digital Zoom:	0.8x-2.0x
Image Size:	60"-300"
Throw Distance:	0.63m-1.58m (87"@0.92m)
Keystone:	H: +/-40°, V: +36°/-40°
Audible Noise (Normal):	30dB
Audible Noise (Eco):	26dB
Input Lag:	16ms
Resolution Support:	VGA(640 x 480) to FullHD(1920 x 1080)
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility:	NTSC, PAL, SECAM
Horizontal Frequency:	15K-102KHz
Vertical Scan Rate:	23-120Hz
Interactive Camera:	Optional (vTouch-10s)
<b>INPUT</b>	
HDMI:	1(HDMI 1.4/ HDCP 1.4)
Audio-in (3.5mm):	1
<b>OUTPUT</b>	
Audio-out (3.5mm):	1
Speaker:	2W
USB Type A (Power):	1 (5V/2A)
<b>CONTROL</b>	
RS232 (DB 9-pin male):	1
RJ45 (LAN control):	1
USB Type A (Services):	1(share with USB A Output)

**OTHERS**

Power Supply Voltage:	100-240V+/- 10%, 50/60Hz(AC in)
Power Consumption:	Normal: 157W Standby: <0.5W
Operating Temperature:	0~40°C
Carton:	Brown
Net Weight:	2.45kg
Gross Weight:	3.55kg
Dimensions (WxDxH) with Adjustment Foot:	293x221x115mm
Packing Dimensions:	365x300x188mm
OSD Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese, Greek, Hungarian. Total 24 languages
User Guide Language:	English, S-Chinese, T-Chinese, Indonesian, Finnish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, total 20 languages
<b>STANDARD ACCESSORY</b>	
Power Cord:	1
Remote Control:	1
QSG:	Yes
Lens Cover:	Yes
Warranty Card:	Yes (CN Only)
<b>OPTIONAL ACCESSORY</b>	
Wall/Ceiling Mount:	PJ-WMK-305PJ-WMK-007
Carry Bag:	PJ-CASE-008